

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 2 E R. W. W. M.

Leonard E. Herzstein, USFS - Chris Sturman & Katie Tobel, witnesses - Oct. 2001 - C.S. File 65/40-9 & 10

Corner #4 HES 178

71 Ren #30

Found: 1 " iron pipe with 2½" brass cap established by Tracy in 1969, properly marked, firmly set in concrete, projecting 12" above ground. The remains of the orig. corner stone are now scattered on the ground. I place a 3 ft. dia. mound of stone around the iron pipe, which now projects 4".

From which the remaining original bearing trees:

8" remains of ponderosa pine stump, bears N.79°E. 14.7 ft (rec. N.75°15'E. 15.18 ft., Rase, 1916, & N.78°30'E., 15.0 ft., Dean, 1985), with scribe marks "S 178" visible on previously opened blaze.

A 18" white oak, bears N.74°45'W., 84.0 ft (rec. N.74°W., 84.48 ft., Rase, 1916, & N.74°50'W., 84.5 ft., Dean, 1985), with decayed face on a partially healed blaze.

And from which the following bearing trees marked by Tracy in 1969:

A 28" P.Pine stump, bears S.78°E. 88.1 ft (rec. S.76¼° E. 88.1 ft. Tracy, 1969, & S.78°00'E., 87.9 ft., Dean, 1985), with healed blaze.

A 36" Douglas fir, bears S.81°30'W., 76.4 feet (rec. S.83°W., 77.2 ft., Tracy, 1969, & S.81°30'W., 77.4 ft., Dean, 1985), with healed blaze.

I mark new accessories for the corner:

A steel fence post, bears S.74°30'E., 3.8 feet, projecting 3.5 feet above the ground, with Forest Service "Property Boundary" and "Land Survey Monument" signs attached.

An 8" D.Fir , bears S.52°30'E., 29.8 feet, scribed "4-178 BT" on a single blaze with a ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

A 6" diameter wood fence corner, bears N.11°15'W., 0.4 feet, projecting 4 feet above the ground, set in concrete.

Bearings are based on S.74°37'E. for the line between corners 4 and 3 per M98-20 and reported to the nearest 15 minutes. Tree measurements are to the center of the root crown. Tree diameters are at breast height.

Oct. 29, 2001 C.S. File 65/40-9

Corner #6 HES 178

Ren #32 72

Found: 1" iron pipe with 2½" brass cap established by Tracy in 1969 properly marked firmly set, projecting 18" above ground, in the remains of the original corner tree stump (size indeterminate). I place a 3-foot diameter mound of stone around the iron pipe, which now projects 14".

From which the remaining original bearing trees:

A 16" white oak stump, bears N.6°W. 38.6 ft (rec. N.5°00'W. 37.62 ft., Rase, 1916, & N.6°25'W. 38.61 ft., Dean, 1985), with no marks visible on decayed blaze.

And from which following bearing trees marked by Tracy in 1969:

An 18" D.Fir stump, bears S.19°W., 31.5 ft (rec. S.20°W., 31.8 ft. Tracy, 1969, and S.19°00'W., 31.5 ft., Dean, 1985), with healed blaze.

A 15" D.Fir stump, bears S.72°30'W., 29.8 ft (rec. S.75°W., 30.0 ft., Tracy, 1969, & S.72°30'W., 29.8 ft., Dean, 1985), with healed blaze.

I mark new accessories for the corner:

A found steel fence post, bears N.77°E., 3.6 ft., projecting 4 ft above the ground, with Forest Service "Property Boundary" and "Land Survey Monument" signs attached.

A found 6" diameter wood fence corner, bears N.85°45'E., 1.6 ft., projecting 5 ft. above the ground, set in concrete.

A 7" D.Fir, bears N.87°E., 22.7 ft., scribed "6-178 BT" on a single blaze with ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

A found 6" diameter wood fence: corner, bears S.89°15'W., 0.8 ft., projecting 5 ft. above the ground, set in concrete.

A found steel fence post, bears S.80°30'W., 3.8 ft., projecting 4 ft. above the ground, with Forest Service "Property Boundary" sign attached.

A 9" D.Fir, bears N.49°30'W., 8.5 ft., scribed "6 HES 178 BT" on a single blaze with a ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

Bearings are based on S.80°31'W. for the line between corners 6 and 5 per M98-20 and reported to the nearest 15 minutes. Tree measurements are to the center of the root crown. Tree diameters are at breast height.

Oct. 23, 2001 C.S. File 65/40-10