

Douglas County Surveyor's Record of  
Government Corners Renewed

T 265 T.S. R 2 E R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

Leonard E. Herzstein, USFS - Chris Sturman &  
Katie Tobel, witnesses - Oct. 29, 2001 -  
C.S. File 65/40-11

Corner #7 HES 178 73

Found: Orig. corner tree, now a 23" W.Oak snag with healed blaze.  
From which the remaining original bearing trees:

A roothole, bears N.67°20'E., 24.7 feet (rec. N.69°00'E., 24.42 ft., Rase, 1916, & N.67°20'E., 24.7 ft., Dean, 1985), with 15" white oak laying alongside with no marks visible.

And from which the following accessories marked by Tracy in 1969:

A 1" iron pipe, bears S.17°W., 2.0 ft. (rec. 2.0 ft., Tracy, 1969, and S.12°12'W., 2.22 ft., Dean, 1985), with 2½" brass cap firmly set, projecting 15" above a 1 ft. dia. mound of stone. I make a 3- foot dia. mound of stone around the iron pipe, which now projects 4".

A 12" D.Fir stump, bears S.45°45'W., 16.0 ft. (rec. S.47°W., 16.4 ft., Tracy, 1969 & S.44°00'W., 16.0 ft., Dean, 1985), with healed blaze.

I mark new accessories for the corner:

A 14" D.Fir, bears N. 61°E., 20.5 ft., scribed "7 BT" on a single blaze with a ¼" brass washer stamped "LS 2150" nailed to the face of the blaze.

A steel fence post, bears S.85°30'E., 2.7 ft., projecting 5 ft. above the ground, with Forest Service "Property Boundary" and "Land Survey Monument" signs attached.

A 6" dia. wood fence corner, bears S.79°W. 3.3 ft. projecting 4 feet above the ground, set in concrete.

A 13" D.Fir, bears N.01°30'W., 9.3 ft., scribed "7-178 BT" on a single blaze with a ¼" brass washer stamped "LS 2150" nailed to the face of the blaze.

Bearings are based on S.85°38'E. for the line between corners 7 and 1 per M98-20 and reported to the nearest 15 minutes. Tree measurements are to the center of the root crown. Tree diameters are at breast height. 10/29/2001 C.S. File 65/40-11

Corner 2 HES 178

74

I find a 2½" outside diameter alum. post, firmly set in concrete, flush with a 3 ft. dia., mound of stone, with a 2½" dia., magnetized alum. cap attached, properly mkd. From which the BTs mkd. by Dean in 1985: Ren # 59

A 12" W.Oak bears N.49°45'E., 311.7 ft. (95.01 m.) (rec. N.49°45'E., 311.7 ft.) with a healed blaze.

A 22" D.Fir bears S.13°00'E., 374.8 ft. (114.24 m.) (rec. S.13°00'E., 374.8 ft.) with a healed blaze.

From which I tie new accessories:

A fd. 6" dia., wood fence corner bears S.88°00'W., 0.7 ft. (0.23 m.) projecting 5 ft. above the ground, set in concrete.

A fd. telephone box bears N.33°30'W., 45.8 ft. (13.95 m.) projecting 3 ft. above the ground.

The corner is in the middle of Illahee Flats meadow under a new electric fence line.

Leonard E. Herzstein, USFS  
July - Nov. 2001  
C.S. File 65/41-1

See next PG