

Douglas County Surveyor's Record of
Government Corners Renewed

26

2E

T. S.

R. W. W. M.

75

KORE-CHAPMAN CO., EUGENE, ORE. 21881

(Ren 62)

Douglas Co.
Surveyors Office

Stephen Flaese
John Pike
3/3/2006
C.S. File
67/14-14

Corner No. 3 HES No. 93

- Found - 2½" dia., DCSO brass cap ref. mon. 3" below surface of gravel rd & at NW corner of large stone buried 6" deep We did not dig up stone used Dean's rec. of S.84°13'E., 1.60 ft. for stones position to tie in accessories.
- 18" D.Fir now 25" dia., x 5 ft. tall sawed stump healed double blaze visible, bears N.13°E., 27.1 ft. (agrees w/rec) 1960
- 28" D.Fir now 36" dia., x 3ft. tall sawed stump. No visible blazes bears S.64½°E., 26.9 ft. (Agrees w/rec M 98-27) 1959 (M 14-5)
- 20" D.Fir now 24" dia., x 6 ft. tall sawed stump, healed double blaze visible bears S.2¾°W., 6.1 ft. (agree w/rec M 98-27) 1960 BT
- SE corner of 16'x22' shingle side cabin bears N.36°W., 37.2 ft. (agrees w/rec. M98-27)
- Large buried boulder is fd close to rec. brg. & dist. No clear markings fd. (Rec. S.57¼°W., 21.1 ft.) OBO 1914
- No trace of NW BT from M14-5
- New - 24" dia., D.Fir, double blazed & scribed "3 HES 93 CS BT" bears S.41°W., 19.7 ft.
- 11" dia., W.Oak, double blazed & scribed "3 HES 93 CS BT" bears N.55°E., 74.5 ft.
- 1/2" I.D. iron pipe, buried 10" deep leans SW'ly bears N.87°W., 67.8 ft. (B&D meas. to top of IP) M14-5
- Note - Corner lies on South edge of gravel Rd. that is soon to be decommissioned.
Compass decl. 16¾°E.