

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 3E R. <sup>E</sup> W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gary L. Langlitz  
Mike Tompkins  
Karen Cheney  
County Surveyor's  
Office  
S. file 59/26

1/4 Cor. Sec. 9 and 10  
Found- 1" iron pipe, loosely set and extending 16" above grnd.,  
brass cap attached. Cap is G.L.O. set 1930. **1**  
Cap marked erroneously 1/4 cor. secs. 3 and 10.  
From which: Orig. B.T. 22" now 24" D.fir, N.44°E., 35.0 ft.  
alive and well healed.  
Orig B. T. 30" D.fir, now a 34" snag, N. 45°W., 30.4 ft., scribed  
" S9 B T " on unhealed face.  
We reset the found monument 27" in the grnd., and obliterate the erroneous  
markings on the cap. We restamp the monument to read as follows:

U. S. General Land Office Survey

T26S R3E  
CS 1976  
S9 | S10  
1/4  
1930

Marked a new bearing tree- 16" D. fir, S77 1/2°W., 35.3 ft.,  
scribed " 1/4 S9 CS BT" on a double blaze.

1/4 Corner for Secs. 33 and 34. **2**  
Found - 40" D. Fir stump, partly decomposed, open & find scribing & reverse  
"S34 BT", bears S.36°E., 17.16 ft.  
BT to the NW has been destroyed when Fish Creek Canal was built. It  
lies in borrow area.  
Orig. GLO brass cap apparently destroyed in logging operations.  
Set - 2 1/2" Brass cap on a 1" gal. I.P. stamped: County Surveyor's Office  
T26S R3E 1/4 S33 S34 1977., from found BT stump.  
Brass cap is 8 ft. east of top of borrow area cut, and 200 ft. more  
or less east of Fish Creek Canal.  
New BT's-A 58" D. Fir bears N.81°E., 36.4 ft. scribed "1/4 S34 CS BT" on a  
single blaze.  
A 11" D. Fir bears N.74 1/2°W., 298.3 ft. scribed "1/4 S33 CS BT" on  
a double blaze. This BT is approx. 25 ft. west of canal.  
Note: Declination determined at Cor Sec. 28, 27, 33 and 34. A line South  
to this corner falls 30 °E of the corner.

5/19/77

Section Corner for Secs. 28, 27, 33 and 34. **3**  
Found - Basalt stone 24"x11"x8", 6" above ground and firmly set in place.  
Marked with one notch on the South edge, three notches on the  
East edge and a "X" on top.  
A 19" Cedar bears N.63°W., 41.7 ft. with healed blaze.  
A 16" D. Fir bears N.36°E., 38.7 ft. with healed blaze.  
A 28" D. Fir bears S.14°W., 41.2 ft. with healed blaze.  
A 9" D. Fir stump bears S.43 1/2°E., 35.8 ft. with healed blaze.  
Set - 2 1/2" Brass cap on 1" Gal. I.P. set 4" above ground surface and  
marked: County Surveyors Office T26S R3E S28 S27 S33 S34 1977.  
New BT's- A 8" Hemlock bears S.11°E., 17.2 ft. scribed "T26S R3E S34 CS BT"  
on a double blaze.  
Note: Corner lies 500 ft. East of F.S. Road No. 260 in a partial cut unit.  
5/12/77

1/4 Corner for Secs. 13 and 24.  
Found - Orig. brass cap set in 1930 has been destroyed by logging operations.  
Orig. 30" now 34" D. Fir stump bears N.48°E., 58.08 ft. Open & find  
scribing & reverse "BT".  
Orig. Pine to the SW has been destroyed by road construction.  
Set - Using the orig. Fir BT stump as reference, I SET a 2 1/2" brass cap  
on a 1" I.P. stamped County Surveyors Office T26S R3E 1/4 S13  
S 24 1978.  
BT's - A 25" D. Fir bears N.14°E., 80.1 ft. scribed "1/4 S13 CS BT" on  
a double blaze.  
A 9" Red Fir bears S.35°30'W., 108.3 ft. scribed "1/4 S24 CS BT" on  
a double blaze. This UT is across road #2687. (on south side)  
Placed BT signs on both trees. Corner is 30 ft. North of F.S. Rd. #2678.  
5/11/78

Dennis Gaylor, U.S.F.S.  
Deputy, Doug. Co. Surveyors Office  
Witnesses: Walter Barton Dave Williams  
Joel Sherriff  
May 12-15, 1977  
C.S. 59/34

Dennis Gaylor  
USFS, Deputy with  
Douglas Co. Surveyors  
Office  
Randal Lopez  
May 11, 1978  
C.S. 60/11