

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 3 E R. W. W. M.

NOKE-CHAPMAN CO. EUGENE, ORE. 21881

5

Section corner for Secs. 11, 12, 13 and 14.

REFERENCED OUT CORNER ONLY - - - See Vol. 23 Pg. 9758 GLO notes

Found - A 2" iron pipe with a U.S.C & G.S. brass cap firmly set and protruding approx. 0.5 ft. from ground, cap is mkd. T26S R3E S11 S12 S14 S13 1930.

An orig. 26" Cedar bearing N.40°E., 81.2 ft. is gone.

An orig. Fir 28" now 36" bears S.59°E., 83.8 ft..

An orig. Fir 26" now 36" bears S.58°W., 10.6 ft.

An orig. 36" now 46" Fir bears N.14°W., 6.6 ft.

Because monument as described before is endangered by planned road work, corner is referenced out as follows:

- Set - P.K. nail is set in the root crown of a distant tree and a 5/8" iron rod with alum. cap is set as a P.O.T. beyond the P.K. nail. This is done in the NW and NE quadrants.
- A P.K. nail set in root crown at base of a 14" D. Fir bears N.50°W., 128.84 ft., Tree is marked with unscribed blaze and DCSO BT tag.
- A 5/8" by 30" long iron rod with a center punched 1" diam. DCSO alum. cap bears N.50°W., 161.94 ft. Rod and cap are firmly set and protrude approx. 4" above ground
- A P.K. nail set in the root crown of a 34" D. Fir bears N. 1 1/2°E., 120.43 ft. tree is marked with an unscribed blaze and a DCSO BT tag.
- A 5/8" by 30" iron rod with a center punched 1" DCSO alum. cap bears N. 1 1/2°E., 159.58 ft., rod and cap are firmly set and protrude approx 5" above ground.

Change Visited By County 6/19/83 One ok - Not Disturbed. J.R.

Stephen J. Fluse
Doug. Co. Surveyors
Office
T. Plouff
S. Means
A. Stephens
May 22, 1980
C.S. 59/30
6/9/83 62/9

6

Sec. corner common to Sec's. 12, 13 and Sec's. 7, & 18, T.26-4E.

Found - Orig. 1930 Brass Cap firmly set, protruding 12" out of the ground, properly marked, with mound of stone at West side of cap, 3-ft. dia. at base, & 1-ft. dia. at top, 2-ft. high.

BT's- No trees were marked on orig. survey.

- New BT's- 14" Fir bears S.48°W., 8.0-ft., scribed "T26S R3E. S13 CS BT" in double blaze.
- 29" Fir bears N.50°W., 31.3-ft., scribed "T26S R3E S12 CS BT" in BARK.
- 24" Fir bears N.12°E., 16.5-ft., scribed "T26S R4E S7 CS BT" in BARK.
- 11" Fir bears S.44°E., 18.2-ft., scribed "T26S R4E S18 CS BT" in double blaze.

9/24/81

Gregory E. Quibell
Deputy Doug. County
Surveyors Office
Debbie Stewart, wit.
Sept. 24, 1981
C.S. 61 / 27

7

1/4 Corner for Sections 29 and 30

Found - Orig. 8" fir, now 9" for 1/4 corner. Good scar on east & west sides as per orig. notes. Tree is alive

Orig. 26" now 35" fir with good scar bears S.70 1/2°E., 77.9 ft. (Rec. S.69°E.)

Orig. 16" now 18" fir with good scar bears N.60°W., 24.4 ft. (Rec. N.56°W.)

New Accessories:

- Set spike stamped "B01" in top of 30" fir stump bears N.44°W., 22.1 ft. (to spike)
- Set spike stamped "B02" in top of 19" fir stump bears S.14 1/2°W., 23.4 ft. (to spike).

Sketch and location map in C.S. file.

Gregory Quibell
Deputy, Doug. Co
Surveyors Off.
John Powell
June 4, 1982
C.S. 61/36

6/4/82