

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 S T. S. R 3 E R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE., 97401

Kristian DeGroot,
PLS 1941
For: USFS
Crew Les Fanning,
Matt Dixon,
& Aaron Fanning
March 1998 -
C.S. File 65/20-8,9,12

1/4 Cor. Sec. 35 & Sec. 2, T26-3E 8
Found - Original corner tree, a 35" Fir snag, ± 22 ft. tall with healed faces on the
North and South sides.
27" Fir bears N.8°E., 53.5 ft. with a healed blaze. 1931
34" Fir snag ± 20 ft. tall bears S.15°E., 34.0 ft. with a healed blaze (Rec.
S.21°E.) 1931
Set - 2½"x30" alum. pipe, 24" in the ground in a 48" dia. mound of stone, base to
top with a 3 ¼" alum. cap stamped:
U.S. DEPT. OF AGRICULTURE FOREST SERVICE
T26S R3E
¼ S2 RM
N.86°22'W
15.00 FT.
bears S.86°22'E., 15.00 ft.
10" Fir bears S.10°W., 18.0 ft. scribed "¼ S2 BT" with a brass washer
stamped "PLS 1941" nailed into the lower blaze
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and
"LAND SURVEY MONUMENT" signs to all BTs.

Cor. Secs. 35 & 36; & Secs. 1 & 2, T26-3E 9
Found - 2" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2½"
brass cap properly stamped. GLO 1930
34" Fir bears N.10°E., 50.8 ft. with a healed blaze. 1931
22" Fir bears S.18°E., 150.5 ft. with illegible scribe marks visible on a
partially healed blaze.
A root hole bears S.55°W., 30.4 ft.
12" Fir snag bears N.30°W., 6.6 ft. with illegible scribe marks visible on a
partially healed blaze.
New BTs - 12" Fir bears N.61°W., 19.4 ft. scribed: "T25¼S R3E S35 BT" on a double
blaze with a brass washer stamped "PLS 1941" nailed into the lower
face.
13" Fir bears S.17°W., 6.8 ft. scribed: "T26S R3E S2 BT" on a double blaze
with a brass washer stamped "PLS 1941" nailed into the lower face.
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and
"LAND SURVEY MONUMENT" signs to all BTs.

Cor. Secs. 3, 4, 9, & 10 10
Found - The original 16"x16"x30" corner stone in place with an "X" chiseled on top
5 notches on the south and 3 notches on the east edges. GLO 1931
37" Hemlock bears N.21°E., 31.7 ft. with a healed blaze.
50" Fir bears S.31°E., 27.1 ft. with a healed blaze.
47" Fir bears S.79°W., 21.1 ft. with a healed blaze.
53" Fir bears N.29°W., 31.0 ft. with a healed blaze.
Set - I remove the 16"x16"x30" corner stone and at the exact corner point I set a
2½"x30" alum. pipe, 8" in the ground in a 48" dia. mound of stone,
base to top with a 3 ¼" alum. cap stamped:
U.S. DEPT. OF AGRICULTURE FOREST SERVICE
T26S R3E
S4 | S3
S9 | S10
PLS 1941
1997
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and
"LAND SURVEY MONUMENT" signs to all BTs.