

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26 S T. S. R 3 E R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE., 91801

Kristian DeGroot,  
PLS 1941

For: USFS

Crew Les Fanning,  
Matt Dixon,  
& Aaron Fanning  
March 1998 -

C.S. File 65/20 -  
12th July 1998

1/4 Cor. Secs. 8 & 9

11

Found - 1" O.D. iron pipe, firmly set, projecting 8" above the ground with a  
2 1/2" brass cap properly stamped. GLO 1931

42" Fir bears S.38°E., 53.5 ft. w/healed blaze. (Rec. S.21°E.) 1931  
30" Fir bears N.76°W., 32.3 ft. with a healed blaze.

New - I build a stone mound, 48" dia., base to top of monument and paint a  
6" red band and BT faces red and nail USFS "BEARING  
TREE" and "LAND SURVEY MONUMENT" signs to BTs.

1/4 Cor. Secs. 9 & 10

12

Found - 1" O.D. iron pipe, firmly set, projecting 8" above the ground with a  
2 1/2" brass cap properly stamped. GLO 1930

26", fire killed, D.Fir snag bears N.44°E. 35.0 ft. w/healed blaze. 1930  
A root hole with burnt Fir remnants bears N.45°W., 30.4 ft. 1930

16" fire killed, D.Fir snag bears S.77°30'W., 35.5 ft. with a healed  
blaze. 1976 (Ren. #1)

New BOs - I build a stone mound, 48" dia. base to top of monument.

5/8"x30" iron rod, set 26" in the ground with plastic cap "BTS ENG-  
SURV" bears S.44°W., 20.0 ft. with a 6 ft. alum. post set  
alongside.

5/8"x30" iron rod, set 26" in the ground with plastic cap "BTS ENG-  
SURV" bears S.45°E., 20.0 ft. with a 6 ft. alum. post set  
alongside.

Paint a 6" red band and BT faces red and nail USFS "BEARING  
TREE" and "LAND SURVEY MONUMENT" signs to BTs.

1/4 Cor. Secs. 10 & 11

13

Found - 1" O.D. iron pipe, firmly set, projecting 10" above the ground with a  
2 1/2" brass cap properly stamped. GLO 1930

24" Fir bears S.32°E., 18.5 ft. with a healed blaze. GLO 1930

New BT - 20" D.Fir bears N.72°W., 23.3 ft. scribed "1/4 S10 BT" with a brass  
washer stamped "PLS 1941" nailed into the lower blaze.

Paint a 6" red band and BT faces red and nail USFS "BEARING  
TREE" and "LAND SURVEY MONUMENT" signs to BTs.

Cor. Secs. 10, 11, 14, & 15

14

Found - 2" O.D. iron pipe, firmly set, projecting 8" above the ground with a  
2 1/2" brass cap properly stamped. GLO 1930

43" Pine bears N.45°E., 35.0 ft. with a healed blaze. GLO 1930

38" Pine bears S.63°E., 29.0 ft. with a healed blaze. GLO 1930

34" Pine bears N.82°W., 13.2 ft. with a healed blaze. GLO 1930

A root hole bears S.25°W., 35.6 ft. GLO 1930

New - 37" Pine bears S.77°W., 94.4 ft. scribed "T26S R3E S15 BT" with a  
brass washer stamped "PLS 1941" nailed into lower blaze.

Paint a 6" red band and BT faces red and nail USFS "BEARING  
TREE" and "LAND SURVEY MONUMENT" signs to BTs.