

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 3E R. ^EW.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gary L. Langlitz
Mike Tompkins
Karen Cheney
County Surveyor's
Office
S. file 59/26

1/4 Cor. Sec. 9 and 10

Found- 1" iron pipe, loosely set and extending 16" above grnd.,
brass cap attached. Cap is G.L.O. set 1930. **1**

Cap marked erroneously 1/4 cor. secs. 3 and 10.

From which: Orig. B.T. 22" now 24" D.fir, N.44°E., 35.0 ft.
alive and well healed.

Orig B. T. 30" D.fir, now a 34" snag, N. 45°W., 30.4 ft., scribed
" S9 B T " on unhealed face.

We reset the found monument 27" in the grnd., and obliterate the erroneous
markings on the cap. We restamp the monument to read as follows:

U. S. General Land Office Survey

T26S R3E

CS 1976

S9 | S10

1/4

1930

Marked a new bearing tree- 16" D. fir, S77 1/2°W., 35.3 ft.,
scribed " 1/4 S9 CS BT" on a double blaze.

1/4 Corner for Secs. 33 and 34. **2**

Found - 40" D. Fir stump, partly decomposed, open & find scribing & reverse
"S34 BT", bears S.36°E., 17.16 ft.

BT to the NW has been destroyed when Fish Creek Canal was built. It
lies in borrow area.

Orig. GLO brass cap apparently destroyed in logging operations.

Set - 2 1/2" Brass cap on a 1" gal. I.P. stamped: County Surveyor's Office
T26S R3E 1/4 S33 S34 1977., from found BT stump.

Brass cap is 8 ft. east of top of borrow area cut, and 200 ft. more
or less east of Fish Creek Canal.

New BT's-A 58" D. Fir bears N.81°E., 36.4 ft. scribed "1/4 S34 CS BT" on a
single blaze.

A 11" D. Fir bears N.74 1/2°W., 298.3 ft. scribed "1/4 S33 CS BT" on
a double blaze. This BT is approx. 25 ft. west of canal.

Note: Declination determined at Cor Sec. 28, 27, 33 and 34. A line South
to this corner falls 30 °E of the corner.

5/19/77. **3**

Section Corner for Secs. 28, 27, 33 and 34.

Found - Basalt stone 24"x11"x8", 6" above ground and firmly set in place.

Marked with one notch on the South edge, three notches on the
East edge and a "X" on top.

A 19" Cedar bears N.63°W., 41.7 ft. with healed blaze.

A 16" D. Fir bears N.36°E., 38.7 ft. with healed blaze.

A 28" D. Fir bears S.14°W., 41.2 ft. with healed blaze.

A 9" D. Fir stump bears S.43 1/2°E., 35.8 ft. with healed blaze.

Set - 2 1/2" Brass cap on 1" Gal. I.P. set 4" above ground surface and
marked: County Surveyors Office T26S R3E S28 S27 S33 S34 1977.

New BT's- A 8" Hemlock bears S.11°E., 17.2 ft. scribed "T26S R3E S34 CS BT"
on a double blaze.

Note: Corner lies 500 ft. East of F.S. Road No. 260 in a partial cut unit.

5/12/77.

1/4 Corner for Secs. 13 and 24.

Found - Orig. brass cap set in 1930 has been destroyed by logging operations.
Orig. 30" now 34" D. Fir stump bears N.48°E., 58.08 ft. Open & find
scribing & reverse "BT".

Orig. Pine to the SW has been destroyed by road construction.

Set - Using the orig. Fir BT stump as reference, I SET a 2 1/2" brass cap
on a 1" I.P. stamped County Surveyors Office T26S R3E 1/4 S13
S 24 1978.

BT's - A 25" D. Fir bears N.14°E., 80.1 ft. scribed "1/4 S13 CS BT" on
a double blaze.

A 9" Red Fir bears S.35°30'W., 108.3 ft. scribed "1/4 S24 CS BT" on
a double blaze. This UT is across road #2687. (on south side)

Placed BT signs on both trees. Corner is 30 ft. North of F.S. Rd. #2678.

5/11/78

Dennis Gaylor, U.S.F.S.
Deputy, Doug. Co. Surveyors Office
Witnesses: Walter Barton Dave Williams
Joel Sherriff
May 12-15, 1977
C.S. 59/34

Dennis Gaylor
USFS, Deputy with
Douglas Co. Surveyors
Office
Randal Lopez
May 11, 1978
C.S. 60/11

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 3 E R. W. W. M.

NOKE-CHAPMAN CO. EUGENE, ORE. 21881

5

Section corner for Secs. 11, 12, 13 and 14.

REFERENCED OUT CORNER ONLY - - - See Vol. 23 Pg. 9758 GLO notes

Found - A 2" iron pipe with a U.S.C & G.S. brass cap firmly set and protruding approx. 0.5 ft. from ground, cap is mkd. T26S R3E S11 S12 S14 S13 1930.

An orig. 26" Cedar bearing N.40°E., 81.2 ft. is gone.

An orig. Fir 28" now 36" bears S.59°E., 83.8 ft..

An orig. Fir 26" now 36" bears S.58°W., 10.6 ft.

An orig. 36" now 46" Fir bears N.14°W., 6.6 ft.

Because monument as described before is endangered by planned road work, corner is referenced out as follows:

- Set - P.K. nail is set in the root crown of a distant tree and a 5/8" iron rod with alum. cap is set as a P.O.T. beyond the P.K. nail. This is done in the NW and NE quadrants.
- A P.K. nail set in root crown at base of a 14" D. Fir bears N.50°W., 128.84 ft., Tree is marked with unscribed blaze and DCSO BT tag.
- A 5/8" by 30" long iron rod with a center punched 1" diam. DCSO alum. cap bears N.50°W., 161.94 ft. Rod and cap are firmly set and protrude approx. 4" above ground
- A P.K. nail set in the root crown of a 34" D. Fir bears N. 1 1/2°E., 120.43 ft. tree is marked with an unscribed blaze and a DCSO BT tag.
- A 5/8" by 30" iron rod with a center punched 1" DCSO alum. cap bears N. 1 1/2°E., 159.58 ft., rod and cap are firmly set and protrude approx 5" above ground.

*Change Visited By
County 6/19/83
One ok - Not
Disturbed.
z.h.*

Stephen J. Fluse
Doug. Co. Surveyors
Office
T. Plouff
S. Means
A. Stephens
May 22, 1980
C.S. 59/30
6/9/83 62/9

6

Sec. corner common to Sec's. 12, 13 and Sec's. 7, & 18, T.26-4E.

Found - Orig. 1930 Brass Cap firmly set, protruding 12" out of the ground, properly marked, with mound of stone at West side of cap, 3-ft. dia. at base, & 1-ft. dia. at top, 2-ft. high.

BT's- No trees were marked on orig. survey.

- New BT's- 14" Fir bears S.48°W., 8.0-ft., scribed "T26S R3E. S13 CS BT" in double blaze.
- 29" Fir bears N.50°W., 31.3-ft., scribed "T26S R3E S12 CS BT" in BARK.
- 24" Fir bears N.12°E., 16.5-ft., scribed "T26S R4E S7 CS BT" in BARK.
- 11" Fir bears S.44°E., 18.2-ft., scribed "T26S R4E S18 CS BT" in double blaze.

9/24/81

Gregory E. Quibell
Deputy Doug. County
Surveyors Office
Debbie Stewart, wit.
Sept. 24, 1981
C.S. 61 / 27

7

1/4 Corner for Sections 29 and 30

Found - Orig. 8" fir, now 9" for 1/4 corner. Good scar on east & west sides as per orig. notes. Tree is alive

Orig. 26" now 35" fir with good scar bears S.70 1/2°E., 77.9 ft. (Rec. S.69°E.)

Orig. 16" now 18" fir with good scar bears N.60°W., 24.4 ft. (Rec. N.56°W.)

New Accessories:

Set spike stamped "B01" in top of 30" fir stump bears N.44°W., 22.1 ft. (to spike)

Set spike stamped "B02" in top of 19" fir stump bears S.14 1/2°W., 23.4 ft. (to spike).

Sketch and location map in C.S. file.

Gregory Quibell
Deputy, Doug. Co
Surveyors Off.
John Powell
June 4, 1982
C.S. 61/36

6/4/82

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 S T. S. R 3 E R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE., 31001

Kristian DeGroot,
PLS 1941
For: USFS
Crew Les Fanning,
Matt Dixon,
& Aaron Fanning
March 1998 -
C.S. File 65/20-8,9,12

1/4 Cor. Sec. 35 & Sec. 2, T26-3E 8
Found - Original corner tree, a 35" Fir snag, ± 22 ft. tall with healed faces on the
North and South sides.
27" Fir bears N.8°E., 53.5 ft. with a healed blaze. 1931
34" Fir snag ± 20 ft. tall bears S.15°E., 34.0 ft. with a healed blaze (Rec.
S.21°E.) 1931
Set - 2½"x30" alum. pipe, 24" in the ground in a 48" dia. mound of stone, base to
top with a 3 ¼" alum. cap stamped:
U.S. DEPT. OF AGRICULTURE FOREST SERVICE
T26S R3E
¼ S2 RM
N.86°22'W
← 15.00 FT.
bears S.86°22'E., 15.00 ft.
10" Fir bears S.10°W., 18.0 ft. scribed "¼ S2 BT" with a brass washer
stamped "PLS 1941" nailed into the lower blaze
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and
"LAND SURVEY MONUMENT" signs to all BTs.

Cor. Secs. 35 & 36; & Secs. 1 & 2, T26-3E 9
Found - 2" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2½"
brass cap properly stamped. GLO 1930
34" Fir bears N.10°E., 50.8 ft. with a healed blaze. 1931
22" Fir bears S.18°E., 150.5 ft. with illegible scribe marks visible on a
partially healed blaze.
A root hole bears S.55°W., 30.4 ft.
12" Fir snag bears N.30°W., 6.6 ft. with illegible scribe marks visible on a
partially healed blaze.
New BTs - 12" Fir bears N.61°W., 19.4 ft. scribed: "T25¼S R3E S35 BT" on a double
blaze with a brass washer stamped "PLS 1941" nailed into the lower
face.
13" Fir bears S.17°W., 6.8 ft. scribed: "T26S R3E S2 BT" on a double blaze
with a brass washer stamped "PLS 1941" nailed into the lower face.
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and
"LAND SURVEY MONUMENT" signs to all BTs.

Cor. Secs. 3, 4, 9, & 10 10
Found - The original 16"x16"x30" corner stone in place with an "X" chiseled on top
5 notches on the south and 3 notches on the east edges. GLO 1931
37" Hemlock bears N.21°E., 31.7 ft. with a healed blaze.
50" Fir bears S.31°E., 27.1 ft. with a healed blaze.
47" Fir bears S.79°W., 21.1 ft. with a healed blaze.
53" Fir bears N.29°W., 31.0 ft. with a healed blaze.
Set - I remove the 16"x16"x30" corner stone and at the exact corner point I set a
2½"x30" alum. pipe, 8" in the ground in a 48" dia. mound of stone,
base to top with a 3 ¼" alum. cap stamped:
U.S. DEPT. OF AGRICULTURE FOREST SERVICE
T26S R3E
S4 | S3
S9 | S10
PLS 1941
1997
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and
"LAND SURVEY MONUMENT" signs to all BTs.

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 S T. S. R 3 E R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE., 91801

Kristian DeGroot,
PLS 1941
For: USFS
Crew Les Fanning,
Matt Dixon,
& Aaron Fanning
March 1998 -

C.S. File 65/20 -
12th July 16

	1/4 Cor. Secs. 8 & 9	11
Found -	1" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2 1/2" brass cap properly stamped. GLO 1931 42" Fir bears S.38°E., 53.5 ft. w/healed blaze. (Rec. S.21°E.) 1931 30" Fir bears N.76°W., 32.3 ft. with a healed blaze.	
New -	I build a stone mound, 48" dia., base to top of monument and paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to BTs.	
	1/4 Cor. Secs. 9 & 10	12
Found -	1" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2 1/2" brass cap properly stamped. GLO 1930 26", fire killed, D.Fir snag bears N.44°E. 35.0 ft. w/healed blaze. 1930 A root hole with burnt Fir remnants bears N.45°W., 30.4 ft. 1930 16" fire killed, D.Fir snag bears S.77°30'W., 35.5 ft. with a healed blaze. 1976 (Ren. #1)	
New BOs -	I build a stone mound, 48" dia. base to top of monument. 5/8"x30" iron rod, set 26" in the ground with plastic cap "BTS ENG-SURV" bears S.44°W., 20.0 ft. with a 6 ft. alum. post set alongside. 5/8"x30" iron rod, set 26" in the ground with plastic cap "BTS ENG-SURV" bears S.45°E., 20.0 ft. with a 6 ft. alum. post set alongside. Paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to BTs.	
	1/4 Cor. Secs. 10 & 11	13
Found -	1" O.D. iron pipe, firmly set, projecting 10" above the ground with a 2 1/2" brass cap properly stamped. GLO 1930 24" Fir bears S.32°E., 18.5 ft. with a healed blaze. GLO 1930	
New BT -	20" D.Fir bears N.72°W., 23.3 ft. scribed "1/4 S10 BT" with a brass washer stamped "PLS 1941" nailed into the lower blaze. Paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to BTs.	
	Cor. Secs. 10, 11, 14, & 15	14
Found -	2" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2 1/2" brass cap properly stamped. GLO 1930 43" Pine bears N.45°E., 35.0 ft. with a healed blaze. GLO 1930 38" Pine bears S.63°E., 29.0 ft. with a healed blaze. GLO 1930 34" Pine bears N.82°W., 13.2 ft. with a healed blaze. GLO 1930 A root hole bears S.25°W., 35.6 ft. GLO 1930	
New -	37" Pine bears S.77°W., 94.4 ft. scribed "T26S R3E S15 BT" with a brass washer stamped "PLS 1941" nailed into lower blaze. Paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to BTs.	