

Douglas County Surveyor's Record of  
Government Corners Renewed

T 27 T. S. R 6 E R. W. W. M.

Type - C.S. 59/40-1

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner for Secs. 30 and 31.  
Found - Orig. 12" now 26" White Fir bears S.35°W., 13.2 ft. Has a healed  
blaze.  
Bearing tree to the NW is gone.  
Set - Referring to the only orig. BT remaining, I SET a 2 1/2" Brass  
cap on a 1" iron pipe stamped County Surveyors Office  
T 27 S 30 E 1/4 S30 S31 1977.  
New BT - A 27" D. Fir bears N.17°E., 13.2 ft. scribed "1/4 S30 CS BT" on  
a double blaze. Placed County BT signs on both original and  
new BT's.  
Note: Corner lies approx. 300 ft. North of Diamond Lake.

Dennis Gaylord, U.S. F. S.  
Deputy, Doug. Co. Surveyors Office  
Witness: Travis Worthen  
Sept. 1977  
C.S. 59/40

1/4 Corner for Secs. 32 and 33. CS FILE 59/40-4  
Found - Original 5" Fir BT is down. (This has been determined to be the  
SW BT for the face is less than 2" radius from the center  
of the log). Stump bears S.5°W., 7.26 ft. Scribing visible  
on double blaze. "1/4 S BT"  
The SE bearing tree is gone.  
Set - A 2 1/2" Brass cap on a 1" iron pipe stamped:  
County Surveyor's Office T27S R6E 1/4 S32 S33 1977  
B.C. set by reference to stump location of remaining orig. BT.  
New BT's - A 11" Lodgepole Pine bears S.11°E., 36.6 ft. scribed "1/4 S33  
CS BT" on a double blaze.  
A 8" Lodgepole Pine bears S.37°W., 45.7 ft. scribed "1/4 S32  
CS BT" on a double blaze. Placed County BT signs on both.

1/4 Corner for Secs. 29 and 32  
Set - 2" Iron pipe 36" long with a 2 1/2" BRASS CAP attached properly  
marked.  
BT's - An 11" Lodgepole Pine bears N.59°30'E., 36.6 ft. scribed "1/4  
S29 CS BT" on double blazes.  
An 11" Shasta Red Fir bears S.26°30'E., 62.2 ft. scribed "1/4  
S32 CS BT" on double blazes.  
Note - A diligent search of the area did not reveal any original corner  
evidence. The corner was reset by proportional measurement.

Dennis Gaylord U.S.F.S.  
Deputy, D.C. Surveyor  
Witness: B. Dorsey  
May 1980  
C.S. 61/9

1/4 Cor. Secs. 32 & 33  
Found - 2 1/2" dia., brass cap on a 1 1/2" O.D. iron pipe, protrudes 4" above  
ground, properly marked. (REN #5) 1977  
5" now nearly gone Pine remnants with scribing "1/4" found near rec.  
S.5°W., 7.3 ft. (Agrees with rec.) OBT  
SE OBT not found.  
11" now 12" dia. dead Lodge Pole Pine with an unhealed blaze  
scribing visible "1/4 S33 CS BT" bears S.11°E., 36.6 ft.  
(Agrees with rec.) 1977  
8" now 9" dia., Lodge Pole Pine with an unhealed double blaze  
scribing visible "1/4 S32 CS BT" bears S.37°W., 45.7 ft.  
(agrees with rec.) 1977  
New BTs - 8" dia., Lodge Pole Pine double blazed and scribed "1/4 S33 CS BT"  
bears S.34°E., 13.4 ft.  
7" dia., Lodge Pole Pine double blazed and scribed "1/4 S33 CS BT"  
bears N.71°E., 30.4 ft.  
4" dia., Lodge Pole Pine double blazed and scribed "X BT" bears  
N.50°W., 19.1 ft.

Douglas Co.  
Surveyors Office -  
Randall W. Smith -  
Stephen J. Flause -  
10/14/1998 - C.S.  
File 66/4-3