

Douglas County Surveyor's Record of
Government Corners Renewed

T 28 S. T. S. R 1 E. R. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

5

SE Sec. corner of Sec. 34.

- Found - Orig. GLO Brass Cap firmly set, protruding 8" out of ground,
marked T28S R1E S34 S35 T29S S3 S2 1921 .
14" Fir (Orig. 10") bears N.76°E., 18.5-ft., with well healed
blaze.
18" Fir (Orig. 14") bears S.73°E., 11.0-ft., (REC. 10.6-ft)
with well healed blaze.
8" snag (Orig. 8" Fir), 14' tall bears S.41°W., 7.9-ft., with
well healed blaze.
14" Fir (Orig. 10") bears N.60°W., 5.9-ft., with well healed
blaze.

New BT - 10" Fir bears S.21°W., 10.6-ft., scribed T29S R1E S3 CS BT
in a double blaze.

*NOTE - All BT's tagged with DCSO BT tags.

7/15/81

Gregory E. Quimby
Deputy, Douglas County
Surveyors Office
Debbie Stewart
witness
July 15, 1981
C.S. 61 / 27

6

Section Corner for Secs. 1, 2, 11 and 12.

- Found - 2" iron pipe with brass cap marked "US General Land Office 2 1
11 12 192" firmly set protruding 4 ins. out of the ground.
(1927 survey)
48" pine bears S.59°W., 25.5 ft. (Rec. S.61 1/4°W., 25.7 ft.)
with visible scribe "S11 BT".

New bearing Objects:

- A 5/8" x 30" iron rod with plastic cap "AA Surveying Service Inc."
bears N.45°E., 12.0 ft.
A 5/8" x 30" iron rod with plastic cap "AA Surveying Service Inc."
bears S.45°E., 16.7 ft.
A 5/8" x 30" iron rod with plastic cap "AA Surveying Service Inc."
bears S.45°W., 10.5 ft.
A 5/8" x 30" iron rod with plastic cap "AA Surveying Service Inc."
bears N.45°W., 13.0 ft.

10/12/84

Ronald Quimby
L.S. #1654
For: AA Survey-
ing Service
Oct. 12, 1984
C.S. 58/290