

Douglas County Surveyor's Record of
Government Corners Renewed

T. 19 S. T. S. R. 10 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Milo E.
Godfrey &
Crew
C.S. File
No. 53/66

Sections Corner to Secs. 26 - 27 - 34 - 35.
Found - Fir Snag, N.59°W. 5.3 ft., prev. opened, wood scribing visible.
42" D.Fir N.58°E. 35.6 ft., shows good scars.
36" D.Fir S.64°W. 11.9 ft., shows good scars.
36" D.Fir S. 7°E. (not S.70°W.) 12.5 ft., shows good scars.
Set - Brass Cap at Cor. Mkd: County Surveyor's T19S R10 W.

S27	S26
S34	S35

Rescribe - 36" D.Fir S.64°W. 11.9 ft. Mkd: T19S R10W s34 CS BT.
36" D.Fir S. 7°E. 12.5 ft. Mkd: T19S R10W s35 CS BT.
42" D.Fir N.58°E. 35.6 ft. Mkd: T19S R10 W s26 CS BT.

New BT: 10" Hemlock N.29°E. 90.0 ft. Mkd: T19S R10W S26 CS BT.

FD. OK 9/20/77 - U.S.F.S. - SEE C.S. 58/142 & 145-43
(FD. CAP STAMPED IN REVERSE)

Sept. 24, 1964

Corner to Sections 25 and 36, T19S R10W.

Found - 28" Doug. Fir, shows good scars.

40" Doug. Fir N.31°W. 4.0 ft., shows good scars.

38" Hemlock S.83°W. 46.9 ft., opened & found good reverse scribing.

Set - Brass Cap at base of Corner Tree (S.E. Side & Mkd:
County Surveyor's T19S R10W

S 25	S 26
S 36	S 37

Blaze & Rescribe: 40" D.Fir N.31°W. 4.0 ft. Mkd: T19S R10W S25 CS BT.

38" Hemlock S.83°W. 46.9 ft. Mkd: T19S R10W S36 CS BT.

Sept. 29, 1964

Godfrey &
Crew
C.S. File
No. 53/66

Bruce R. Rogers, Dep.
Mike Stone
June 23, 1965
C. S. File No. 53/66

Sec. Corner to Section 31, T19-10W. & Sec. 36, T19-11W.

Found - 50" Fir, now snag, S.46 1/2°W. 29.7 ft.

36" Fir, now snag, N.77 1/2°E. 19.1 ft. (See affidavits for evidence of scribing)

Set - Brass Cap at Cor. Mkd: Doug. County Surveyor's Office, 1965
T 19 S
R11W S 36 | S 31 R10W

New BT's: 8" Alder S.36°W. 9.4 ft. Mkd: T20S R11W S1 CS BT.

12" Alder S. 7°W. 16.9 ft. Mkd: T20S R11W S1 CS BT.

Closing Corner to Sec. 6, T20-10W & Sec. 1, T20-11W.

(South Boundary 19-10W)

Set - Iron Pipe with Brass Cap Mkd: RS239 C.C. Sec. 1, T20S R11W
Sec. 6, T20S R10W

Scribed New BT's: 14" Fir S. 46° E. 34.5 ft.
30" Fir S. 24° W. 65.7 ft.

West 1/16 Sec. 31, T19-10W. & Sec. 6, T20-10W.

Set - Iron Pipe with Brass Cap Mkd: RS 239 W 1/16

S 31	T19S R10W
S 6	T20S R10W

Scribed New BT's: 24" Fir N. 12° E. 23.7 ft.
28" Fir S. 76° E. 31.0 ft.

1/4 Cor. to Sec. 31, T19-10 & Sec. 6, T20-10W.

Set - Iron Pipe with Brass Cap Mkd: RS 239

1/4 S 31	T19S R10W
S 6	T20S R10W

New BT's: Scribed, 22" Fir South 4.1 feet.
24" Fir N. 15° W. 36.5 ft.

Section Corner, Secs. 31 & 32, T19-10W. & Secs. 5 & 6, T20-10W.

Set - Iron Pipe with Brass Cap Mkd: RS 239

S 31	S 32	T19S R10W
S 6	S 5	T20S R10W

Scribed New BT's: 40" Fir N. 3° W. 27.0 ft. - 14" Fir N. 59° E. 21.5 ft.
30" Fir S. 6° E. 25.5 ft. - 40" Fir S. 72° W. 59.6 ft.

West 1/16 Sec. 32, T19-10W & Sec. 5, T20-10W.

Set - Iron Pipe with Brass Cap Mkd: RS239, W 1/16

S 32	T19S R10W
S 5	T20S R10W

Scribed New BT's: 40" Fir S.70°W. 19.7 ft.
18" Fir N. 5° E. 39.8 ft.

Wilford N. Haines
For: U.S.F.S. - U.S.Fly. & Int. Paper.
November 1965
Map, File M 31 - 6

RE-RENEWED (SEE AFFIDAVIT NO. #32)

RE-RENEWED (SEE AFFIDAVIT NO. #37)

FD. 3/27/80
E. ALVARADO
U.S. FLY. SERV.
C.S. 41/16
9/82
REFERENCED
SEE # 29

1
2
3
4
5
6
7
8