

Douglas County Surveyor's Record of
Government Corners Renewed

T. 19 S. T. S. R. 10 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued) 1/2 Corner Sections 25 & 36.

I establish new BT's, as follows. Each BT has a scribed face & a U.S.F.S. BT. sign breast high & facing the monument.

Bearing Trees set: a 32" D.Fir bears N. 10* E. 50.3 feet
a 28" D.Fir bears S. 60* E. 29.27 feet.

1/4 Corner to Sections 26 and 35.

Found a faint "X" & orig. line blazes.

Found - 32" Fir with overgrown face, opened face & found orig. scribing.

This is the formerly 18" fir in the S. E. Quad.

At the proper distance & bearing from the Orig. BT., I placed a 2"x36" galv. I.P., flanged at the bottom & capped with a br. disk welded on top.

The monument projects 6" above ground. I filled in around the pipe monument with stone & packed earth.

I stamped the disk

1/4 S 26
S 35
1971
4185

I established new BT's., as follows.

Each BT. has a scribed face & a U.S.F.S. BT. sign breast high & facing monument, Bearing Trees set: a 24" D.Fir bears S. 19* W. 51.0 ft.
a 36" D.Fir bears N. 25* E. 41.75 ft.

1/4 Corner for Secs. 27 and 34.

Found - 2 old blazed trees east of the north fork of Smith River & by chopping out the blazes & finding them to be 70 & 61 yrs. old: (both trees have been dead at least 7 yrs.). We determine this to be the orig. blaze line. Other blaze line are as recent as 12-24 yrs. old. Calls to toe of slope, old trail & river were checked & found to agree with the GLO.

A 18" rotten Alder snag bears N.8°W., 13.01 ft. with face chopped out. Nor orig. scribing visible.

Set - 2 1/4" Brass cap attached to a 2" x 30" I.P. 6" above ground marked: T19S R10W

1/4 S 27
34
PLS 1017
1977

from which new BT's:

46" D.Fir bears N.22°W., 35.31 ft. double faced scribed 1/4 S27 and BT.

22" Maple bears S.84°E., 30.88 ft. double faced scribed 1/4 S34 and BT.

Note: Go USFS Rd. #1860 to fork of west and north fork of the Smith River. Location poster about 300 ft. from the bridge, go west 80 ft.

9/12/77

East 1/4 Corner, Section 36 only.

Found no evidence of the 1920 Government survey corner.

At proportional distance:

Set - 5/8" x 40" Iron rod

From Which:

40" Red Cedar bears S.7°W., 87.2 ft. marked "BT 1/4 S. 36 T. 19 S., R 10 W:

28" Red Cedar bears S.42 1/2°W., 58.8 ft. marked "BT 1/4 S36 T. 19-S., R 10 W"

6/3/78

Section corner for Sec. 31, T.19-9 and Sec. 6, T.20-9 ONLY.

Found - Remains of the 6" Chittem.

Set - 5/8" x 40" Iron rod S.20°W., 40 lks. from the uproot hole where the 6" Chittem stood.

New VT's- 48" D. Fir bears N.32 1/2°E., 49.0 ft. marked "BT S.31 T.19S. R. 9 W."

44" D. Fir bears S. 53 1/2°E., 18.2 ft. marked BT S. 6 T. 20 S. R. 9 W."

6/3/78

17

18

19

20

James W. Prochman
For U.S. Forest Service
July, 1971 C.S. File No. 55/206
Map File M 43 - 22

Trav. 1972

Ernesto R. Alvarado
U.S.F.S. Surveyor
Nat'l Forest
Gordon H. Long
Land Surveyor
June-Sept. 1977
M 65 - 63
C.S. 58/162

Forrest J. [unclear]
For: International
Paper Company
June 3, 1971
M 71 - 62

RE-RENEWED. SEE CORNER NO. # 36

RE-RENEWED. SEE CORNER NO. # 35