

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 19      T. S.      R 10      R. W. W. M.

ROKE, CHAPMAN CO., EUGENE, ORE. 21001

Ernest R. Alvarado  
U.S.F.S.  
Deputy, Doug. Co.  
Surveyors Office  
Witnesses: Carol  
Mickison  
C. 31, 1978  
S. 60/17

**21**

1/4 Corner for Secs. 28 and 33.  
Found - Orig. 56" D. Fir, bears N.71°E., 7.3 ft. with "S" scribing visible. The face was chopped out by B. Best and H. Britton in 11/61 to find the scribing.  
Set - Brass cap marked: Douglas County Surveyor Office T19S R10W S28 S33 1/4 1978  
BT's - 27" D. Fir bears N.82°W., 18 ft. marked double blaze upper 1/4 S33 lower CSBT.  
Note - Location poster on North shoulder of N. Fork access road which is 600 ft. due south of corner. Corner is located on small spur ridge on North side of N. Fork of Smith River.  
10/31/78

Ernest R. Alvarado  
USFS - Deputy, Doug.  
Co. Surveyors Off.  
Witness: Diane Lawson  
Nov. 8, 1978  
C.S. 60/17

**22**

Section Corner for Secs. 33 and 34; and Secs. 4 and 3 of T.20-10.  
Found - 1952 GLO brass cap properly marked.  
13" D. Fir bears S.26°W., 7.2 ft.  
13" D. Fir bears N.29°W., 11.3 ft.  
12" D. Fir bears S.54°E., 13.8 ft.  
17" D. Fir bears N.50°E., 6.4 ft.  
CONDITION REPORT ONLY. NO NEW MONUMENT OR ACCESSORIES.  
Note - Go down USFS Rd. #48 to section line post for township line. (Sec. cor. for 32, 33, 5, 4 is just off road.) Sec. cor. for 33, 34, 4, 3 is one mile east of Sec. line post.  
11/9/78

**RE-OPENER NO. 49**  
FD. 3/11/78  
E. ALVARADO  
U.S. FOR. SERVICE  
C.S. 61/6

**23**

1/4 Corner for Sec. 33; and Sec. 4 of T.20-10  
Found - 1952 GLO brass cap properly marked.  
40" D. Fir bears S.6°W., 7.1 ft.  
43" D. Fir bears N.75°E., 97 ft.  
CONDITION REPORT ONLY. NO NEW MONUMENT OR ACCESSORIES.  
Note - Go to sec. corner for 32, 33, 5, 4 which is located 6 ft. East of N. Fork access Road. From there go East 1/2 mile to corner  
11/8/78

**FD. 9/80**  
**D. PEEL LS#752**  
**M 85 46**  
**FD. OK 12/80**  
**M 111-33**

Donald L. Peel LS#752  
Triangle Eng. Co.  
For: U.S. Forest  
Service  
Sept. 1980  
M 85 - 46

**24**

Sec. Corner to Secs. 28-29-32-33  
Fd. - Alder Hub of unknown origin.  
Orig. 21" Alder bears S.46°E., 35.7 ft. with bark scribed.  
Set - U.S. Forest Service 2 1/2" aluminum mon.  
BT's - 27" Fir bears N.42°E., 80.1 ft.  
52" Fir bears S.86°E., 58.4 ft.  
17" Alder bears S.39°W., 14.3 ft. with bark scribed.  
21" Alder bears N.49°W., 20.7 ft. with bark scribed.  
Note - Position of the alder hub agrees with call note distances to the North fork Smith River to the West and North but the distance to the East is long.  
9/80

**25**

1/4 Corner to Secs. 33 & 34  
Set - 2 1/2" alum, mon. by single proportionate measure.  
BT's - 28" Fir bears N.56°E., 42.1 ft.  
28" Fir bears S.75°W., 43.3 ft.

William Shull  
For: J.S. Forest Service  
June 1982  
M 92 - 29

**26**

Center 1/4 Corner for Section 34  
Set - Rock tablet monument marked T19S R10W S34 C1/4 1982 LS 909.  
BT's - 9" cedar bears N.62°W., 49.0 ft. scribed "C1/4 S34 BT".  
24" Alder, N.58°E., 28.3 ft. scribed C1/4 S34 BT (bark scribed)

**27**

1/4 Corner for Sections 34 and 35  
Set - USFS monument marked T19S R10W 1/4 34 35 1982 PLS 909.  
BT's - 20" D. fir, N.65°E., 46.4 ft. scribed "1/4 S35 BT".  
16" D. fir, S.50°W., 11.8 ft. scribed "1/4 S34 BT".  
6/82

**REFERENCED - SEE #30**

Donald Peel LS #752  
For: International  
Paper Company  
Sept. 8, 1982  
M 92 - 79

**28**

1/4 Corner for Secs. 29 and 32  
Set - U.S.F.S. 2 1/2" Alum. monument on a 1 1/2" x 36" I.P. Cap marked: T19S R10W 1/4 S29 S32 PLS 752 1982".  
BTs - 54" Fir S.3°W., 197.2 ft.  
50" fir, S.88 1/2°W., 254.1 ft.  
9/82