

Douglas County Surveyor's Record of  
Government Corners Renewed

T 19

T. S.

R 10

R. W. W. M.

39

Ernesto Alvarado  
U.S.F.S.  
Don Large  
Gene Tracy  
Feb. 11, 1986  
C.S. 62/33

1/4 Corner for Sections 34 and 35

(Monument was referenced out 9/10/82 by Ernesto R. Alvarado, USFS. Ren.#30)

Found - The three reference markers and were not disturbed by the road construction. The two BTs set by William L. Shull were destroyed by the road construction.

34" D. fir with 8"x3/8" nail bears N.20°30'E., 95.2 ft.

14" D. fir with 8"x3/8" nail bears N.80°30'W., 53.0 ft.

25" D. fir with 8" x 3/8" nail bears N.80°E., 35.7 ft.

Set - At intersections of distance from the three reference markers -  
Set Douglas County brass cap, 10" below the surface of road.  
Cap marked T19S R10W 1/4 sections 34 and 35., 1986 U.S.F.S. alum. cap buried alongside.

New BTs - 38" D. fir bears N.39°W., 25 ft. to a nailmarked 1/4 S34 CS BT.

26" D. fir bears S.83 3/4°E., 37.3 ft. to a nail marked 1/4 S35 CS BT.

Distances are to side and center of trees at root crown.

Location - Go USFS Rd No. 23 to USFS Rd. No. 942. From gate go 1 mile to intersection of USFS Rd. #946. The corner is 10" below road surface on the westside of USFS Rd. #942 at intersection.

1/4 Corner Sec. 32 and 5 of T20-10.

See Ren. #9

40

Found - A BLM 3" brass cap on a galvanized iron pipe stamped "T19S R10W 1/4 S32 S5 T20S 10W 1979 BLM".

BT's - A 42" Douglas fir bears S 78°W, 103.0 ft. (rec. S 78 1/4°W 158 lks.).

10" Alder stump bears N 4°E, 36.0 ft. (rec. N 4°E, 56 lks.).

New BT's - 22" Alder bears N 47 1/2°E, 42.6 ft. Bark scribed "1/4 S32 BT".

34" Alder bears S 2 1/2°W, 117.7 ft., Scribed " 1/4 S5 BT".

Section Corner to Sections 32 and 33 , also sections 4 and 5 of T20-10.

41

Found - GLO 2 1/2" brass cap on a 1 1/2' galvanized iron pipe set in 1952.

BT's - A 24" douglas fir stub bears S86°W, 10.7 ft. (rec. S85°W, 15 lks.) Healed.(BLM 1892).

34" douglas fir bears S 20°E, 66.7 ft. (rec. S 20°E,101 lks). healed. (BLM 1952).

26" douglas fir bears N 40°E, 34.9 ft., (rec. N 40°E, 53 lks). healed (BLM 1979)

33" Alder bears N 12°W, 8.6 ft. (rec. N 16°W, 8.5 ft. ) (1982 RLS 752).

1/4 Corner for Section 7 only of T19-9

42

Set - U.S.F.S. Aluminum monument mkd. "T19S 1/4 R10W R9W PLS 1978 1988".

Removed ALUM. MON. SET REBAR - POSITION CHANGE. C.S. 63/104 5/90

34" Fir, N.48°E., 115.5 ft. BLM BT

26" Hemlock, S.72 1/2°E., 59.1 ft. scribed 1/4 S7 BT.

Note: 1/4 Cor. set by BLM in 1958 bears N.37°04'53"E., 74.85 ft.

1/4 Corner for Sections 1 and 12

43

Found - U.S.F.S. Alum. monument "PLS 752"

68" Fir, S.42°E., 34.8 ft.

40" Fir, N.64°W., 22.2 ft.

Note - 1979 survey data - Lane C.S. 22751

1/4 Corner for Sections 11 and 12

44

Found - U.S.F.S. Alum. monument "PLS 752"

39" Fir stump, S.46°E., 51.2 ft.

48" Fir stump, N.84°W., 71.0 ft.

21" Hemlock stump, N.7°W 17.2 ft.

Section Corner for 11, 12, 13 and 14

45

Found - Douglas County Brass Cap. Ren. #13

24" Fir stump, N.35 1/2°E., 61.5 ft.

38" Fir stump, S.36 1/2°E., 56.1 ft.

30" Fir stump, S.6 1/2°W., 39.0 ft.

Note: True corner point bears S.4°38'E., 1.30 ft. Lane Co. Survey data C.S. 24151 (1980)

RE-RENEWED, SEE CORNER NO. #47

James W. Prochnau  
For: Siuslaw National  
Forest M 104 - 51 A&B  
June 30, 1987

FOOK 24  
Clyde Mullins  
5/94 M120-13  
FOR I.P.  
USDA COVEN  
FOOK 12/90  
M 111-33

Daniel Baker  
LS #1978  
For: Margaret  
Crowell  
Sept. 19, 1988  
M 107-1  
(See C.S.  
63/69 for  
Lane Co. Info.)