

Douglas County Surveyor's Record of  
Government Corners Renewed

T 19 S T. S. R 9 W R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21851

13

Stephen J. Flause  
Shawn Means  
Terrie Plouff  
Douglas County Surveyor  
Office  
April 1980  
C.S. 61/6

East Witness Corner for 1/4 Corner for Secs. 14 and 23  
Found - 1958 B.L.M. Brass Cap on 2" iron pipe firmly set and protruding from ground 0.5 ft. properly marked.  
An 12" now a 16" D. Fir bears N.11°E., 5.9 ft. (Rec. N.10°E., 5.9 ft.) with a blazed "X" on the south face of tree and a healed blaze at base of tree, no scribing visible.  
An 8" Fir now an 8" dead snag 15 feet tall bears S.64°W., 7.5 feet (Rec. S.68°W., 7.9 feet), open blaze at base of snag scribed "BT".  
New BT's- An 11" D. Fir bears S.44°E., 16.5 ft., scribed "T19S R9W WC S23 CS BT" on a double blaze.  
An 14" D. Fir bears S.06°E., 24.0 ft., scribed "WC T19S R9W S23 CS BT" on a double blaze.  
An 8" D. Fir bears N.20°W., 12.0 ft., scribed "WC T19S R9W S14 CS BT" on a double blaze.  
All new trees tagged with Douglas County Surveyor's Office tags.

14

Stephen J. Flause  
Shawn Means  
Nathan Reed  
Douglas Co. Surveyor's  
Office  
March 1980  
C.S. 61/6

West W.C. for 1/4 Secs. 14 and 23  
Found - 1958 BLM Brass Cap on a 2" iron pipe firmly set and protruding 0.5 ft. from ground properly marked.  
A 11" Hemlock now a 12" rotten stump 2.5 ft. tall bears S.42 3/4°W., 2.6 ft. Blazes are rotted but scribed "BT" is visible with a U.S. Plywood BT tag marked as per record.  
Northwest BT from resurvey is missing.  
We also find two unrecorded BT's:  
A 17" Hemlock bears S.45 1/2°W., 53.0 ft. with U.S. Plywood BT tag reads reverse bearing and distance N.48°E., 53.4 ft. scribed "WC T19S R9W S23 on a single unhealed blaze marked with yellow paint.  
A 17" Hemlock bears S.74°W., 39.6 ft. with U.S. Plywood BT tag reads reverse bearing and distance N.76°E., 39.2 ft. and scribed "WC T19S R9W S23" on a single unhealed blaze marked with yellow paint.  
Note - Because of unrecorded nature of BT's we do not retag but leave as found. No other trees available.

3/19/80

15

Stephen J. Flause  
Karen Mosley  
Doug. Co. Surveyors  
Office  
April 13, 1981  
C.S. 61/19

East witness corner for 1/4 corner for Secs. 14 and 23.  
Found as described in Renewal #13.  
To cap at corner we ADD the stamping as follows (in a larger stamp size than the BLM markings) "E DCSO 1981".

16

West witness corner for 1/4 corner for Secs. 14 and 23.  
Found as described in Renewal #14.  
To cap at corner we ADD the stamping as follows (in a larger stamp size than the BLM markings) "W DCSO 1981".

4/31/81

17

Sec. corner for Sec's. 3, 4, 9, & 10.  
Found - Brass Cap (BLM). 1957 - 1960 RESURVEY  
BT's - 12" Fir bears S.54 1/2 °E., 11.8-ft. (scar visible), 1899 BT.  
22" Fir bears N.26°E., 17.5-ft. (scar visible), 1899 BT.  
30" Fir bears N. 51 1/2 ° W., 10.4-ft. (scar visible), 1899 BT.  
24" Fir bears S.81°W., 29.2-ft. (scar visible), 1957 BT.

7/16/81

18

Sec. corner for Sec's. 9, 10, 15, & 16.  
Found - Brass Cap (BLM). 1968 - 1969 RESURVEY  
BT's - 15" Fir bears N.40 1/2 °E., 12.3-ft. (scar visible).  
18" Fir stub bears S.45°E., 27.9-ft. (scar visible).  
23" Fir bears S.34 1/2 °W., 17.3-ft. (scar visible).  
23" Fir bears N.39 1/2 °W., 6.6-ft., (scar visible).  
\*NOTE - All BT's are from 1968 Resurvey.

7/16/81

Les Roberts  
For: International Paper Co.  
July 16, 1981  
M 88 - 21

RE-RENEWED, SEE CORNER NO. 15

RE-RENEWED, SEE CORNER NO. 16

RE-RENEWED, SEE CORNER NO. #43