

Douglas County Surveyor's Record of
Government Corners Renewed

T. 19 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21981

Clyde F. Mulkins, LS#2006 & Ronald E. Stuntzner, LS#1342
For: U.S. Forest Service, Siuslaw National Forest
March 18, 1983

M 94 - 21 A, B, & C ALSO SEE C.S. 58/183 for Cor. INFO. filed in LWS Co.

- 25
1/4 Section Corner on west line of Sec. 6. 1963 Resurvey.
Found - B.L.M. BCIP mkd: 1/4 S6 T19S R9W 1958, from which:
BTs - 18" cedar bears S.53-1/2°E., 77.3-ft. w/healed face.
Up-rooted maple, record N.77-1/2°E., 76.6-ft.
New BT - 36" cedar bears S.81°E., 81.6-ft. (scribed: 1/4 S6 BT).
3/18/1983
- 26
Closing Corner for Secs. 6, & 7 on Sec. 1 of T.19-10. (1963 Resurvey).
Found - B.L.M. BCIP mkd: T19S S6 S1 CC S7 R10W R9W 1958, from which:
BTs - 15" D.fir bears N.56°E., 71.6-ft. w/healed face. (1958).
18" D.fir bears S.53°E., 76.1-ft. w/visible scribe.
16" D.fir bears S.10°W., 75.4-ft. w/visible scribe.
13" D.fir bears N.51°W., 2.3-ft. w/healed blaze.
3/18/1983
- 27
1/4 Section Corner common to Secs. 6, & 7. 1963 Resurvey.
Found - B.L.M. BCIP mkd: 1/4 S6 S7 T19S R9W 1958, from which:
BTs - 12" D.fir snag bears N.24°E., 9.6-ft. (Orig.).
27" D.fir snag bears N.22°E., 25.3-ft. w/healed face. (1958).
25" hemlock bears S.27°E., 56.6-ft. open face-scrib. visible (1958).
19" hemlock bears S.68°E., 13.7-ft. w/healed face.
3/18/1983
- 28
Section Corner common to Secs. 4, 5, 8, & 9. (1963 Resurvey).
Found - Original Corner Tree - 11" D.fir snag from which:
BTs - 32" D.fir bears S.50°W., 17.2-ft. w/healed face.
12" D.fir bears S.63°E., 5.9-ft., open face with scribing:
"R9W S9" visible. (Original BT).
11" D.fir snag bears N.69°E., 8.5-ft. w/healed face (Orig. BT).
14" D.fir bears N.35°W., 3.9-ft. w/healed face (Orig. BT).
24" D.fir bears N.61-1/4°E., 33.0-ft. w/healed face (1958).
Set - 2-1/2" x 30" aluminum pipe w/ 3" aluminum cap, which is a
standard U.S.F.S. monument, for a reference monument mkd:
RM T19S R9W S5 5.00 S88°46'E S8 1983 PLS 2006, which bears
N.88°46'W., 5.00-ft.
New BT - 18" D.fir bears S.8°E., 36.7-ft., scribed: T19S R9W S9 BT.
3/18/1983
- 29
1/4 Section Corner common to Secs. 4, & 5. (1963 Resurvey).
Found - B.L.M. BCIP mkd: 1/4 S5 S4 T19S R9W 1958, from which:
BTs - 12" D.fir bears S.38-1/2°E., 18.1-ft. (Rec. 29-1ks) (1958).
7" D.fir bears N.59-1/2°W., 30.1-ft. (Rec. 31.0-ft.) (1958).
(this BT is a down snag).
New BT - 26" D.fir bears N.72°W., 56.9-ft., scribed: 1/4 S5 BT.
note - See map for additional information. 3/18/83
- 30
North 1/4 Section Corner of Sec. 5.
Set - 2-1/2" x 30" aluminum pipe w/3" alum. cap (standard USFS mon.),
mkd: T18S R9W 1/4 S5 T19S R9W 1983 PLS 2006, from which:
New BTs- 18" D.fir bears S.86°W., 15.3-ft., scribed: N1/4 S5 BT.
10" D.fir bears S.16°W., 7.1-ft., scribed: N1/4 S5 BT.
3/18/83
- 31
Center 1/4 Corner for Sec. 6.
Set - 2-1/2" x 30" alum. pipe w/3" alum. cap (standard USFS mon.),
mkd: T19S R9W C 1/4 S6 1983 PLS 2006, from which:
New BTs- 10" hemlock bears N.82°E., 9.5-ft., scribed: C1/4 S6 BT.
14" hemlock bears N.12°E., 7.7-ft., scribed: C1/4 S6 BT.
3/18/83
- 32
North 1/4 Section Corner of Sec. 6.
Set - 2-1/2" x 30" alum. pipe w/3" alum. cap (standard USFS mon.),
mkd: T18S R9W 1/4 S6 T19S R9W 1983 PLS 2006, from which:
New BTs- 12" hemlock bears S.32°W., 28.8-ft., scribed: N1/4 S6 BT.
18" hemlock bears S.28°E., 16.0-ft., scribed: N1/4 S6 BT.
3/18/83

25

26

27

28

29

30

31

32

REF

#

52