

Douglas County Surveyor's Record of
Government Corners Renewed

T.19 S. T. S. 9 W. R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97601

33

CC at SW corner of Sec. 31. (Tnsp Corner). Ren.#11.
CORNER REPORT ONLY.

History- This corner was originally established in 1899 by Chandler. The corner mon. was a 6" chittum - BTs were: 6" chittum N.20° 40-lks, & 20" fir S.26-3/4°E.,26-lks.
In 1921, Mensch fnd the corner & scribed a 4" chittum S.38° 10-lks, as the orig. fir BT was dead.
In 1978 (see Co. Surv. file# M 71-62) Forrest Hales fnd an u-rooted chittum & set a 5/8" Iron Rod for the closing corner mon., holding the position of the fnd chittum as the orig. northeast bearing tree.

Mon. Fd.- 5/8" I.R. (set by Hales).

Accessories Fd. - BTs described by Hales survey:

48" D.Fir, single blazed w/scribing bears N.32-1/2°E.,51.1-ft. (Rec. 49.0-ft.).

40" D.Fir (Rec.44") single blazed w/visible scribing "S6 T20S R9W BT" bears S.50°E.,21.4-ft. (Rec. S.53-1/2°E.,18.2-ft.).

NOTE - I visited this corner w/ Ernesto Alvarado of the Siuslaw Nat. Forest, who produced a copy (see file) of a Forest Service "CORNER RECORD" card dated 1968. According to the info. on the card, the cor. had been visited by J.Deaton & D.Thrall 10 yrs. prior to the Hales survey. The card shows that a 16" fir stub w/scribing was located & that blazed lines ran E. & S. from the cor. position. This evidently was accepted as the Orig. fir BT reported by Mensch to be dead in 1921 (47 yrs. earlier). Mr. Alvarado indicated he had set a temporary stake at the Orig. bearing & dist. from a decayed fir stump (stump bears S.26-3/4°E.,26-lks.from stake)

From the Hales 5/8" I.R. we measure to the temp. stake set Alvarado N.22°E.,16.9-ft. & we measure to the 30" fir stump S.89-1/2°E.,11.3-ft. We did not find any scribing on the stump. We fnd. blazed line running E. & N. from the general area of the closing cor. (the blazed line to the North was East of the line mkd. by Hales).

Without performing a survey it would not be practical to distinguish if an intersection point could be determined from the found blazed lines.

Bearing Tree tags with no info. (name, date, bearings or distances) scribed were found. One tag was found on the 48" Hales BT & faced a South Southwest direction. The other was found on a maple stump (approx. 8-ft. Easterly of Hales Monument) & faced North Northwest.

This is a report only--No monuments or BTs were set or scribed.

No Orig. evidence of the corner mon. or its accessories could be ascertained at this time.

Sketch - See file for sketch and additional documentation.

Larry (Ed) Monrean, L.S.#1830, Deputy
Douglas County Surveyors Office
R. W. Smith, S. J. Flause
January 5, 1984
C.S. 62/16

Forrest J.Hales,
PLS #453
For: Hales, Forrest
March 30, 1984
M 96 - 35

East 1/4 Sec. Corner for Sec. 36 only of T.19-40.
Set - 5/8" x 40" I.R. mkd: F.J.H 453 from which:
BTs - 40" Red Cedar stump bears S.9°55'W.,93.8-ft. to face.
28" Red Cedar stump bears S.42°36'W.,66.9-ft.to face.
Fd. BTs recorded by Hales in 1978. SEE REN.#10
1978 mon. was removed in logging.

RE-RENEWED **CORNER** #31

1/84

34

Les Roberts,
OPLS #1039
For: International
Paper Co.
April 3, 1984
M 96 - 46
C.S. 58/293

Witness Cor For:

Section Corner common to Secs. 27,26,34, & 35.

3/84

35

Found - 1957 BLM B.C. laying on creek bank (Cap had been washed out by Beaver Creek.)
BTs - 24" alder bears S.10°E.,19.8-ft. (bark scrbd.) 1899 BT - (Rec: S.14°E.,19.8-ft.).
54" cedar bears S.19-1/2°W.,81.2-ft.(scar visible), as per Rec. 1957 BT.

20" alder set in 1899 & fnd in 1957 is now destroyed.
22" alder bearing N.49°E. & set in 1957 is now destroyed.
18" alder bearing N.71°W. & set in 1957 was uprooted by creek.
Set - 2" x 30" aluminum pipe & cap for Witness Cor. Witness Cor. was set S.0°32'00"W.,25.00-ft. from true section corner.
Buried purple magnetic marker under 30" aluminum pipe.
New BTs- 25" alder bears S.64°E.,38.5-ft.(bark scrbd/painted/brass washer).
24" alder bears N.34°E.,6.6-ft.(bark scrbd/painted/brass washer).
Set metal fence post w/sign beside brass cap.

4/84