

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 19    T. S.    R. 9    R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97401

Robert B. Ward Jr.  
L.S. 1091  
For: Siuslaw Nat. Forest  
June 1991  
M 113 - 37 A & B

1/4 Corner for Sections 18 & 19. 45  
Set - U.S.F.S. Alum. corner monument Stamped "T. 19S R9W 1/4 S18 S19 L.S. 1091 1991"  
BT's - 19" Hemlock bears N.30°W., 24.0 ft. (scribed "1/4 S18 BT")  
10" Hemlock bears N.36°E., 34.7 ft. (scribed "1/4 S18 BT")  
8" Hemlock bears S,52°E., 27.8 ft. (scribed "1/4 S19 BT")  
10" Hemlock bears S.46°W., 25.6 ft. (scribed "1/4 S19 BT")  
8/12/91

Section Corner for Sec's 17, 18, 19 & 20. 46  
Set - U.S.F.S. Alum. corner monument stamped " T.19S R9W S17 S18 S19 S20 L.S. 1091 1991"  
BT's - 9" Fir bears N.29°E., 22.1 ft. (scribed "T19S R9W S17 BT")  
11" Fir bears N.13°W, 10.4 ft. (scribed "T19S R9W S18 BT")  
10" Fir bears S.80°W., 5.5 ft. (scribed "T19S R9W S19 BT")  
13" Fir bears S.23°E., 18.6 ft. (scribed "T19S R9W S20 BT")  
8/12/91

1/4 Corner for Sections 17 & 18. 47  
Set - U.S.F.S. Alum. corner monument stamped "T19S R9W 1/4 S17 S18 L.S. 1091 1991"  
BT's - 11" Fir bears S.56°E., 33.6 ft. (scribed "1/4 S17 BT")  
18" Fir bears S.77°W., 6.6 ft. (scribed "1/4 S18 BT")  
12" Fir bears N.31°W., 38.5 ft. (scribed "1/4 S18 BT")  
13" Fir bears N.32°E., 18.7 ft. (scribed "1/4 S17 BT")  
8/12/91

Section Corner for Sections 31 & 32 only. 48  
Fnd. - 1921 G.L.O. brass cap attached to a badly rusted iron pipe.  
17" Fir bears N.21°E., 20.4 ft. (healed face)  
Set - U.S.F.S. Alum. corner monument stamped "T19S R9W S31 S32 T20S R9WS6 L.S 1091 1991"  
New BTs-23" Fir bears S.34°E.,29.1 ft. (scribed "T20S R9W S6 BT")  
15" Maple bears S.16°W., 7.9 ft. (scribed "T20S R9W S6 BT")  
25" maple bears N.73°W., 26.1 ft (scribed "T19S R9W S31 BT") (bark scribed)  
8/12/91

Wayne Donovan  
LS #2553  
5/19/93  
C.S. File 63/153

North 1/4 Cor. Sec. 1 T20-9 49  
Found - 1953 G.L.O. Brass cap in good condition.  
2 1/2" brass cap bears N.89°12'50"W., 81.75' - (1/4 cor. secs. 36.)  
22" Fir, stump bears S.55 1/2°E., 37.8', visible scribing.  
20" Fir, stump bears S.69°W., 27.4', healed face.  
New BTs -  
17" Fir, bears S.22 1/2°W., 53.8', blazed & scribed "1/4 S1 BT"  
10" Fir, bears S.43 3/4°E., 15.6', blazed & scribed "1/4 S1 BT"  
Note - Corner lies on a gradual NW slope.

Daniel Baker  
For: Davidson  
Industries Inc.  
March 1997  
M 124-48

C 1/4 Sec. 7 50  
Set - 1 3/4" Iron Pipe w/Brass cap mkd:  
T19S R9W  
C 1/4 + S7  
PLS 1978  
1997  
13" Hemlock, N.13 1/4°E., 23.5', scribed "C1/4 S7 BT"  
39" Hemlock, N.29°W., 23.0', scribed "C1/4 S7 BT"  
11" Alder, S.19°E., 44.3', scribed "C1/4 S7 BT"  
34" Hemlock, S.49°W., 22.4', scribed "C1/4 S7 BT"

1/4 Cor. Secs. 7 & 8 51  
Found - US BLM Brass Cap 1957  
34" Fir, S.59°E., 77.4', healed  
Set - 15" Alder, N.55°W., 19.3', scribed "1/4 S7 BT"  
9" Hemlock N.38°E., 33.0', scribed "1/4 S8 BT"  
13" Alder, S.24°W., 46.0', scribed "1/4 S7 BT"