

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 6 R. W. W. M.

ROYE-CHAPMAN CO., EUGENE, ORE. 97196

Wardson
Surveyor
Evans
K ershner
Witnesses
6.5.39/176
July 22, 1948

SEC. COR. 33-34(South)
Set 1" G. I. P. with a brass cap marked Co. Surv. Office
T 20 S, R 6 W, S 33, S 34. From which
2 1/2" Fir bears N 25° W 35.1 ft. dist. (new B. T.)
A stump bears N 71° W 21.1 ft. dist. (O. B. T. scribe marks
still good)

#71
FD 11/83 Smith
L 490
M 95-49

1

Chas. C. Hayden
Surveyor
Fred Prella
Witness
June, 1950
FILE 40/255

S.E. COR. SEC. 28
Run East by traverse from South 1/4 Cor. to the S.E. corner of Sec. 28
where I found the B.T. described as a 60" Fir stub S 72° 00' 32.2 ft.
Marks rotted away. Fred Prella saw scribe marks on this 16 yrs. ago.
Orig. Fir 3" now 2 1/2" bears S 76° E 13.9 ft., remarked B.T.
Set a 5/8" iron rod and marked new a
Fir 8" S 1° 00' W 17.8 ft. B.T.
Fir 6" N 65° W 13.6 ft. B.T.

2

Ben B. Irving - County Surveyor
Jim Byron - Deputy
Ray Irving (Chairman)
John Fee
April 26 - 29, 1954.
Survey for Clarence C. Backus
File 45/275 (see also 41/274)

1/4 section corner to secs. 33/34.
Found a 20 inch Red Fir - S.37°30'E., 19.8 scribed S 1/4.
Found O. B. T. - N.52°W., 26.4 - Blazed - Not cut out.
Set 1 inch iron pipe with brass cap m'k'd County Surveyor's
Office 1/2 S 33/34 T20S, R6W.
Blazed and Scribed a 10 inch Red Fir, S.29°29'E., 29.8, 1/4 S 34 CS BT;
and a 1 1/4 inch Red Fir, N.78°55'W., 53.2, 1/4 S 33 CS BT.

FD. 11/83 Smith
L 490
M 95-49
FD. OK 6-99
D. Edwards
M 131-70

Section corner 27, 26, 34 and 35.
Found a 40 foot Fir snag - N.59°E., 13.2 feet scribed S 26 BT.
Found slab of BT - N.30°W., 2.7 scribed S 27 BT.
Set a 1 inch iron pipe - Brass Cap m'k'd County Surveyor's Office 27/26
34/35
T20S, R6W. 1954.
Blazed and Scribed the following trees:
36 inch Red Fir - N.21°W., 31.5 - S 27 T20S, R6W, CS BT:
18 inch Red Fir - S.21°W., 81.3 - S 34 T20S, R6W, CS BT:
12 inch Red Fir - S.28°E., 43.8 - S 35 T20S, R6W, CS BT.
24 inch Red Fir - N.26°E., 59.8 - S 26 T20S, R6W, CS BT.

FD. 11/83 Smith
L 490
M 95-49

4

Section corner to secs. 34, 35 (T20S, R6W) and 3 (T21S, R6W).
Found the following trees:
48 inch Fir - N.49°W., 19.8 - Scribing gone.
48 inch Fir - S.41°W., 23.1 - Scribing gone.
48 inch Fir - N.30°E., 52.0 - Blazed - Not cut out.
Blazed and Scribed the following trees:
8 inch Cedar - N.83°E., 48.5 - S 35 T20S, R6W, CS BT.
14 inch Cedar - N.41°W., 78.0 - S 34 T20S, R6W.

BEARING S 83° E 1/4.
(NOT N 83° E)

25

5

FD 11/83
L 490 Smith
M 95-49

1/4 section corner to secs. 34/35.
Set by proportional measurement between the Northeast and Southeast
corners of section 34.
Set a 1 inch iron pipe with brass pipe m'k'd County Surveyor's Office. 34/35
1/4 S T20S, R6W., 1954.
Blazed and scribed the following trees:
9 inch Red Fir - N.78°E., 62.2 feet - 1/4 S 35 CS BT.
12 inch Red Fir - N.51°45'W., 34.7 feet - 1/4 S 34 CS BT.

6

Wilford N. Haines
Surveyor for Wooley Logging
Co.
1956.
Map File M 3 - 23.

Section corner to secs. 27, 28, 33 and 34.
Found iron pin and a 30 inch Fir snag, S.76°E., 13.9 feet. (original)
Scribed:
8 inch Fir, South, 17.6 feet.

FD OK
1-2000
Les Roberts
M 134-6

7

Section corner to secs. 28, 29, 32 and 33.
Position for corner located by double proportional measurement.
Set an angle iron with brass cap at corner point.
From which:
40 inch Fir, N.25°W., 74.0 feet.
48 inch Fir, N.27°E., 72.4 feet.
26 inch Fir, S.85°E., 42.5 feet.
30 inch Fir, S.47°13'W., 50.2 feet.

8