

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

Wilford N. Haines
Survey for Woolley Logging Co.
1956
Map File No. M 3 - 23.

South $\frac{1}{4}$ corner to section 33.
Location of corner determined by proportional measurement.
Set an angle iron with brass cap at corner point.
From which:
16 inch Fir, N.55°E., 45.2 feet.
16 inch Fir, N.04°E., 25.2 feet.

FD. 4/87
D. Marx
M 105-45
FOOK
M 121-24 R48

18

South $\frac{1}{4}$ corner to section 31.
Location of corner established by proportional measurement.
Set an angle iron with brass cap at corner point.
From which:
60 inch Fir, N.45°W., 87.6 feet.
54 inch Fir, N.59°W., 101.5 feet.

19

Section corner to sec. 31, T20S, R6W., and sec. 36, T20S, R7W. (Township corner to T 20 S, Rgs. 6 & 7 W. - not common with T21S, Rgs. 6 & 7 W.)
Found original bearing tree, a Vine Maple, N.43°E., 15.8 feet.
Set angle iron at point for corner.
From which:
44 inch Fir, N.57°W., 91.9 feet.
2" in rock cliff, S.68°W., 95.7 feet.
60 inch Fir, N.41°30'E., 20.1 feet. (Had XXXI carved in)

RE-NEWED CORNER NO. # 56

20

James W. Byron, Deputy
M. Godfrey
S. Bilow
July 31, 1958
C.S. File No. 49/89

Closing Corner to Sec. 36, T.20S, R.6W. & Secs. 1 & 2, T.21S, R.6W.
Found - Two Original BT's:
Orig. 10", now 36" Stump shows good scar & part of old face.
N.59°W. 9.9 ft.
Orig. 10", now 26" Fir previously opened, shows good scribing,
"S2 BT" S.80°W. 15.8 ft.
Also find $\frac{1}{2}$ one inch angle iron set by Haines with 1" disk on top stmpd. survey point 239 Haines.
Set Brass Cap at Corner Mkd: CC S36 T20S R6W County Surveyor's
S2/S1 T21S R6W Office, 1958
New BT's: 16" R.Fir bears N.16 $\frac{1}{2}$ °W. 27.9 ft. scribed S36 T20S R6W CS BT.
26" R.Fir bears S.80°W. 15.8 ft. scribed CC S2 T21S R6W CS BT.
30" R.Fir bears East 9.0 ft. scribed CC S1 T21S R6W CS BT.

21

Renew Corner to Sections 35 & 36, T20S R6W, & Sec. 2, T21S R6W.
Found - Orig. 24", now 48" Fir Snag. I open & find good scribing "BT"
S.45°E. 25.1 ft.
All other BT's gone as recorded in 1882.
Also find Haines" Marker at corner.
Set Brass Cap at Corner Mkd: S35/S36 T20S R6W County Surveyor's
S2 T21S R6W Office, 1958
New BT's: 16" R.Fir bears N.68 $\frac{1}{2}$ °W. 12.0 ft. scribed S35 T20S R6W CS BT.
12" R.Fir bears N.54°E. 45.5 ft. scribed S36 T20S R6W CS BT.
"See note in file for location of corner in relation to other."

RE-NEWED CORNER NO. # 70

22

Wilford N. Haines
Jan. 28, 1961.
C. S. File No. 51/173

$\frac{1}{4}$ Section Corner to Sections 28 and 29.
Beginning at corner to secs. 28, 29, 32 & 33. Thence
N. 4°01'W. 2719.6 ft.
Set a 1" x 1" x 36" T. Iron for $\frac{1}{4}$ S29/S28 from which I
blazed & scribed: 10" Yew N.81°E. 29.9 ft.
20" Yew S.16 $\frac{1}{2}$ °W. 46.9 ft.
Found no trace of original $\frac{1}{4}$ corner.
Continued N.4°01'W. 2719.6 ft. to corner sections 20, 21, 28 & 29.

23