

Douglas County Surveyor's Record of
Government Corners Renewed

T 20 S. T. S. R 6 W. R. W. W. M.

KOKE-CHAPMAN EUGENE, ORE. 21861

See Corner Information
in C. S. File No. 53/1
For Cor. Set in 1937 by Lane County

*FD. B.C. 3 BT's
4/91 D. Peck
M113-45*

1/4 Corner to Sections 19 and 30.
Found - Fir, now 30", N.20°W. 8.6 ft. Tree has been chopped open previously. Good scribing "4" visible on old face. Tree is leaning badly, not uprooted yet, but may not stand long. Badly decayed Snag (Fir) S.30°W. 2.6 ft. Fragmentary but unmistakable scribe marks visible on old face.
Set - Brass Cap at Cor. Mkd: County Surveyor's (Doug) T20S R6W 1/4 S19 S30 Office, 1962
New BT's: 7" D. Fir N.33°W. 29.7 ft. Mkd: 1/4 S19 DCS BT.
9" D. Fir S.25°E. 52.6 ft. Mkd: 1/4 S30 DCS BT.
On County Line.

37

Correction - Section Corner to Sections 21 | 22
28 | 27

Found - Iron Pipe with Brass Cap as set by Cadastral, 1950.
Trees found in field: Orig. 13" Fir, now 18", S.75°E. 25.1 ft.
Orig. 24" Fir, now 32", N.48°E. 35.0 ft.
(These 2 trees show very plain healed-over scars)
60" Fir Stump S.53°W. 79.0 ft.
Other Tree not found.

38

BT's. as recorded in Gov't notes do not agree, See Volume 27, Pg. 11323.
6/72 - RESET G.L.O. B.C. IN PLACE ON ROCK BANK Feb. 15, 1962
NO NEW BT'S. C.S. 54/22

39

Section Corner to Section 20 - 21 - 28 - 29.
Found - Gov't Brass Cap set in 1950.
Fir Tree S.34°E. 25.1 ft. Tree in good condition, Good Scar.
Fir Tree N.56 1/2°E. 38.2 ft. Tree dead, scribing visible.
Fir Tree S.31 1/4°W., not N.31 1/4°W., 18.5 ft. Tree dead, scribing visible.
Hemlock Snag, dead, N.57°W. 17.2 ft., scribing visible.
Since 3 of the BT's mkd. in 1950 are now dead, I blaze & scribe 3 new trees:
8" D. Fir S.84°W. 40.2 ft. Mkd: T20S R6W S29 DCS BT.
8" D. Fir N.77°W. 7.8 ft. Mkd: S20 DCS BT.
13" D. Fir N.80°E. 28.0 ft. Mkd: T20S R6W S21 DCS BT.

75

1/4 Corner to Sections 26 and 25.
Found - Rock Set by McClung for 1/4 Cor. Mkd: thus "1"
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
T20S R6W 1/4 S26/S25
New BT's: 43" D. Fir N.85°W. 21.5 ft. Mkd: 1/4 S26 CS BT.
12" Hemlock S.81 1/2°E. 63.6 ft. Mkd: 1/4 S25 CS BT.

40

1/4 Corner to Sections 26 and 35.
Found - Old Fir Snag, 40", N.20°W. 9.2 ft. Old scribing visible "1/4 S BT".
No trace found of Laurel to S. W.
Set - Brass Cap at Cor. Mkd: County Surveyor's T20S R6W 1/4 S26 S35 Office, 1962
New BT's: 27" D. Fir N.18°E. 25.4 ft. Mkd: 1/4 S26 CS BT.
14" D. Fir S.45°E. 12.4 ft. Mkd: 1/4 S35 CS BT.
Note - Corner lies on West Slope, approx. 150 ft. W. of top of ridge.

41

Section Corner to Sections 19 - 20 - 29 - 30.
Found - BT's. in Secs. 20 and 30 as described in the gov't notes but the ones in Sec. 19 and 29 were down and rotted so I mkd:
30" R. Fir bearing N.48°W. 41 lks. T20S R6W S19 BT.
48" R. Fir bearing S.44°E. 66 lks. T20S R6W S29 BT.
There were no signs of a post left so I set a 4" Dogwood Post Mkd: S19, 20, 29 and 30 according to the notes on the 2 Bearing Trees left standing.
Note - This corner was found by Milo E. Godfrey, Deputy, Feb. 8, 1962, See C. S. File No. 52/104 for his notes.

42

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy and Clebe Putnam
February 1962
C. S. File No. 49/89

A. H. Hinkson
July 3, 1937
Sent by
Lane Co. Surv.
February, '62
See also Lane
County File
C.S. No. 53/1

FD OK 496
Roberts
M123-60