

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 20 S. T. S. R. 6 W. R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

48

Weyerhaeuser Co.  
By Wm. L. Wilt,  
Land Agent  
1/13/61  
S. File  
No. 53/1

1/4 Corner between Sections 22 and 27.  
From Orig. GLO Notes, 1950, Found Brass Cap & BT's. as follows:  
32" Hemlock N. 7 1/4° W. 82 lks., good condition.  
40" Cedar S. 44 1/4° W. 9 lks., good condition.  
Retracement Notes - Plates, "W" Nails on:  
44" Cedar N. 56° E. 37.5 feet  
40" Cedar S. 44° W. 5.0 feet.

Weyerhaeuser Co.  
Jan. 9, 1963  
C. S. File No. 53/102  
Page No. 3

Closing Corner to Sections 30 and 31. Found - Sandstone 16 x 8 x 12 ins. well above ground & firmly set.  
On top side is marked "+" & "CC", also Wilford Haines' "T" Iron.  
24" Fir N. 37 1/2° E. 12.5 ft., now 42" Fir (green) face open, shows scribing.  
24" Fir S. 56° E. 14.5 ft., now 42" Fir (green) healed face, unopened.  
24" Fir S. 34° W. 49.5 ft., now 38" Fir Stump, shows bottom old face.  
10" Maple N. 14° W. 15.8 ft., no trace found.  
Marked the following trees with "W" Nails & Plate.  
42" Fir N. 31° E. 15.0 ft. (Orig. BT.)  
42" Fir S. 67° E. 10.8 ft. (Orig. BT.)  
38" Fir Stump S. 37° W. 46.0 ft. (Orig. BT.)  
4" Chinq. N. 66° W. 13.0 ft.

Wm. L. Wilt, Land Agent

Wilford N. Haines  
Found & Reported by M. E. Godfrey, Deputy  
February 1962  
C. S. File 49/89 See Haines Map M 21 - 72

C. C. to Secs. 30 and 31.

Note - This corner reported found by M.E.G. 1962.  
Same as corner listed above.

Found - Sandstone Rock, 16 x 8 x 12 ins. above ground, firmly set.  
1 notch on S. Side, "+" & "CC" on top, Haines' "T" Iron alongside.  
42" Fir N. 30° E. 16.6 ft. (not N. 37 1/2° E. 12.5 ft.) prev. opened, scribing "S30" visible on old face. Tree in good condition.  
42" Fir S. 63° E. 12.6 ft. (not S. 56° E. 14.5 ft.) Shows very good scar. Didn't open. Tree in good condition.  
38" Fir Stump S. 37° W. 47.5 ft. (not S. 34° W. 49.5 ft.) Chopped open & found bottom of old scar with axe marks, just below top of stump. Apparently scribing all on log which was gone.  
No trace of Maple to N. W.

Closing Corner to Sections 19 and 30. Corner found O. K.

Found - Haines' "T" Iron at Corner.  
Orig. 7", now 60" Fir N. 73° E. 11.2 ft. Has been prev. chopped open & good scribing visible. Apparently bark scribed "T20S R6W S19BT363"  
18" D. Fir S. 69° E. 40.2 ft., scribed in wood, pitched over, cannot read scribing, about 4 years old.  
Stump Hole & Maple shoots S. 32 1/2° E. 20.5 ft.  
No trace of Orig. N.W. & S.W. BT's.

Cor. to Sections 24 & 25 only, T20S R7W. Found O. K.

Found - Haines' "T" Iron at Corner.  
66" Fir S. 5° W. 137.3 ft., shows old scars.  
Old Fir Snag, badly decayed N. 82° E. (notes call for N. 80° E.) 47 ft., Too far gone to find any scribing.  
48" Fir N. 47° W. 47.8 ft., bark scribed "T20S R7W S24 BT.363" & Haines' metal disc.  
No trace of Maple BT., notes call for 6" Maple N. 43° W. 44.2 ft.  
Note - This corner bears S. 209.5 ft. from CC. Secs. 19 & 30, T20-6W, (See Cor. No. 51). Todd's field notes call for this corner to be south 255.4 ft. from CC Secs. 19 & 30.

1/4 Corner to Sections 29 and 32.

Found - Stump of Cedar S. 85° E., gone See. Ren. #10.  
Stump of Fir N. 36° E. on fire, (scribe visible)  
Set - New "T" Iron by Creek, from which  
New BT's: 14" Maple S. 45° W. 37.8 feet  
12" R. Cedar N. 31° E. 168.7 feet.

Wilford N.  
Haines  
Nov. 1965  
C. S. File  
No. 51/309

Nov. 30, 1965

53

FD. T. Iron & Stump  
3 BT's - 6/91  
D. Peel  
m113-45

FD. T. Iron  
3 BT's  
D. Peel  
m113-45

WILFORD N. HAINES' CORNER NO. 77