

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 20 T. S. R 6 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

C O N T - - -

59

From hole BT's bear:
 Orig. 30" now 52" cedar with well healed blaze bears N.36°E., 69.3 ft.
 Orig. 20" now 48" sawed fir stump with well healed blaze bears
 S.82°W., 58.7 ft.
 Orig. 20" now 48" sawed fir stump with no blaze visible bears
 N87°W., 79.2 ft.
 14" fir, Ren. #26A, now 18" with well healed blaze bears N.45°E., 32.3'
 14" fir, Ren. #26A, now 20" with well healed blaze bears S.78°E., 24.5'.
 20" cedar, Ren. #26A, now 29" with well healed blaze bears S.75°W.,
 97.0 ft.
 24" madrone, Ren. #26A, now 26" stump bears N.18°W., 104.9 ft.
 16" fir per resurvey, now 26" with well healed blaze bears N.6°E., 52.8'
 16" fir per resurvey, now 24" with well healed blaze bears
 S.59°E., 35.6 ft.
 6" fir per resurvey, now 16" with well healed blaze bears S.37°W.,
 99.7 ft.
 6" fir per resurvey, now 10" with well healed blaze bears
 N.22°W., 108.9 ft.
 Set - Since found hole fits well, I reset found brass cap in its original
 hole and add the marks 1983 to cap.

Gregory Quibell,
 Deputy, Doug. Co.
 Surveyors Office
 John Powell
 Randy Smith
 May 10, 1983
 C.S. 62/7

5/10/83

1/4 Corner for Secs. 27 and 34.
 Set - 1 1/2" x 36" alum. pipe with 3 3/4" alum. cap with magnetic insert
 marked Oregon State Dept. of Forestry. Set 30" in ground.
 New BTs - 25" fir, N.36°E., 15.2 ft.
 34" fir, S.22°E., 40.4 ft. with yellow metal location poster.

60

Center 1/4 corner for section 34.
 Set - 1 1/2" x 36" alum. pipe with 3 3/4" alum. cap with magnetic insert
 marked Oregon State Dept. of Forestry. Set 34" in ground.
 New BTs - 13" fir, S.84 1/2°W., 34.8 ft. with yellow metal location poster.
 12" fir, S.36°E., 35.1 ft.
 4" x 4" x 72" white painted cedar post bears N.05°E., 1.1 ft.

61

*1130-31
 Fook By D Edwards 9/1998*

1/4 Corner for Section 34 only, (south).
 Set - 1 1/2" x 36" alum. pipe with 3 3/4" alum. cap with magnetic insert
 marked Oregon State Dept. of Forestry, 30" in ground.
 New BTs - 10" hemlock, N.42°W., 24.5 ft. with yellow metal location poster.
 34" fir, N.77°W., 46.2 ft.
 4" x 4" x 72" white painted cedar post, N.36°E., 1.8 ft.
 Corner falls in center of old road, course N.73°E., from S.24°W.

62

Closing Corner for Sections 5 and 4 only of T.21-6
 Found - No evidence of original corner found.
 A 3/4" "T" iron iwth a 1" brass washer attached to top is firmly
 set and protrudes approx. 2" above ground. Ren. #4 in T.21-6
 Search made for original bearing trees-no evidence found.
 From Ren. #4, a 12" Fir now 23" DBH D. fir with a fully healed
 single blaze bears S.04 3/4°E., 103.3 ft. distant. (Record
 S.02°E., 103.3 ft.)
 From Ren. #4, an 18" now 29" DBH D. fir with a fully healed single
 blaze bears S.80°W., 15.3 ft. distant as per record.
 We perpetuate corner position established in Haines survey and recorded
 in Renewal #4 of T.21-6 by adding a new bearing tree as follows:
 A 5" DBH D. fir scribed "X BT" bearing S.77°E., 8.5 ft. distant.
 Monument is on wide low bench near foot of steep easterly slope.

63

2/19/88

Section Corner for 29, 30 31 and 32
 Found - Haines "T" Iron Ren #11
 42" Fir N 59 3/4°E , 37 4 ft bark scribed
 28" Fir S 62 3/4°W , 40 6 ft closed face
 31" Fir stump S 16 3/4°E , 21 3 ft - Weyco tag and "W" nail
 (Distance to "W" nail) (not of record)
 41" Fir N 47 1/2°W , 37 8 ft preveiously opened to visible
 scribing (Not of record)

64

6/91

Llq D. Smith
 LS 101
 For Oreg. Dept of
 Fo stry
 November, 1983
 M 95 - 49

Douglas County
 Surveyors Office
 S.J. Flause
 R. Smith
 Feb. 19, 1988
 C.S. 62/50

Donald Peel - For:
 Weyerhaeuser Company
 June 25, 1991
 M 113 - 45

RE-OPENED BY W. W. W. 76