

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

David Edwards
For: Roseburg
Resources Co.
June 1998
CS File 65/18-2 A&B
M 130-2

1/4 Cor. Secs. 27 & 28
Set - 3 1/2" dia., brass cap on aluminum post. 100
8" dia. Chinquapin, bears N.78°E., 15.22'.
7" dia. Fir, bears S.40°W., 16.33'.
10" dia. Fir, bears., S.88 1/2°W., 20.14'.
10" dia. Chinquapin, bears N.52°W., 6.15'.
Note - BTs are scribed according to the 1972 BLM Manual, are measured to the center of tree at root crown.

1/4 Cor. Secs. 26 & 27 101
Set - 3 1/2" dia., brass cap on aluminum post.
10" dia. Alder, bears N.25°E., 57.20'.
13" dia. Alder, bears S.39°E., 12.38'.
18" dia. Ash, bears S.20°W., 53.30'.
24" dia. Ash, bears N.59°W., 7.0'.

Center 1/4 Sec. 26 102
Set - 5/8" x 48" steel pin w/alum. cap.
11" dia. Hemlock, bears N.67°E., 9.30'.
13" dia. Alder, bears S.3°E., 57.40'.
19" dia. Alder, bears S.75°W., 11.42'.
10" dia. Hemlock, bears N.6°W., 20.48'.

Les Roberts
For: Seneca Jones
Timber Co.
April 1999
M 131-45

Corner of secs. 19, 20, 29 & 30 103
Found - 1966 Douglas Co. iron pipe & brass cap. (Ren. #53)
60" Fir, N.45°E., 17.8' (scar vis.), 1891 BT.
Vertical Rock BO (3.0' x 10.0') bears S.68°E., 17.7', mkd: "29 x BO" by Haines.
Set - 6" Fir, N.70°E., 10.8 ft., (scribed/metal washer/painted red)
8" Fir, N.51°W., 14.6 ft., scribed/metal washer/painted red)
10" Fir, S.76°W., 7.3 ft., scribed/metal washer/painted red)

1/4 cor. Secs. 20 & 29 104
Found - 2 1/2" alum. pipe with alum. cap set by Les Roberts in survey M99-7. (Ren. #90)
38" Fir, S.34°W., 32.0 ft., (scar vis.) 1961 BT (Haines 1961 BT NW BT is downed)
New BT - 8" Maple, N.9°E., 5.6' scribed/metal washer painted red)

R. Ward
3/2001
M136-60
C.S. File
65/36-17 A-L

1/4 Cor. Secs. 25 & 26 105
Found - 1"x1" Haines T iron. (Ren. #13)
47" D.Fir bears N.39°W. 23.6 ft. bark scribed.
40" D.Fir bears N.15°W. 15.9 ft. healed face.
60" D.Fir bears N.11°E. 75.0 ft. bark scribed.
New BT - 24" D.Fir bears S.34°E. 56.8 ft. blazed, scribed "1/4 S24 BT"