

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T. S. R. 7 W. R. W. W. M.

HOKE-CHARMAN CO., EUGENE, ORE. 21887

44

Corner to Sections 24 & 25 only, T20S R7W. Corner Found O. K.
Found - Haines' "T" Iron at Corner

66" Fir S. 5° W. 137.3 ft., shows old scars.
Old Fir Snag, badly decayed N. 82° E. (notes call for N. 80° E.)
57 ft., too far gone to find any scribing.
48" Fir N. 47° W. 47.8 ft., bark scribed "T20S R7W S24 BT 363"
& Haines' metal disc.

No trace of Maple BT., notes call for 6" Maple N. 43° W. 44.2 ft.

Note - This corner bears South 209.5 ft from CC. Secs. 19 & 30,
T20-6W. (See Ren. No. 43) Todd's field notes call for
this corner to be south 255.4 ft. from C. C. Secs. 19-30.

Wilford N. Haines
C.S. File No. 49/89
February 1962
Haines Map M 21 - 72
C.S. File No. 51/309
February 1965
Renewed Corners
Wilford N. Haines

45

South $\frac{1}{4}$ Corner Section 35 only.

Found - 20" Fir N. 33° E. 7 lks., now burned stub, good scribe.
24" Fir S. 24° E. 10 lks., now windfall, scribe still in stub.

Set - 1" x 1" x 36" "T" Iron and scribed:
48" Fir N. 73° W. 33.5 feet.
44" Fir N. 48 $\frac{1}{2}$ ° E. 37.5 feet.

$\frac{1}{4}$ Corner to Sections 34 and 35.

Found - Old cutting lines East & South.
Decomposed Sandstone (no marks).
Stub of Fir S. 25° W. 42 lks.

Set - 1" x 1" x 36" "T" Iron by Stone
No new bearing trees.

By rough measurement, this point is 2622.0 ft. S. of Corner
to 26 - 27 - 34 - 35.

$\frac{1}{4}$ Corner to Sections 33 and 34.

Found - Fir with good scar N. 10° W. 6 lks.
Rock for Corner.

Set - 1" XL" X 36" "T" Iron by Rock & Scribed:
8" Fir S. 56 $\frac{3}{4}$ ° E. 18.0 feet.
14" Fir S. 89° W. 6.6 feet.

Section Corner to Sections 27 - 28 - 33 - 34.

Set - 1" xl" x 36" "T" Iron from Orig. Fir BT., now down.

Scribed - 10" Maple N. 80° W. 51.4 feet.
12" Hemlock N. 8 $\frac{1}{2}$ ° E. 51.5 ft.
14" Alder S. 14° W. 23.0 ft.
18" Alder S. 62 $\frac{1}{2}$ ° E. 10.5 ft.

$\frac{1}{4}$ Corner to Sections 27 and 34.

Found - Stump of Orig. BT's: Cedar S. 28° W. 55 lks.
Cedar N. 23° E. 105 lks.

Scribed - 12" Fir N. 49 $\frac{1}{2}$ ° E. 26.0 ft.
16" Fir S. 49 $\frac{1}{2}$ ° E. 7.1 ft.

$\frac{1}{4}$ Corner to Sections 34 only. (sour)

Found - "X" on Rock. - Fir BT is down. - Maple is gone

Drove - "T" Iron in ground 1.2 ft. N. of "X".

Scribed - 28" Fir N. 77° W. 99.5 ft.

$\frac{1}{4}$ Corner to Sections 32 and 33.

Found - "T" Iron, see Ren. #20 & #33.

R. Cedar Stump, Scribed by Co. Surv., N. 72° E. 23.0 ft.
New BT: 14" Hemlock N. 61° W. 165.9 feet.

46

47

48

49

50

51

Nov. 30, 1965

Wilford N. Haines
Nov. 1965
C.S. File 51/309

Fd. T. Iron
3 BTs - D. Peel
4/91 M 113-45

SEE ALSO H-3

RE-NEWED CORNER NO. #76