

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T.S. R. 7 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

52

$\frac{1}{4}$ Corner to Sections 29 and 32.
Found - Sandstone 4"x8"x12" Mkd: "S $\frac{1}{4}$ " on S. Side & "X" on top, not recorded in original notes.
Haines' "T" Iron & BT. as recorded in Ren. #8. ~~99~~
36" Fir N. 73° E. 8.2 ft., down & shows scribe on partially healed scar.
Orig. 16", now 30" Fir S. 4° W. 13.2 ft., shows fair scar. Do Not Oper
Orig. 16", now 28" Fir N. 30° E. 6.6 ft., lying face down, scribe visible, We do not open.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T20S R7W $\frac{1}{4}$ S 29 S 32

New BT's: 14" Hemlock N. 63° E. 29.1 ft. Mkd: $\frac{1}{4}$ S29 CS BT.
8" Yew S. 70 $\frac{1}{2}$ ° E. 41.3 ft. Mkd: $\frac{1}{4}$ S32 CS BT.

9/8/66 - CORNER O.K. - S. EDGE of OXBOW FIRE

Section Corner to Sections 19 - 20 - 29 - 30,

Found - Haines' "T" Iron & Bearing Object as recorded in Ren. #10.
Vertical Rock 3.0 ft. high x 10.0 ft. long Mkd: "S29 x 80".
Orig. 48, now 56" Fir N. 45° E. 17.8 ft., alive, prev. opened & shows "20" scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T20S S 19 S 20 R7W S 30 S 29

New BT's: 11" Maple S. 42° E. 24.2 ft. Mkd: T20S R7W S29 CS BT.
6" Hemlock S. 11° W. 33.4 ft. Mkd: T20S R7W S30 CS BT.
No tree available to N. W.

Note - This corner lies on very steep, N. W. slope approximately 75 feet W. of top of spur, sloping N. ~~103~~

Vernon "Ray" Tracy
Mike Stone & Jerry Layne
February 8 & 9, 1966
C. S. File No. 54/22

53

$\frac{1}{4}$ Corner to Sections 16 and 17.

Found - Sandstone 20"x16"x6" mkd. "S $\frac{1}{4}$ " on West face & charred remains of BT's., as follows:
Orig. 30", now 36" Fir N. 61° E. 9.2 ft. Now 60 ft. high Snag, find old axe marks, no scribe.
Orig. 20", now 28" Fir S. 80° W. 4.6 ft., shows fair scar, badly burned, we do not open. Tree may live.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T20S R7W (Set Rock Alongside) $\frac{1}{4}$ S 17/S 16

New BT's: 56" D. Fir N. 37° E. 28.9 ft. mkd. $\frac{1}{4}$ S16 CS BT(alive when marked)
50" D. Fir S. 31° W. 25.5 ft. mkd. $\frac{1}{4}$ S17 CS BT(alive when marked)

Note - This corner lies on very steep, N.W. slope, approx. 170 ft. South of spur. Corners west in OxBow burn.

54

Section Corner to Sections 16 - 17 - 20 - 21,

Found - No trace of Rock called for.
Orig. 24", now 50" Fir N. 8° E. 26.4 ft. Open & find "S1" scribe under 70 to 75 years growth. Appears that tree will live, even though badly burned. No trace of other BT's.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T 20 S R 7 W S 17 S 16 S 20 S 21

New BT's: 11" D. Fir N. 6° E. 8.7 ft. mkd. T20S R7W S16 CS BT.
9" D. Fir S. 9° W. 21.6 ft. mkd. T20SR7W S21 CS BT.
15" Maple S. 30° E. 8.0 ft. mkd. T20S R7W S20 CS BT.
20" D. Fir N. 25° W. 70.0 ft. mkd. T20S R7W S17 CS BT.

Note - Corner lies on very steep, west slope in OxBow Burn.

55

Section Corner to Sections 29 - 30 - 31 - 32

Found - Sandstone 18"x14"x8" mkd. with notch on S. edge & 5 notches on E. edge & "X" on top, tipped out of position. ~~98~~
Orig. 18", now 36" Cedar N. 3° E. 15.8 ft., shows faint scar. "Rescribe".
Orig. 36", now 48" Cedar S. 87° E. 24.4 ft., shows good scar, do not open.
Orig. 30", now 51" Cedar S. 8° W. 44.9 ft., shows faint scar. "Rescribe".
Orig. 20", now 46" Cedar N. 74° W. 79.2 ft., shows faint scar, do not open.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T20S R 7 W S 30 S 29 S 31 S 32

(Set Rock alongside) 1966
New BT's: See page over

56

RE-RENEWED, SEE COUNTY FILE NO. #83