

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T. S. R. 7 W. R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21801

61

$\frac{1}{4}$ Corner to Sections 31 and 32.
Found - Unrecorded Haines' "T" Iron & also, unrecorded Sandstone,
18"x14"x9" mkd. " $\frac{1}{4}$ " on W. face, appears old.
Orig. 48", now 60" Fir S. 66° E. 29.0 ft., slope dist. shows
partial face on bark. Badly burned, no scribe found. Alive.
Orig. 66", now 68" Fir, S. 88° W. 25.1 ft., slope dist. Has
" $\frac{1}{4}$ S BT" bark scribe appears to be Orig. No Snag.
Rescribe Orig. S. E. BT. " $\frac{1}{4}$ S 20 CS BT".
Do not mark any new Bearing Trees at this time due to high rate
of snags falling.

62

$\frac{1}{4}$ Corner to Sections 19 and 20.
Found - GLO Brass Cap mkd. " $\frac{1}{4}$ S19/S20 T20S R7W 1960".
13", now 15" Fir S. 57° E. 97.7 ft., Dead, Burned Face.
(Rescribe " $\frac{1}{4}$ S20 CS BT".
All other BT's, now burned off at ground level.
New BT: 36" Burned Fir Stump N. 75° W. 28.2 ft. mkd. $\frac{1}{4}$ S19 CS BT.
Set - Red Steel Fence Post alongside Brass Cap.
Note - Corner lies on old N. - S. cutting line. No live trees close.
9/22/66

63

$\frac{1}{4}$ Corner to Sections 20 and 21.
Found - Sandstone 24" x 14" x 12" mkd. "X" on top & " $\frac{1}{4}$ " on W. face.
Orig. 36", now 50" Fir West 38.8 ft., down & burned, we
open on under side & fine "4 B" scribe.
No trace of other Orig. BT.
Set - Brass Cap at Cor. Mkd: County Surveyors T 20 S R 7 W
Office, 1966 $\frac{1}{4}$ S 20/S 21.
Reset Rock Alongside. B.C. 74
New BT's: 8" Hemlock, Dead, S. 2° W. 27.8 ft. mkd. $\frac{1}{4}$ S 20 CS BT.
11" Maple Snag N. 69° E. 12.0 ft. mkd. $\frac{1}{4}$ S21 CS BT.
Note - No live trees available. Corner lies approx. 130 ft. N. of creek,
Course S. 60° W.
10/12/66

64

Section Cornerto Secs. 3 - 4 - 9 - 10.
Found - Orig. Stone, now missing, from which a:
36" Fir bears S. 12° E. 54 lks.; now 30" burnt tree with
scribed "T 2" visible.
24" Fir bears S. 87° W. 54 lks.; now 30" burnt tree with scribes
"S 9" visible.
30" Fir bears N. 19° W. 8 lks.; now 36" burnt and down with
face grown over.
Set - 1 $\frac{1}{2}$ " x 36" gal. I.P. with 3" br. cap mkd: Ore.St.Bd. of Forestry
T20S R7W S3 S4S9 S10 1967 RS563", 30" in gr., in edge of
hole of uprooted NW BT, and from which a:
38" Burnt Fir bears S. 66° W. 50.6 ft.; scribed T20S R7W S10 BT RS563.
44" Burnt Fir bears N. 26° E. 28.4 ft.; scribed T20S R7W S3 BT.
36" Burnt Fir bears N. 60° W. 38.5 ft.; scribed T20S R7W S4 BT.
Set - 4" x 4" x 72" white painted Cedar post, 1 ft. SE. of corner pipe.
Ore.St.Forestry Dept. metal locatdon poster on NE BT.
This corner on the Douglas-Lane County Line.

65

$\frac{1}{4}$ Corner to Sections 9 and 10.
Reestablished by single prop. measurement. ^{33" IN GROUND}
Set - Ore.St.Bd. of Forestry 1 $\frac{1}{2}$ "x36" Gal I.P. from which:
20" Burnt Fir Stump S. 87° W., 12.0 ft. with YMLP.
26" Burnt Fir S. 50° E. 20.0 ft., YMLP.
 $\frac{1}{4}$ "x4"x72" White Painted Cedar Post NW. 1.0 ft.

MICROFILM TO HERE 10/67

66

$\frac{1}{4}$ Section Corner Common to Sections 26 and 35.
Found - 24", now 48" Cedar, S. 30° W., 15 lks.
Set - 5/8" x 48" Steel Rod for $\frac{1}{4}$ Corner.
Rescribed: 48" Cedar S. 30° W. 15 lks.
Scribed: 48" Maple N. 22° W. 42.4 ft.

Nov. 17, 1967

Vernon "Ray" Tracy
Jack Heritage & ELM
Sept. 1966
C. S. File No. 54/22

State of Oregon - Dept. of Forestry
Wiljq E. Green
March, 1967
C.S. File No. 55/36
Map File M 34 - 10.

Wilford N.
Haines
11/17/67
C. S. File
No. 51/309