

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

FO. OK 10/95 BY EDWARDS, M/22-71

67

1/4 Corner to Sections 21 and 22.
Found - Rock for corner, now a pile of sand.
40" Fir, now Snag, S. 36° E. 60 lks.
4", now 16" Fir, West 10 lks. (Rescribed this tree)
Set - 5/8" Steel Rod for Corner.
Note - This corner in Oxbow Fire area.

68

1/4 Corner to Sections 15 and 22.
Found - Rock with "X" and "S".
No old bearing trees.
Set - 5/8" Steel Rod west 2.35 ft.
Scribed - 12" Fir S. 52° W. 26.5 ft.
16" Fir N. 29° W. 11.4 ft.
Note - This corner in Oxbow Fire area - 60.0 ft. east of ridge
not 2.0 chains.

69

Section Corner to Sections 14 - 15 - 22 - 23.
Found - Rock with "X".
Set - 5/8" Steel Rod alongside.
Scribed: 24" Alder S. 72° E. 31.8 ft.
28" Fir N. 83° E. 40.5 ft.
10" Cedar N. 33° W. 42.7 ft.
16" Fir S. 02° W. 66.0 ft.

70

1/4 Corner to Sections 22 and 23.
Found - Alder Stub for W. Corner of Section 22.
Set - 5/8" Steel Rod 27 lks. east of W. corner on gravel
bar in creek for 1/4 corner.
Scribed - 20" Alder N. 64° E. 26.9 ft.
30" Maple S. 82° W. 72.0 ft.

71

Section Corner to Sections 22 - 23 - 26 - 27.
Found - Rock with "X". This rock was not in this position in
in 1946 when I first was at this corner.

Set - 5/8" Steel Rod by rock, corner appears to be S. & E.
of Rock, I did not have notes.

Found - Orig. 48" Fir N. 07° E. 95 lks. 55.40 ft.
Orig. 36" Cedar N. 59° W. 118 lks. 75.87 ft.
Orig. 48" Cedar Stub. S. 66° E. 54 lks. 41.03 ft.
(Dist. measured to center of BTs.)

8/5/74 (SEE "NGI FO" INFO. IN C.S. 59/18)

72

Center 1/4 Corner to Section 22.
Set - 5/8" Steel Rod.
Note - This corner on slide that made Pearl Lake.
Scribed - 26" Fir N. 47° E. 27.0 ft.
26" Fir S. 87° W. 67.2 ft.

73

Section Corner to Sections 20 - 21 - 28 - 29.
Found - "T" Iron & BT's. as recorded in Ren. #12 & #58.
Also steel fence post.
24" Hemlock N.81°W. 67.0 ft., now high stumped, drive 5/8"x 30"
Iron Rod in ground below blaze.
22" D. Fir, S. 86°W. 94.9 ft., now turned out & slid downhill.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 20 S R 7 W
Office S 20 | S 21
1968 S 29 | S 28
New BT: 63" D. Fir Stumps S. 80° E. 120.1 ft. mkd. "T20S R7W S28 CS BT.
(Drive 5/8"x 30" I. R. 18" into center of stump)
Reset "T" Iron & steel fence post alongside Brass Cap.
This corner lies on S. slope approx. 150 ft. N. of small creek, corners

Wilford N. Haines
For Woolley Logging
Nov. 17, 1967
Map File M 35 - 3

Vernon "Ray" Tracy
Jack Heritage & V. Pa
May 6, 1968
C. S. File No. 54/22

RE-RECORDED CORNER NO. #81