

Douglas County Surveyor's Record of  
Government Corners Renewed

T 20 T. S. R 7 R. W. W. M.

FOX-CHAPMAN CO., EUGENE, ORE. 97401

Les Roberts  
LS #1039  
Sept. 2, 1989  
C.S. 63/85

Center 1/4 Corner for Section 33  
Found - 1984 BLM brass cap set firmly in the ground in recently logged unit.  
11" hemlock stump, S.84°W., 48.6 ft. (scar vis.) 1984 BT.  
20" fir stump, N.20°W., 65.1 ft. (scar vis) 1984 BT.  
Set - 72" alum. post, with land survey sign bolted to, beside BC.  
New RP - 20" cedar stump, S.77°W., 46.1 ft. to spike driven into base of stump, stump not scribed.  
Soaked sides and tops of stumps with a wood preservative. Covered tops of stumps with 0.020 thick sheets of aluminum.

94

9/2/89

Donald Peel  
For: Weyerhaeuser  
Co.  
June, 1991  
M 113 - 45

1/4 Corner for Section 30 only of T.20-6  
Found - 1 1/2" Iron pipe with DCSO brass cap dated 1962. Ren. #24  
24" Fir N.34°E., 25.0 ft. closed face.  
22" Rotten Fir stub S.62°W., 7.1 ft. previously opened to visible scribing. (Rec. S.57 1/2°W)  
16" Fir S.28 1/2°E., 25.7 ft. closed face - BLM tag. Not of record 6/91

95

D.A. Edwards  
For: Pete Hopkins  
Oct. 1995  
M122 - 71 CS 63/100-4

Section Corner for Sections 21, 22, 27 & 28  
This corner was determined by proportion and lies in a large clearcut and therefore no bearing trees could be scribed. The corner itself falls on the nearly vertical face of a large boulder and could not be monumented.

96

New Accessories -  
Reference monuments set are 5/8" x 30" steel pins with red plastic cap mkd. "D.A. EDWARDS-LS 2339"  
Ref. mon. brs. N.2°23'00"E., 27.24 ft.  
Ref. mon. brs. N.59°17'13"E., 24.50 ft.  
Ref. mon. brs. S.36°14'31"E., 16.13 ft.  
Ref. mon. brs. S.69°03'32"W., 36.62 ft.

Center 1/4 for Section 27  
Set - 5/8" x 30" steel pin w/red plastic cap mkd. "D.A. EDWARDS-LS 2339"  
New Accessories -  
14" diam. Chinquapin bears N.64 1/2°E., 26.9 ft.  
9" diam. Fir bears S.49 1/2°E., 17.00 ft.  
18" diam. Alder bears S.8°W., 23.90 ft.  
8" diam. Maple bears N.69°W., 10.10 ft.

97

Mark Smalley  
For: Roseburg Forest  
Products  
Crew: Bill Olson &  
Ralph McMannis  
12/18/1996  
C.S. File 65/20-18

Cor. Secs. 29, 30, 31, & 32  
Fd - 1966 DCSO brass cap. (Ren. # 56)  
36" Cedar snag, N.3°E., 24 lks, scribe visible.  
49" Cedar stump, N.72 1/2°W., 120 lks.  
49" Cedar stump, S.8°W., 68 lks.  
72" Cedar stump, S.87°E., 39 lks.  
Set - 27" Maple N.26°W., 39.5 ft., scribed "S30 BT"  
11" Alder S.53°W., 35.5 ft., scribed "S31 BT"  
14" Alder S.2°E., 24.9 ft., scribed "S32 BT"  
9" Alder N.69°E., 48.0 ft., scribed "S29 BT"

98

Corner falls in draw.

(CS file 65/20-18)

1/4 Cor. Secs. 29 & 32  
Fd - 1966 DCSO brass cap. (Ren. #52)  
14" Hemlock, N.63°E., 29', rotted stump.  
8" Yew, S.70 1/2°E., 41.3', down - alive.  
36" Fir, N.73°E., 8.2', dead-down.  
Set - 12" Hemlock, N.63°W., 16.5', scribed "1/4 S29 BT"  
13" Hemlock, N.79°W., 17.1', scribed "1/4 S29 BT"  
17" Hemlock, S.76°E., 53.6', scribed "1/4 S32 BT"  
12" Fir, S.28°W., 22.8', scribed "1/4 S32 BT"

99

(CS file 65/20-19)