

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 20 S **T. S.** R 8 W **R.W.W.M.**

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

12

Sec. Corner common to Secs. 17, 18, 19, & 20.
 Found - 1-1/4" galv. I.P. w/ 2-1/2" G.L.O. B.C., marked: T20S R8W
 S18 S17 S19 S20 1954, (found buried 12" in slide area, leaning
 NE...I reset to vertical), from which:
 Fd BTs - 52" cedar stump, face visible, bears N.56°20'E.,84.3-ft.
 (rec. per 1967 Remonumentation N.56°E.,83.82-ft.)
 45" fir stump bears S.78°05'E.,13.0-ft. (rec. per original
 G.L.O. notes S.79°E.,12.54-ft.)
 46" snag w/ T20S R8W S19 BT visible, bears S.70°16'W.,34.3-ft.
 (rec. per orig.G.L.O. notes S.70°W.,36.96-ft.)
 New BTs- 6" D.Fir, scribed T20S R8W S17 BT, bears N.58°23'E.,40.5-ft.
 5" D.Fir, scribed T20S R8W S20 BT, bears S.13°30'E.,7.2-ft.
 5" D.Fir, scribed T20S R8W S19 BT, bears S.42°53'W.,18.2-ft.
 9" alder, bark scribed: T20S R8W S18 BT, bears N.58°47'W.,27.1-ft.
 3/83

Robert G. Dean, LS#1808
 &
 William J. Ruppert, LS#866
 For: International Paper Co.
 March 30, 1983
 M 93 - 80 & C.S. 58/204(N)

13

Sec. Corner common to Secs. 16, 17, 20, & 21.
 Found - 1-1/4" galv. I.P. w/ 2-1/2" G.L.O. B.C. Mkd:T20S R8W S17 S16
 S20 S21 1954, from which:
 Fd BT - 50" fir stump w/ T20S R8W S16BT visible, bears N.23°56'E.,
 123.5-ft. (rec. per 1967 Remonumentation N25°E.,123.42-ft.)
 New BTs- 7" D.Fir, scribed T20S R8W S20BT, bears S.52°25'W.,12.7-ft.
 7" D.Fir, scribed T20S R8W S17 BT, bears N.68°34'W.,37.0-ft.
 6" D.Fir, scribed T20S R8W S16 BT, bears N.14°27'E.,38.9-ft.
 7" D.Fir, scribed T20S R8W S21 BT, bears S.37°07'E.,38.6-ft.
 3/83

14

1/4 Corner for Sec. 34; and Sec. 3 of T21-8.
 Found - 24" fir stump, N.17°E., 10.5 ft. scribe visible-1950 BT.
 28" fir stump, S.6 1/2°W., 12.5 ft. (cut below scribe-orig. BT.)
 Reset - 1" iron pipe with GLO brass cap "1950" at slope distance from
 existing BTs.)
 Note: 1/2" rebar driven in center of BT stumps and 4" x 4" post
 found east, 0.5 ft. from corner point.

Darrel W. Baker
 L. #1978
 For International
 Paper Company
 Oct 25, 1984
 M 97 - 51
 C.S. 58/289

15

1/4 Corner Sections 2, & 35, T 19-8.
 Found - G.L.O. Iron Pipe 1" diameter with brass cap 6" above ground.
 BT's - 24" fir stump bears N 59°W, 33.9'. Marked "1/4 S 35 BT".
 21" fir stump bears N 67° E, 17.3'. Blaze rotted.
 New - 7" fir bears N49 1/2°W, 43.7' to spike marked "1/4 S 35 BT".
 BT's No other tree are available.

Richard Hintz
 International Paper Co.
 Dec. 1986 M103-6

16

South 1/4 Corner Section 12.
 Found - 1954 G.L.O. Brass Cap correctly stamped.
 BT's - Root hole bears N 47°E, 22.5'. 1960 BT Rec. N47°E, 22.4'.
 Root Hole bears S44°E, 58.0'. 1960 BT Rec. S44°E, 58.1'.
 26" fir stump bears S11°W, 36.8'.(Scribe Visible) 1967 BT
 rec. S10°W, 37.0'.
 New 6" Fir, bears S15°E, 18.8 '. (scribed/painted red.)
 BT's 12" fir, bears N46°E, 8.6'.(scribed/painted red)
 Note: Set aluminum fence post, with survey attention sign, wired
 to beside brass cap. Painted all BT's red. Corner lies on
 spur ridge sloping East.

Les Roberts
 For International Paper Co.
 Dec. 1986 M 103 - 63

17

West 1/4 Corner Section 12.
 Found - Found 1954 G.L.O. brass cap correctly stamped set firmly
 in the ground.
 BT's - A 10" fir stump bears S54°E, 14.5'(no marks). 1954 BT rec.
 S54 1/2°E, 31.0'.
 12" fir stump bears S65°W, 31.0'(no marks). 1954 BT rec.
 S63 1/2°W, 14.5'.
 21" fir bears S70°E, 40.5'(scar vis.). 1967 BT. rec.S71E,
 40.9'.
 Set - A 6" fir, bears N09°W, 25.9' (scribed/painted red).
 Note: Set metal fence post, with survey attention sign wired to, beside
 brass cap. Painted all BT's red. Corner lies on top of ridge. Ridge
 bears N.W. and S.E.