

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

N.W. Corner Section 30 only.

28

End - 1950 G.L.O. Brass cap set firmly in the ground.
20" Fir, S 58°W, 16.5' (Scar vis.), 1950 BT. Record S 58°E, 16.5'.
39" Fir, N 47°E, 19.8' (Scar Vis.), 1950 BT. Record N 47½°E, 19.8'.
See also Vol 43, Pg. 16711 for B.L.M. Renewal.

New Accessories -

72" aluminum post, with land monument survey sign attached to,
beside brass cap. Painted all bearing trees red.

Note - Corner lies on West slope about 200' South of creek. Creek
flows west. 3/93

Northwest Corner Sec. 6; SW Cor 31, T19-8

29

Found - 3½" Brass cap in good condition.

30" Fir, bears S.20°E., 57.1', healed face.

51" Hemlock, bears S.82½°W., 24.3', healed face.

46" Fir stump, bears N.53½°W., 49.4', no marks.

31" Cedar, bears N.3 ¾°E., 54.2', healed face.

New BT- 15" Hemlock, bears S.84½°E., 41.6', blazed & scribed "T20S
R8W S6 BT"

Note - Corner lies on a North facing bench.

North ¼ Corner Sec. 6: S ¼ Sec. 31 T19-8

30

Found - 1954 G.L.O. Brass cap out of ground - reset from existing
bearing tree.

32" Fir, bears S.56°W., 26.4', healed face.

1954 BT - blow down.

New BTs -

9" Fir, bears N.64°W., 18.2', blazed & scribed "¼ S31 BT"

5" Fir, bears S.85°E., 20.5', blazed & scribed "¼ S6 BT"

9" Hemlock, bears N.10°W., 26.8', blazed & scribed "¼ S31
BT"

31

By: Les Roberts
For: International
Paper Co
March 1993
CS 63/149
M 116 - 60

Wayne Donovan
L.S. # 2553
5/19/93
C.S.File 63/153