

Douglas County Surveyor's Record of
Government Corners Renewed

T 20 T. S. R 10 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97101

Fd. OK 2/92
BY R. STUNTZNER
M 114-80
7/92-Royce Hill
M 115-71

Daniel Baker PLS 1978
For: U.S. Forest Serv.
June 1986
M 102 - 12

111
1/4 Corner for Sections 30 and 31
Set - 2 3/8" x 30" alum. pipe with 3" alum. cap.
New BTs - 16" cedar, S.2 1/4°W., 18.1 ft. scribed "1/4 S31 BT"
16" cedar, N.87 1/2°W., 26.5 ft. scribed "1/4 S30 BT"
Set - 2 3/8" x 30" alum. pipe with 3" alum. cap as a reference point
bears S.89°25'40"W., 37.38 ft.
Note - 1/2" iron pipe (M 10-3) bears S.88°32'09"W., 98.2 ft. Ren. No. 1

112
Section corner for Secs. 30 and 31; and Secs. 25 and 36 of T.20-11
Found - 2 1/2" iron pipe with brass cap Ren. No. 38
7" dead chittum bears S.71 1/2°E., 27.4 ft. (Rec. NE)
63" fir, S.17 3/4°W., 73.4 ft. bark scribed
18" rotted maple, N.31 1/2°W., 24.6 ft.
16" cedar, N.16 1/2°W., 46.2 ft. closed face
New BT - 72" spruce bears S.72 3/4°E., 74.3 ft. scribed "T20S R10W S31 BT"

113
1/4 Corner for Sec. 30; and Sec. 25 of T.20-11.
Set - 2 3/8" x 30" alum. pipe with 3" alum. cap marked "T20S R11W R10W
1/4 S25 S30 PLS 1978 1986".
New BTs - 8" fir N.28°E., 11.0 ft. scribed "1/4 S30 BT".
9" Fir, S43 1/2°W., 16.9 ft. scribed "1/4 S25 BT".

114
Section Corner for Secs. 19, 20, 29 and 30
Found - 1 1/4" I.P. stamped brass cap (PLS 497-1983 Ren. #79
From which:
27"hemlock stump bears N.61°05'E., 15.1 ft. to a 1/2" x 30" I.R.
set in the top center (visible scribe on partially
healed blaze.)
24" fir stump bears S.82°05'E., 24.1 ft. to a 1/2" x 30"
I.R. set in the top center (healed blaze.)
42" fir stump bears S.61°10'W., 42.5 ft. to a 1/2" x 30"
I.R. set in the top center (no visible scribe on rotted blaze.)
37" fir stump bears N.15°27'W., 20.6 ft. to a 1/2" x 30" I.R.
set in the top center (visible scribe on rotted blaze.)
No previous record of Iron Rods in center of stumps.

115
Center 1/4 Corner for Section 19
Set - 2 3/8" x 30" al. pipe with 3 1/4" stamped al. cap marked:
T20S R10W C1/4 . S19 1987 PLS 497.
New Accessories:
16" maple bears S.62°E., 6.7 ft. scribed C1/4 S19 BT.
2 3/8" x 30" al. pipe with 3 1/4" stamped al. cap bears
S.1°46'W., 55.9 ft. (RM)

116
1/4 Corner for Sections 19 and 20
Set - 2 3/8" x 30" al. pipe with 3 1/4" stamped al. cap. Cap mkd.
T20S R10W 1/4 . S19 . S20 1987 PLS 497.
New BTs - 10" maple bears N.26°45'E., 26.4 ft. scribed 1/4 S20 BT.
18" maple bears S.25°30'W., 42.4' scribed 1/4 S19BT.

117
1/4 Corner for Sec. 6 and 5. See Ren#44
Set - A USFS 2 1/2" x 30" aluminum pipe with 3 1/4" aluminum
cap stamped "T 20S R10W 1/4 S6|S5 1987 PLS 1305".
New BT's - A 16" Maple bears N 7 1/4°E, 64.0 ft. Scribed "1/4 S5 1987".
New BO's - A U.S.F.S. 2 1/2" x 30" aluminum pipe with 3 1/4" aluminum
cap stamped "RM 1/4 S5 1987 PLS 1305" bears N 2°25'E, 313.0 ft
A U.S.F.S. 2 1/2" x 30" aluminum pipe with 3 1/4" aluminum
cap stamped " RM 1/4 S5 1987 PLS 1305" bears S9°46'W, 90.3 ft.

118
1/4 Corner for Sec. 5, and 32 of T19-10. See Ren#17
Found - A BLM 3" brass cap on a 2" galvanized iron pipe.
BT's - A 42" Douglas Fir bears S 78°W, 103.0 ft. Record S78 1/4°W 158lks.
10" Alder stump bears N 4°E, 36.0 ft. Record N4°E, 56lks.
New Bt's - A 22" Alder bears N 47 1/2°E 42.6 ft. bark scribed "1/4 S 32 BT"
34" Alder bears S 2 1/2°W, 117.7 ft., scribed "1/4 S 5 BT".

Richard Hintz
For: Siuslaw National
Forest
April 1987
M 104 - 9

James W. Prochnau
For: Siuslaw National
Forest M 104-51A&B
June, 30, 1987