

**Douglas County Surveyor's Record of  
Government Corners Renewed**

20 T. S. 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

Les Roberts LS1039  
For: International  
Paper & US Forest  
Service.  
December 1990  
M 111 - 33

Section Corner for Sec's 3, 4, 33 & 34 T. 19 R. 10 125  
Found - 1952 G.L.O. brass cap  
BT's - 12" fir S.53°E 13.7 ft. (scar vis.) 1952 BT.  
13" fir snag S.25°W. 7.3 ft. (scar vis.) 1952 BT.  
14" fir N.28°W. 10.9 ft. (scar vis.) 1952 BT.  
18" fir N.57°E 6.4 ft. (scar vis.) 1952 BT.  
Set - 2½" X 30" aluminum pipe and ~~XXXX~~ cap for reference monument  
Brass cap bears N.89°42'30"E., 63.06 ft. from reference  
monument. See renewal # 22. T.19 R.10 12/90

Harvey Wilcox LS2244  
For: U.S.F.S.  
December 1990  
M 111 - 47 A - F

Section Corner for Sec's 30 & 31; & Sec's 25 & 36 of T.20 R.11. 126  
Found - 2½" brass cap on 2¼" IP. 14" above ground with 1" IP alongside.  
BTs Fnd-Original BT 32" maple, rotten face, tags, bears N.29°W., 25.30'.  
17" cedar, healed face, tags, bears N.20°W., 47.3 ft. Ren # 112  
76" spruce, visible scribe, tags, bears S.72°45'E., 74.3 ft.  
Cascara, dead, tags, bears S72°E., 27.6 ft.  
65" douglas fir, visible scribe, tags, bears S.18°W., 70.3 ft.  
Set R.M. Std. U.S.F.S. disk "RM T20S R10W S30 S.88°20'W 43.40'  
1990 RLS 2244" bears N.88°20'E., 43.4 ft. 12/90

Harvey Wilcox LS2244  
For: U.S.F.S.  
December 1990  
M 111 - 47 A - F

*FD. OK BY STUNTZNER  
2/92  
M114-80*

South West Corner for Section 31. 127  
Found - 2½" brass cap on 1½" IP 12" above ground, with 1" IP along side.  
BTs Fnd 30" maple S.E. trunk of tree with healed face, tags,  
bears N.14°W., 15.2 ft. Ren. # 25  
21" douglas fir, healed face, tags, bears N.80°E., 83.6 ft.  
37" douglas fir, healed face, tags, bears S.77°15'E., 42.9 ft.  
39" maple, healed face, tags, bears S,27°W., 11.2 ft.  
Note - This tree trunk has blown down (39" maple) retagged another  
trunk of same tree, it bears S,25°30'W., 14.2 ft.  
Set R.M-Std. U.S.F.S. disk "RM T20S R10W S31 S88°09'W 52.91 1990 RLS2244"

Ronald Stuntzner  
For: The Travelers Co  
Feb. 1992  
M 114 - 80

Center 1/4 for Section 31 128  
Set - 3/4" iron rod with 2" aluminum cap marked "C¼ S31 1992 LS 1342"  
BT's - 13" Maple with face scribed "C¼ S31 BT" & tag bears N.26°W, 14.95'  
18" cedar with face scribed "C¼ S31 BT" & tag bears N.16°E, 14.85'  
39" cedar with face scribed "C¼ S31 BT" & tag bears S.23°E, 43.25'  
44" cedar with face scribed "C¼ S31 BT" & tag bears S.17°W, 26.65'  
4/92

Douglas County  
Surveyors Office  
R.W. Smith  
S.J. Flause  
J. Pike  
May 6, 1992  
C.S. 64/26

1/4 Corner for Section 1; and Section 36 of T.19-10 129  
Found -A 2½" dia. 1952 BLM brass cap on a 1½" O.D. Iron Pipe firmly  
set and protruding approx. 3" above ground.  
A 36" Fir, now a fallen and partially rotted fir snag, with  
evidence of a fully healed single blaze, the root hole of  
which bears N.75°E., 39.6 ft. (as per record)  
A 54" Fir now a 45" DBH D. Fir with a fully healed single  
blaze bears S.86°E., 53.2 ft. (Rec. S.83°45'E., 52.1 ft.)  
(previously recorded dia. appears to be erroneous)  
New BTs - A 55" DBH 80 ft. tall fir snag with a high, open cruisers  
blaze bears S.72°W., 57.8 ft.  
A 6" DBH Alder bark scribed "1/4 S1 CS BT" bears N.86 3/4°W, 30.7 ft. distant.  
Monument is on a south slope near bottom of very steep slope.  
Monument on an east-west cutting line with older clear cut to north  
Old growth to south. Monument is approx. 200 ft. south from a  
closed logging spur road end.

5/6/92