

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 20 S. T. S. R. 10 W. R.W.W.M.

KOIKE-CHAPMAN CO., EUGENE, ORE. 21681

John M. Powell & Crew  
C.S. File 53/66

Tom O. McCullough  
For: U.S. Forest Service  
Feb., 1970  
C.S. File No. 55/142

Tom O. McCullough  
For: U. S. Forest Service  
April, 1970  
C.S. File No. 55/148

SEPT. 68

55-9/83  
R. Spurr  
4/95-12

Closing Corner to Sections 6 and 7, T20-9W. 36  
Found - Concrete filled I. Pipe but Brass Cap broken off.  
Orig. 30", now 34" Cedar, alive, N. 37° E. 34.3 ft., shows good scar.  
We Rescribe "T20S R9W S6 CC CS BT".  
Orig. 40" Cedar, now 42" sawed stump, S. 82½° E. 61.4 ft., scribe  
visible on unhealed blaze.  
No other trees to SE or suitable trees close NE or W.  
Corner Pipe was under logging debris which we remove to set Brass Cap:  
Set - Brass Cap at Cor. Mkd: County Surveyor's T20S R9W CC 

S	6
S	7

 R10W  
(Dep. old pipe alongside) Office, 1968  
Note - This corner lies about 600' W. of ridge, course N & S and  
on N. side of ravine 15 ft. in logged off unit.

7/10/68

Section Corner Thus: 37  
T 20 S  
R10W 

S	36	S	31
S	1		

 R9W T21S

Found - GLO Brass Cap properly marked in 1951.  
16", now 27" Cedar, N. 66½° E. 17.2 ft., shows good scar. *REN. #1-T20-9*  
16", now 19" Cedar, N. 57° W. 34.3 ft., scribe visible "S".  
New BT: 24" Maple S. 24° E. 29.8 ft. mkd: "T21S R10W=S 1 CS BT".  
Also tagged other bearing trees. 9/30/69

Section Corner Common to Secs. 30 & 31, T20-10W and 38  
Secs. 25 & 36, T20-11W. *Refer to Ren. #112*  
Found - 1½" Pipe from which: Refer to Ren. #10.  
24" Maple Stump bears N. 32° W. 25.0 ft. (Orig.)  
Face chopped out, evidence of old chop marks & face, with tag.  
50" Fir bears S. 18° W. 20.3 ft., scribed S36 CS, with tag.  
Set - 2"x30" Iron Pipe with Brass cap mkd: 

R	T 20 S	R
11	25	30
W	36	31

 10  
from which: 

1970
650

  
4" Chittewood bears N. 72° E. 27.6 ft. 1970  
scribed R10 S31 BT, with tag. 650  
6" Cedar bears N. 20° W. 47.3 ft. scribed  
R11 S25 BT, with tag.  
Set 2 fence posts with signs ± 5 ft. west facing south.  
± 5 ft. north facing east.

Section Corner to Sections 28 - 29 - 32 - 33. 39  
Corner established in 1878, re-established by Gibson in June, 1957,  
by double proportional measurements, See *Ren. #7*.  
Found - an "X" 8" high on east face of 4' sandstone outcrop,  
scribed by Gibson in 1957, from which:  
44" Fir bears N. 45½° W. 35.8 ft., visible scribing, with tag.  
14" Maple bears N. 88° E. 48.6 ft., scribing visible, with tag.  
6" Fir bears S. 21° W. 4.2 ft., face healed, with tag, windthrown.  
Set - 2"x30" Iron Pipe with Brass Cap Mkd: T 20 S R 10 W  
WC 4.4 ft. east of true corner. WC 

29	28
32	33

  
from which: 

1970
650

  
11" Fir bears N. 32° W. 23.2 ft. scribed S29 BT.  
11" Fir bears S. 89½° W. 16.1 ft. scribed S32 BT  
with tag.  
Set 2 fence posts with signs ± 5' W. facing S. & 5' S. facing W.

Section Corner to Sections 20 - 21 - 28 - 29. 40  
Found - ¾" I.P. set by Gibson in 1957, See *Ren. #6*, from which:  
Orig. 48" Fir bears N. 35° E. 46.4 ft., scribing visible, with tag,  
has been chopped out. out.  
20" Alder bears S. 36° W. 35.4 ft scribing vis., with tag, has been chopped  
Set = 2"x30" I.P. with Brass Cap Mkd: T20S R10W 

20	21
29	28

  
from which: 

650
1970

  
12" Maple bears N. 68° W. 26.2 ft. scribed S20 BT, with tag.  
12" Hemlock bears S. 1° E. 54.5 ft. scribed S28 BT, with tag.  
Set - 2 fence posts with signs: ± 5 ft. W. facing S. & 5 ft. S. facing W.