

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 20 S. T. S. R. 10 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Sections 28 and 21. 41  
Set - 3/4" Iron Pipe, from which: SEE REN. No. 9  
18" Maple, now down with visible scribing, N.60°W.  
The S. E. BT is now gone. 38.6 feet.  
Scribed: 12" Maple S. 6 1/2° E. 37.4 feet.  
14" Maple N. 70 1/2° W. 44.5 feet.

Sept. 1, '70

Stuntzner,  
Ronald E.  
For. U.S.  
Plywood  
M 42 - 2  
C.S. 55/163

MARCH 77

1/4 Corner to Sections 7 and 8. 42  
No evidence of original corner found.  
At the properly proportioned position I placed a 2" x 36" galv. I. P.,  
flanged at the bottom and capped with a bronze disk welded on top.  
The monument projects 6" above ground. I filled in around the  
pipe monument with stone and packed earth.  
I stamped the disk

SEE  
M 90-42

~~RENEWED SEE CORNER NO. #95~~

S6/S5  
1971  
4185

I established new bearing trees as follows. Each bearing tree has a  
scribed face and a U.S.F.S. bearing tree sign breast high and facing  
the monument.  
Set: A 10" Spruce bears S. 69° E. 26.60 feet.  
A 10" Maple bears S. 30° W. 59.43 feet.

Rev. 10/12/71

Section corner to Sections 6 - 5 - 7 - 8 43  
No evidence of original corner found.  
At the properly proportioned position I placed a 2" x 36" galvanized  
iron pipe, flanged at the bottom and capped with a bronze disk  
welded on top. The monument projects 6" above ground. I filled  
in around the pipe monument with stone and packed earth.  
I stamped the disk:

SEE NEW NOTES

T20S R10W  
S6/S5  
S7/S8  
1971  
4185

I established new bearing trees as follows. Each bearing tree has a  
scribed face and a U.S.F.S. bearing tree sign high and facing the  
monument.  
Set: an 18" maple bears S 46° W 47.55 feet.  
a 26" maple bears S 26° E 43.06 feet.  
a 4" alder bears N 17° E 27.56 feet.  
a 32" hemlock bears N 19° W 59.10 feet.

James W. Prochman  
For U.S. Forest Service  
May, 1971  
C.S. File 55/201  
Map File M 43 - 56

1/4 Corner to Sections 6 and 5. 44  
No evidence of original corner found. Ren. #3  
At the properly proportioned position I placed a 2" x 36" galv. I.P.  
flanged at the bottom and capped with a bronze disk welded on top.  
The monument projects 6" above ground. I filled in around the  
pipe monument with stone and packed earth.  
I stamped the disk:

~~RENEWED SEE CORNER NO. #117~~

S6/S5  
1971  
4185

I established new bearing trees as follows. Each bearing tree has a  
scribed face and a U.S.F.S. bearing tree sign breast high and facing  
the monument.  
Set: a 28" maple bears N. 15° E. 30 feet.  
a 32" Hemlock bears N. 44° W. 80.86 feet.

Rev. 10/12/71

POSSIBLE SITKA SHOWS - PER DICK HAMILIN  
4/17/77