

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 10 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21891

$\frac{1}{4}$ Corner to Section 1 only. T 20S R11W. 45
No evidence of original corner found.
At the properly proportioned position I placed a 2" x 36" galv. I. P.,
flanged at the bottom and capped with a bronze disk welded on top.
The monument projects 6" above ground. I filled in around the pipe
monument with stone and packed earth.
I stamped the disk: $\frac{1}{4}$ S1
1971
4185

I established new bearing trees as follows. Each bearing tree has a
scribed face and a U.S.F.S. bearing tree sign breast high and facing the
monument.
Set: a 16" fir bears N 82° W 31.00 feet.
an 18" fir bears N 57° W 42.18 feet.

$\frac{1}{4}$ Corner to Section 6 only. 46
Original corner never established.
At the properly proportioned position I placed a 2" x 36" galvanized
iron pipe, flanged at the bottom and capped with a bronze disk
welded on top. The monument projects 6" above ground. I filled
in around the pipe monument with stone and packed earth.
I stamped the disk: $\frac{1}{4}$ S6
1971
4185

I established new bearing trees as follows. Each bearing tree has a
scribed face and a U.S.F.S. bearing tree sign breast high and facing
the monument.
Set: a 28" fir bears N 40° E 24.1 feet.
a 20" fir bears N 24° E 34.6 feet.

Section Corner to Sections 1 and 12 only. T 20S R 11W. 47
Found: Original maple B.T. in NE quadrant (Good face but scribing was
destroyed in 1894). Found fir B.T. now 30" windfall with faint
face on bottom. Corner agrees very well with " canon " call
0.25 chains North.
Note: In 1894 all markings relating to R10W were destroyed making
corner common to Sections 1 and 12 only.
From the original maple B.T. in NE quadrant I placed a 2" x 36" galvanized
iron pipe, flanged at bottom and capped with a bronze disk welded
on top. The monument projects 6" above ground. I filled in around
the pipe monument with stone and packed earth.
Set: a 24" fir bears N 30° W 75.29 feet.
an 18" fir bears S 3° W 23.93 feet.
I stamped the disk: T20S T20S
S1 R10W
S12
R11W S6
1971
4185

Closing Corner to Sections 6 and 7. 48
No evidence of original corner found.
At the properly proportioned position I placed a 2" x 36" galv. I. P.,
flanged at the bottom and capped with a bronze disk welded on top.
The monument projects 6" above ground. I filled in around the pipe
monument with stone and packed earth.
I stamped the disk: S12 T20S
S6 cc
S7 R10W
1971
4185

I established new bearing trees as follows. Each tree has a scribed face
and a U.S.F.S. bearing tree sign breast high and facing the monument.
Set: a 16" fir bears N 60° E 72.25 feet.
an 18" fir bears S 49° E 47.59 feet.

James W. Prochnau
For U. S. Forest Service
May, 1971
C.S. File 55/201
Map File M 43 - 56

FD OK
9/18/84
CO. Surveyor's office
c.s. 62/21

RE-RENEWED, SEE CORNER NO # 84