

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Section 12 only. T20S R11W

49

No evidence or original corner found.

At the properly proportioned position I placed a 2" x 36" galv. I.P., flanged at the bottom and capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth.

I stamped the disk: _____

1/4 S12
1971
4185

I established new bearing trees as follows. Each bearing tree has a scribed face and a U.S.F.S. bearing tree sign breast high and facing the monument.

Set: a 32" fir bears S 66° W 33.90 feet.
a 20" fir bears N 73° W 29.10 feet.

1/4 Corner to Section 7 only.

Original Corner never established.

#93 50

At the properly proportioned position I placed a 2" x 36" galv. I.P., flanged at the bottom and capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth.

I stamped the disk: _____

1/4 S7
1971
4185

I established new bearing trees as follows. Each bearing tree has a scribed face and a U.S.F.S. bearing tree sign breast high and facing the monument.

Set: a 22" fir bears N 29° E 49.4 feet.
a 14" fir bears N 78° E 75.54 feet.

1/4 corner to Sections 6 and 7.

No evidence of original corner found.

#91 51

At the properly proportioned position I placed a 2" x 36" galv. I.P., flanged at the bottom and capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth.

I stamped the disk: _____

1/4 S6
S7
1971
4185

I established new bearing trees as follows. Each tree has a scribed face and a U.S.F.S. bearing tree sign breast high and facing the monument.

Set: a 18" fir stump bears N 72° E 28.23 feet.
a 26" fir stump bears S 52° E. 13.4 feet.

Rev. 10/12/71

1/4 Corner to Sections 5 and 8.

No evidence of original corner found.

52

At the properly proportioned position I placed a 2" x 36" galv. I.P., flanged at the bottom and capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth.

I stamped the disk: _____

1/4 S5
S8
1971
4185

I established new bearing trees as follows. Each bearing tree has a scribed face and a U.S.F.S. bearing tree sign breast high and facing the monument.

Set: a 6" fir bears N 36° W 90.7 feet.
a 12" fir bears S.78° W 92.5 feet.

Rev. 10/12/71

SEE
M 90-42

RE-RENEWED, SEE CORNER NO. #93 #91

#122

James W. Trochman
For U.S. Forest Service
May, 1971
C.S. File 55/201
Map File M 43- 56