

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T. S. R. 10 W. R.W.W.M.

ROSE-CHAPMAN CO., EUGENE, ORE. - 21001

U. S. Forest Service
By James W. Prochnau
Oct. 12, 1971
C. S. File 55/201 Map M 43- 56

Section Corner to Sections 5 - 6 - 7 - 8.
Orig. Surv. record states: Set post for corner from which:
A fir 48" diam bears S.65°W. 76 lks. dist.
A maple 4" diam. bears N.69½°E. 33 lks. dist.
A fir 48" diam bears N.42°W 1.11 lks. (Corr. later to 111 lks.) dist.
A fir 16" diam. bears S.68°E. 1.03 lks. (Corr. later to 102 lks.) dist.
Found the N.W.(Sec.6) BT. with "X" and \equiv chopped in face. Now a bucked root
wad which has slid about 450 ft. downhill. This BT. while still green was
identified by Richard Hanlin during Doug. Co. timber appraisal as recorded
in Doug.Co.Surv. office. Noted X \equiv & faint bark scribe. Found U.S.Ply.tag
set by Walter Camp on 11/22/65 on 48" Fir stump location corner N.76½°E.
39.0 ft. Mr. Camp states that he set corner & his tag from a Forest Service
tag on nearby maple, that he was shown this tag by Mr. Mel Holmes, adjacent
land owner & verified tag with Forest Serv. personnel at Gardiner Ranger
Station as being the tag referencing the corner used to run a 1953 transit
survey to establish property lines in 1953. Mr. Holmes states that before
sliding out the Sec. 6 BT. was in a proper position relating to the corner
as ref. by Mr. Camp. I found evidence of a large fir sliding out from the
proper position of the Sec. 6 BT., in relation to the Walter Camp tag.

Considering the above evidence, I located the corner from the record on
said tag set by W. Camp on 11/22/65. At this position, I placed a 2"x36"
galv. Iron Pipe, flanged at the bottom & capped with a bronze disk welded
on top. The monument projects 6" aboveground. I filled in around the
pipe monument with stone & packed earth. The monument was set a post
set by Camp referenced by his tag.

T 20 S R 10 W
S 6 S 5
S 7 S 8
1971
4185

I stamped the disk-----

I established new BT's., as follows. Each BT. has a scribed face &
a U.S.F.S. BT. sign breast high & facing the monument.
BT's.Set: A 30" fir stump bears S. 74° E. 59.60 feet.
A 60" fir stump bears S. 80° W. 40.78 feet.
A 6" alder bears N. 54° W. 10.80 feet
A 24" Spruce bears N. 54° E. 118.38 feet.

PROCHNAU'S FIRST
CORNER - REV. #43

Jan 1972

Gary Langlitz
P. Earle
County Surveyor's
office
C.S. 56/49
3/19/74

1/4 corner for sections 10 and 11.
Found - 1952 U.S. GLO brass cap properly mkd. mounted on an iron pipe.
BT's - 10" now 20" Hemlock stump bears S.40°E., 31.7 ft. showing
a well healed blaze.
A 40" fir stump, bears S.12°W., 35.0 ft. showing a well
healed blaze.
Set - A steel fencepost with survey marker sign attached alongside the
brass cap.
New Bearing Object - A boat spike driven in the top of a 60" D.Fir stump,
directly above its root collar, marked with a "10" bears
N.76°W., 26.7 ft.
This corner lies on a steep north slope nearly at the bottom of a canyon
in a clearcut unit.

Jan 1975

Gar E. Commons
P. Earle
Surveyors office
Jan. 16, 1975
C.S. 57/17

1/4 Corner for Secs. 30 and 29.
Found - 60" D.Fir snag, is now a stump, extremely rotted on outside.
32" Hemlock N.42°E., 34 ft. (rec. N.43°E., 32.0 ft.) is now a 34"
stump. We opened scribe and found "CS" on portion of tree removed
by fallers. We opened and found "BT" (we attached this to top of
stump). The first record I could find of this BT was in the field
notes of railroad creek survey by Roy C. Gibson for E.K. Wood Lbr.
in 1957. He found BT and stated it was not orig. Knife scribed 25
years old.
Set - A railroad spike with "X" marked on head in center of 60" D. Fir.
New BT's - A 6" Hemlock, bears N.56°E., 40.6 ft. scribed "1/4 S30 CS BT."
A 12" Hemlock, bears N.57°W., 81.6 ft. scribed "1/4 S30 CS BT."
1/16/75

C.S. 42/275

RENEWED CORNER NO. 49

53

54

55