

Douglas County Surveyor's Record of  
Government Corners Renewed

T 20 T. S. R 10 R.W.W.M.

MOORE-CHAPMAN CO., EUGENE, ORE. 97101

84

Donald Peel For:  
Davidson Industries  
May 6, 1983  
M 94 - 64  
C.S. 58/274

Closing corner for Sections 6 and 7 only. (west side)  
Found - 10"x7"x7" stone mkd CC with 1 notch, in circle of stones  
approx. 4 ft. in diam.  
Set - U.S.F.S. alum. monument in mound of stone.  
34" fir, N.79 1/2°E., 92.5 ft.  
20" Alder, S.45 1/2°E., 12.0 ft. (bark scribed)  
17" fir, N.60°E., 95.8 ft. (Prochnau BT)  
20" fir snag, S.72°E., 56.6 ft. (Prochnau BT)  
Note: Closing corner set by J. Prochnau in 1971 bears N.51°33'26"E., 23

★ SEE  
C.S. 62/19  
4/2/84

FD. OK 9/15/84  
D.S. 10/1/84  
C.S. 10/1/84

See Ren. #

85

Section corner for Secs. 31 and 32; and 5 & 6 of T.21-10.  
Found - 1 1/2" iron pipe with 2 1/2" brass cap set in conc properly  
marked. Ren. #65  
21" red cedar bears N.6°W., 28.8 ft. with scribe marks "BT S"  
visible on partially healed face.  
27" D. fir bears S.43°E., 85.0 ft. with healed face.  
New BTs - 13" D. fir bears N.55°E., 80.7 ft. blazed and scribed "T20S  
R10W S32 BT".  
19" big leaf maple bears S.81°W., 73.3 ft. bark scribed "T21S  
R10W S6 BT".

Herman Pieske, LS 1651  
AA Surveying Services  
For: US Dept. of Agric.  
Siustlaw National Forest  
November 1983  
M 95 - 59 A & B

CHANGES MADE PER A.F. PRODUCE EXHIBIT  
1/10/84 Co. (See file C.S. 10/1/84)

86

1/4 Corner for Section 32; and Sec. 5 of T.21-10.  
Set - 2 1/2" x 30" alum. pipe, 24" in the ground, with 3 1/4" cap mkd.  
"US Dep of Agri-Forest Service T20S 1/4 S32 S5 T21S RLS 165:  
1983 Unlawful to disturb".  
BTs - 20" hemlock bears N.31°E., 57.2 ft. scribed "1/4 S32 BT".  
24" hemlock bears S.8°W., 59.4 ft. scribed "1/4 S5 BT".

87

Section corner for Secs. 33 and 34; and Secs. 3 & 4 of T.21-10.  
Found - 2" iron pipe loosely set 18" above ground with 3" brass ca.  
firmed up. (1951 GLO cap.)  
36" D. fir bears N.67°E., (75° rec.) 148.49 ft. healed.  
35" hemlock bears N.84°W., 64.3 ft. scribes visible "R10W  
S33 BT US".  
36" D. fir bears S.59°W., 62.7 ft. healed blaze.  
New BT - 36" big leaf maple bears S.10°E., 27.8 ft. blazed and scribed  
"T21S R10W S3 BT".

FD. OK 2/92 BY R. STUNTZNER M114-80

88

Herman Pieske LS 1651  
AA Surveying Company  
For: U.S. Forest Serv.  
November 1984  
M 97 - 76 A & B

1/4 Corner for Section 31; and Section 6 of T.21-10  
Set - 2 1/2" x 30" alum. pipe with 3 1/4" alum. cap mkd. "US Dep of Agri-  
Forest Service T20S R10W S31 1/4 S6 T21S RLS 1651 1983 Unlawful  
to Disturb". Set pipe and cap 12" below ground in pasture.  
New BTS-10" alder bears N.85°47'E., 170.7 ft. bark scribed "1/4 S31 BT".  
12" alder bears S.29°10' W., 264.2 ft. bark scribed "1/4 S6 BT".

89

Ronald Stuntzner  
For: International  
Paper Company  
Oct. 19, 1984  
M 97 - 80

1/4 Corner for Sections 35 and 36.  
Found - 1951 GLO proportioned corner, 1" I.P. with 2 1/2" brass cap.  
24" hemlock now 30", S.33°E., 41 lks. (tagged with visible  
scar.  
New BT - 8" hemlock bears N.38°E., 12.8 ft. (faced with no scribe a  
tagged.  
Note - 1951 SW BT lost in logging road construction.

10/84

90

Richard Hintz  
For: International  
Paper Co.  
M 90 - 42  
April, 1983

1/4 Corner for Sections 19 and 30  
Found - 3/4" I.P.  
60" fir windfall is lying approx 35 ft. south of hole and/or  
depression in ground. Hole bears N.52°W. 19 ft. from I.P.  
See USFS index file No. R-3 at Mapleton.  
Set - Replace the 3/4" I.P. with 1 1/4" I.P./B.C.  
From Which:  
10" Fir bears S.48°30'E., 30.3 ft. Scribed.  
20" cedar bears N.60°00'W., 46.0 ft. Scribed.

RENEWED, SEE CORNER #108

4/83