

**Douglas County Surveyor's Record of
Government Corners Renewed**

20 T. S. 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

Michael J. Schwartz & L.W. Hunnemuller
 RPLS 1922 RPLS 1050
 Sulphur Cadastral Survey - Siuslaw Natl. Forest
 U.S. Forest Service
 October, 1985
 M 99 - 79 A & B

91

1/4 Section Cor. for Secs. 6 and 7. See Renewal #51

Found - Brass cap set by Prochnau in 1971

BT's - 18" Fir stump, bears N.72°E., 28.23 ft.
 26" fir stump, bears S.52°E., 13.4 ft.

SET - A 3 1/2" x 30" Aluminum flared pipe with alum. cap stamped:
 T20S R10W 1/4 S6 S7 1984 RPLS 1922. (Cap lies S69°51'20"E.,
 7.99 ft. from Prochnau's corner.)

New BT's- A 5" D. Fir, bears S.28°E., 14.8 ft. dist., scribed X BT.

NEW BO - Set a 3 1/2" x 30" aluminum flared pipe with alum. cap stamped:
 1/4 S6 RM S12-39W., 44.7 ft. 1984 RPLS 1922.

92

Section Corner for Secs. 5, 6, 7, and 8 See Renewal #53

Found - 1971 Brass cap, marked T20S R10W Sec. 5,6,7,8 1971 4185.

BT's - 8" Alder, bears N.54°W., 10.3 ft. dist., with a face high bark
 scribe. (Record, 10.8 ft. 1971)

 30" Fir stump, bears S.74°E., 60.0 ft. dist. Bark scribed
 "RENW S8" (Record, 59.60 ft. 1971)

 60" Fir stump, bears S.80°W., 42.27 ft. dist., bark scribed
 "BT E7" (Record, 40.78 ft. 1971)

 Spruce BT (1971) is windthrown.

NEW BT's- 7" Alder, bears S.48°E., 47.1 ft., marked: T20S R10W S8 BT

 11" Alder, bears N.70°E., 22.2 ft. dist., marked T20S R10W
 S5 BT.

NEW BO - Set a 3 1/2" x 30" aluminum flared pipe, with aluminum cap,
 stamped T20S R10W S6 RM S80-10E 72.4 ft. 1984 RPLS 1922.

93

WEST

1/4 Section Corner for Sec. 7 only See Renewal #50

Set - 3 1/2" x 30" aluminum flared pipe, with aluminum cap stamped
 T20S R11W R10W 1/4 S7 1985 RLS 1922.

Found - 2" iron pipe from Prochnau survey bears N12°09'12"W 2.14 ft. from
 corner set this survey. (Removed cap)

Old BT's- 24" C. Fir, bears N.31°E., 50.2 ft. dist. With a healed face.
 16" D. Fir, bears N.80°E., 75.2 ft. dist. With a healed face.

94

Center 1/4 Sec. Cor. for Sec. 7

Set - A 3 1/2" x 30" aluminum flared pipe, with aluminum cap stamped
 T20S R10W C1/4 S7 1985 RLS 1922

BT's - 5" D. Fir, bears S.71°W., 10.8 ft. Marked C1/4 S7 BT.

BO - Set a 3 1/2" x 30" aluminum flared pipe, with aluminum cap,
 for Reference Monument, stamped: RM S7 C1/4 N89-36W 41.2' 1985
 RLS 1922.

95

1/4 Sec. Cor. for Secs. 7 and 8 Renewal #42

Found - A 1971 Brass cap, marked: 1/4 S7 S8 1971 4185.

BT's - 18" D. Fir, bears(S69°E 26.6 ft. 1971) Tree so badly "J"d,
 couldn't tell where to measure to.
 11" maple, S.30°W 58.4 ft. dist., scribing visible. (Record,
 59.43 ft. 1971)

NEW BT - 10" D. Fir, bears S.43°E., 44.6 ft. dist., scribed 1/4 S8 BT.

96

1/4 Sec. Cor for Secs. 7 and 18

SET - A 3 1/2" x 30" flared aluminum pipe, with aluminum cap,
 stamped: T20S R10W 1/4 S7 S18 1984 RPLS 1922.

NEW BT's- 29" Red Cedar, bears S.67°W., 32.7 ft. dist., scribed: 1/4 S18
 BT.
 51" Red Cedar, bears N.7°W., 58.3 ft. dist., scribed: 1/4 S7 BT.

97

1/4 Sec. Cor. for Secs. 17 and 18

SET - A 3 1/2" x 30" aluminum flared pipe, with aluminum cap,
 stamped: 1/4 S18 S17 1984 RPLS 1922.

BT - 4" Alder, bears S.74°W., 57.3 ft. dist., scribed 1/4 S18 BT.

BO - Set a 3 1/2" x 30" aluminum flared pipe, with alum. cap
 for reference monument. Stamped: RM 1/4 S17 S13-56W 54.7 ft.
 1984 PLS 1922.