

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Michael J. Schwartz, & L.W. Hunnemuller
RPLS #1922 RPLS #1050
Sulphur Cadastral Survey - Siuslaw Natl. Forest
U.S. Forest Service
October 1985
M 99 - 79 A & B

98

Sec. Corner to Secs. 7, 8, 17, and 18 Ren. #19
Found - Douglas County Brass cap, marked County Surveyor's Office
T20S S7 S8 S17 S18 R10W 1968.
BT's - 18" Maple, bears S.22°E., 56.0 ft. dist., with healed face.
(Record, 24" Maple 57.7 ft. 1968)
Decayed Fir, bears S.40°W., 50.2 ft. dist., with a face ch
slab, scribed W BT (1874)
20" D. Fir stump, bears S.40°W., 55.3 ft. dist., with ba
scribing visible: "T20S R10W S17"
25" D. Fir snag (12 ft.) bears S.76°W., 44.7 ft. dist., with
bark scribing visible: "R10W"
29" Maple, bears N.81°E., 7.0 ft. dist., With a severe lean
and scars visible. (1968)
New BO's- Marked a concrete nail in large sandstone boulder, N63°W.,
10.7 ft.
Set a 3 1/2" x 30" alum. flared pipe with alum. cap for Ref-
erence monument. Stamped: T20S R10W RM S18 N1-14E 49.3
1985 RLS 1922.

99

EAST
1/4 Sec. Cor. to Sec. 13 only, (T20S R11W)
SET - An Aluminum Surv-Kap on a 5/8 in. Iron Rod in rock. Stamped:
T20S R11W R10W 1/4 S13 1985 RLS 1922
BT's - A 32" D. Fir, bears N.39°E., 16.1 ft. dist., scribed: 1/4 S18
BT.
12" Maple, bears S.61°E., 68.3 ft. dist., scribed X BT.

100

WEST 1/4 Corner to Section 18 only
SET - A 3 1/2" x 30" aluminum flared pipe, with an alum. cap stamped:
T20S R11W R10W 1/4 S18 1985 RLS 1922
BT's - 8" Alder, bears S.74°E., 29.7 ft. dist., bark scribed "1 S18"
"BT"
10" D. Fir, bears S.69°W., 26.9 ft. dist., scribed, X BT.
BO - Set a 3 1/2" x 30" Alum. flared pipe, with alum. cap for
Reference Monument, stamped: RM 1/4 S18 N1-17E 40.7 ft.
1985 RLS 1922

101

Center 1/4 Sec. Cor. to Section 18
SET - A 3 1/2" x 30" alum. flared pipe, with an alum. cap stamped:
T20S R10W C1/4 S18 1985 RLS 1922
BT - 19" D. Fir, bears S.38 1/2°W., 51.0 ft. dist., scribed:
C 1/4 S18 BT
BO - Set a 3 1/2" x 30" aluminum flared pipe, with an alum. cap
for a Reference Monument, stamped: RM C1/4 S18 N72-54W
63.3 ft. 1985 RLS 1922.

102

1/4 Section Corner for Secs. 18 and 19 Ren. #26
Found - Douglas County Brass cap, marked: T20S 1/4 S18 S19 R10W
1968
BT's - 28" maple, bears N.45°E., 27.3 ft. dist., with open face.
(Record, N.45°E., 26.4 ft. 1892)
30" Maple stub, bears S.10°E., 11.9 ft. dist., with heal
scar.
NEW BT - 22" Double Alder, bears N.83°W., 38.4 ft. dist., scribed
1/4 S18 BT.
No suitable bearing trees to south.

103

EAST
1/4 Section Corner for Section 24 only. (T20S R11W)
SET - 3 1/2" x 30" aluminum flared pipe with alum. cap stamped:
R11W T20S R10W 1/4 S24 1984 RPLS 1922
BT's - 6" D. Fir, bears N.46°W., 16.6 ft. dist., scribed:
1/4 S24 BT
9" D. Fir, bears S.43°E., 16.6 ft. dist., scribed:
1/4 S24 BT.