

Douglas County Surveyor's Record of  
Government Corners Renewed

20 T. S. 11 R. W. W. M.

Jan. 23, 1929  
Frank Cain  
Harry Henderson  
Will Bailey  
Witness  
H. I. Eppstein  
Ren. Cor. Vol. 1  
Pg. 7

COR. 30-31-36-25 T.20S. R.11W. (T20S, R6S, 10 + 11W.)  
Set corner from old Witness trees. Set stake and made mound  
of rocks. Make Bearing Tree as follows:  
Maple 10" bears N. 45° W. 65 links  
Maple 24" bears N. 45° W. 55 links  
Maple 18" bears N. 45° W. 55 links  
No trees near in S. E. (See Cor. Vol. of T20S R6S for later renewal) 1

Jan. 24, 1929  
Frank Cain  
Harry Henderson  
Witness  
H. L. Eppstein  
Ren. Cor. Vol. 1  
Pg. 7

COR. BETWEEN 2-35 T.20-21S. R.11W.  
Set a Chittam post 4" x 4" x 3 1/2' by original B. T. to Witness  
Cedar 12" S. 18° W. 18 links decayed but marks plain other  
B. T. destroyed.  
Marked New Bearing trees.  
Fir 10" Bears S. 82° W. 17 links  
Fir 16" Bears N. 46° W. 18 links

Jan. 24, 1929  
Frank Cain  
Harry Henderson  
Witness  
H. L. Eppstein  
Ren. Cor. Vol. 1  
Pg. 7

MEANDER COR. ON LEFT BANK SMITH RIVER between Secs. 3 & 34  
T.20-21S. R.11 W. A plow sheer marks corner, Mark an Alder  
10" Bears S. 15° E. 85 links. 3

May 26, 1923  
J. W. Cole  
Wallace Smiley  
Maillard Smiley  
Witness  
H. L. Eppstein  
Ren. Cor. Vol. 1  
Pg. 8

CORNER BET. SECS. 8 & 17 (Duplicate of #7)  
I renewed this corner from the original Bearing trees both  
of which are alive and standing and check closely. I chopped  
open the fir B.T. and the scribe marks were plainly visible.  
I set a 2" x 60" iron pipe for corner. 4

May 26, 1923  
J. W. Cole  
Wallace Smiley  
Maillard Smiley  
Witness  
H. L. Eppstein  
Ren. Cor. Vol. 1  
Pg. 8

CORNER TO SECS. 8-9-16-17  
I renewed this corner from the original Bearing trees and set a  
steel buggy axle 1" x 60" from which original Cedar B. T.  
bearing scribe marks bears S. 41° W. 50 links  
An alder bearing tree rotted out bears S. 20° E. 205 links.  
A Maple 20" dia showing scars bears N. 89° W. 13.12 links.  
Stump of large Fir No marks visible bears N. 9° E 4.80 chains. 5

May 26, 1923  
J. W. Cole  
Wallace Smiley  
Maillard Smiley  
Witness  
H. L. Eppstein  
Ren. Cor. Vol. 1  
Pg. 8

CORNER TO 9-10-15-16  
Set Iron pipe 2" x 36" from which the original trees bears  
as follows.  
An Alder 24" N. 76° E. 21 lks.  
An Alder 16" S. 27 1/2° E. 10 lks.  
A Hemlock 8" S. 62° W. 15 lks.  
An Alder 15" N. 20° W. 15 lks. 6

May 26, 1923  
J. W. Cole  
Wallace Smiley  
Maillard Smiley  
Witness  
H. L. Eppstein  
Ren. Cor. Vol. 1  
Pg. 8

1/4 CORNER BET. SECS. 8 & 17 (Duplicate of #4)  
I renewed this corner from the original Bearing trees both of  
which are alive and standing and check closely. I chopped open  
the fir B.T. and the scribe marks were plainly visible.  
I set a 2" x 60" Iron Pipe for corner. 7

Reported by W. J. Brayton as having been set by 2157. c.s. 41/194

1/4 cor. Between 26 & 35  
I set this from the physical features Mentioned in the notes  
a full description is in drawer 41 envelope 119  
set 1 1/2" IP 4" driven in ground with 1" above  
8" Maple, S 38° W, 96' M'k'd. 1/2 35 B.T.  
11" " N 69° E, 76' " " 26 " "  
The pipe is now 15' West of the foot of the Hill & 8' east of the  
new channel of the east fork of Eslick Creek FEB. 1953 8

Reported by W. J. Brayton as having been set by 2157. c.s. 41/194

Closing corner to secs 7 and 18. (West Body)  
4 inch post set by # 2157.  
1 1/2" iron pipe.  
BTs:  
17" Spruce S. 60° W., 10.2.  
48" Fir N. 54° E., 108.0.  
6" Spruce, S. 80E., 38.0. MAY, 1954 9