

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 20 S. T. S. R. 11 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

129

1/4 Corner common to Secs. 22 & 23.
 Found - No trace of original corner.
 Set - 3-1/2 " USFS Aluminum cap on a 2-1/2 " x 30" aluminum pipe
 at point of proportionate measure.
 26" Hemlock bears N.62°23'W., 29.0-ft.(1981) scribed 1/4S22 BT.
 20" Hemlock bears N.51°55'E., 33.1-ft.(1981) scribed 1/4S23 BT.
 - - - - - 9/81

FD OK 11-91
L. ROBERTS
M 14-29

130

Center 1/4 of Sec. 23.
 Set - 3-1/2 " USFS Aluminum cap on a 2-1/2 " x 30" Aluminum pipe.
 New BTs - 40" Fir bears S.29°0'E., 109.1-ft.(1981)
 61" Fir bears S.81°15'E., 79.8-ft.(1981), both trees scribed
 C1/4 S23 BT.
 - - - - - 9/81

131

1/4 Corner common to Secs. 23 & 26.
 Found - No trace of original corner.
 Set - 3-1/2 " USFS Aluminum cap on a 2-1/2 " x 30" aluminum pipe
 at point of proportionate measure.
 New BTs - 10" Alder bears N.6°52'W., 33.6-ft.(1981) bark scribed "1/4S23BT"
 14" Alder bears N.52°03'E., 52.4-ft.(1981) bark scribed 1/4S26BT
 S. Typo Error 12/90 JH
 - - - - - 9/81

Sec. Corner common to Secs. 22, 23, 26, & 27.
 (Information only). For affidavit, see C.S. 58/260. 132

Found - 3-1/2" iron cap on a 2-1/2" I.P.
 BTs - 27" Alder bears S.34°0'W., 39.9-ft.
 25" Hemlock bears N.31°0'E., 36.5-ft.
 48" twin Alder bears N.1°0'W., 44.3-ft.
 24" Alder stump bears S.48°0'E., 35.8-ft.
 Note - BT dates unknown. - - - - - 9/81

Sec. Corner common to Secs. 23, 24, 25, & 26. 133

Found - No trace of original corner.
 Set - 3" B.C. cemented in sandstone outcrop at point of proportionate
 measure.
 BTs - 31" Fir bears S.39°30'E., 71.9-ft.(1981) scribed T20S R11W
 S25 BT.
 53" Fir bears N.52°0'W., 28.9-ft.(1981) scribed T20S R11W S23 BT
 8" Fir bears N.64°0'E., 22.5-ft.(1981) scribed T20S R11W S24 BT
 BO - 2-ft. wide sandstone ledge marked X BO bears S.70°15'W., 27.5-ft.
 (1981). - - - - - 9/81

FD OK 12/90
M 11-47 A-F

134

Sec. corner common to Secs. 4, 5, 8, & 9.
 Found - Douglas County B.C., properly marked. Ren. # 86.
 BTs. - 24" fir bears N.4°E., 74.5-ft. with healed face. Ren#10.
 24" alder bears S.63°W., 31.5-ft., with scribe visible. Ren#10.
 20" cedar stump bears S.32°E., 42.5-ft., with healed face. #10.
 New BTs.- 32" fir mrd. "T20S R11W SE S5 BT", bears N.13°W., 86.8-ft.
 20" fir mrd. "T20S R11W SW S4 BT", bears N.46 1/2°E., 52.0-ft.
 - - - - - 1/82

135

Sec. corner common to Secs. 5, 6, 7, & 8.
 Found - Douglas County B.C., properly mrd. Ren.#87.
 BTs. - 16" fir high stump bears N.72°E., 13.7-ft. Orig.
 38" fir bears S.43°W., 8.6-ft. (stump). Orig.
 30" fir bears S.21°E., 6.8-ft. (stump). Orig.
 26" spruce bears N.44°E., 28.8-ft., with healed face. Ren.#87.
 22" alder bears N.14°W., 36.0-ft., with rotten face. Ren.#87.
 New BTs.- 6" alder, mrd. "T20S R11W NE S7 BT" bears S.86°W., 22.6-ft.
 8" alder, mrd. "T20S R11W NW S8 BT" bears S.61°E., 13.3-ft.
 - - - - - 1/82

136

1/4 corner between Secs. 7, & 8.
 Found - Brass Cap, properly marked. Ren. #80
 BTs. - 32" fir bears S.43 1/2 °E., 6.9-ft.(down) Orig.
 6" spruce stub bears N.31°W., 20.8-ft. Ren.# 62.
 20" spruce stub bears N.70°W., 23.9-ft. Ren.# 62.
 New BTs.- 13 1/2 " alder, mrd. "E 1/4 S7 BT", bears N.40°W., 26.3-ft.
 14 1/2 " alder, mrd. "W 1/4 S8 BT", bears N.46°E., 30.1-ft.
 - - - - - 1/82

Robert B. Ward
 Oregon P.L.S. #1091
 For: Champion International
 Sept. 1981
 M 89 - 58 & C.S. 58 / 260

Gerald K. Attig OR L.S.#1121
 For: U.S. Forest Service
 Nov. '81 thru Jan. '82
 M 91 - 20