

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 20 T. S. R 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Ronald Stutzner
For: Siuslaw National
Forest
Oct. 1981
M 91 - 53

143

Section corner for Sections 29, 28, 32 and 33. Ren. #34
 Found - Original corner, with 1964 County brass cap properly marked.
 Rotted stump (rec. spruce) bears N.60°E., 39.6 ft. No scribes visible.
 48" fir stump bears S.46°E., 6.0 ft. barely visible arc scribing.
 Rotted hemlock remains as per 1964 remon. bears S.13°W., 37.0 ft. (Rec. 38.9 ft.)
 8" D. fir now down, bears N17°E., 12.4 ft., visible scribes.
 11" D. fir now 12", bears S.69°E., 33.0 ft. healed face.
 13" D. fir now 20" bears S.9°W., 18.5 ft. healed face.
 10" D. fir bears N.14°W., 11.0 ft. healed face.
 New BT - 16" D. fir bears N.32°E., 35.8 ft. scribed T20S R11W S28 BT.

Ronald Stutzner
For: Siuslaw Nat'l
Forest
Feb. 8, 1982
M 91 - 52

144

1/4 Corner for Sections 33 and 34.
 Set - Alum. pipe with alum. cap marked T20S R11W 1/4 S33/S34 1981 PLS 1342.
 No evidence of orig. corner found.
 New BT's- 15" D. fir bears S.57°E., 29.9 ft. scribed W 1/4 S34 BT.
 10" W.R. Cedar bears S.1°W., 25.3 ft. scribed E 1/4 S33 BT.

145

1/4 Corner for Sections 32 and 33
 Set - Alum. pipe with alum. cap marked T20S R11W 1/4 S32/S33 1981 PLS 1342.
 No evidence of original corner found.
 New BT's- 9" D. fir bears N.60°E., 54.8 ft. scribed 1/4 S33 BT.
 12" Alder bears N.10°W., 40.3 ft. bark scribed 1/4 S32 BT.

146

1/4 Corner for Secs. 27 and 34.
 Set - Alum. cap rock monument at proportioned mid-point marked T20S R11W 1/4 S27/S34 1981 PLS 1342.
 No evidence of orig. corner found.
 New BT's- 34" W.R. Cedar bears S.64°E., 80.8 ft. scribed N 1/4 S34 BT.
 Also 54" D. fir with 32' schooledmarmed stem bears S.68°E., 78.8 ft. not tag.
 26" maple bears N.7°W., 99.3 ft. scribed S 1/4 S27 BT.

147

Section corner for Secs. 27, 26, 34 and 35
 Set - Alum. pipe with alum. cap at double proportioned section corner marked T20S R11W S27 S26 S34 S35 1981 PLS 1342.
 Orig. calls checked however no orig. evidence found.
 New BT's- 24" D. fir bears N.54°E., 44.0 ft. scribed T20S R11W S26 BT.
 20" alder (poor condition) bears S.1°E., 34.5 ft. bark scribed T20S R11W S35 BT.
 34" D. fir bears S.70°W., 59.8 ft. scribed T20S R11W S34 BT.
 40" D. fir bears N.44°W., 29.0 ft. scribed T20S R11W S27 BT.
 50" D. Fir remains (very old snag) bears S.16°E., 8.8 ft. not tagged.

148

1/4 Corner for Sections 34 and 35
 Set - Alum. pipe with alum. cap at proportioned position marked: T20S R11W 1/4 S34/S35 1981 PLS 1342. *FND. OK 12/90 M 111-47 A-F*
 No evidence of original corner found.
 New BT's- 22" D. fir bears N.5°E., 33.3 ft. scribed W 1/4 S35 BT.
 22" D. Fir bears S.1°E., 21.4 ft. scribed W 1/4 S35 BT.
 23" D. fir bears N.35°W., 19.8 ft. scribed E 1/4 S34 BT.

149

Witness corner for meander corner Secs. 34 and 35.
 Set - Alum. pipe with alum. cap marked "T20S R11 W.C. S34 S35 M.C. 1982 PLS 1342.
 Proportioned orig. M.C. location falls in Smith River, S.0°17'15"E., 149.36ft
 New BT's- 32" D. fir bears N.48°E., 25.2 ft. scribed W.C. S35 BT.
 12" D. fir bears N.30°W., 39.3 ft. scribed W.C. S34 BT.

Ronald E. Stutzner PLS 1342
 For: Siuslaw National Forest
 Feb. 15, 1982
 M 91 - 54 A & B

*FND OK
12/90
M 111-47 A-F*