

Douglas County Surveyor's Record of
Government Corners Renewed

T 20 T. S. R 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

Donald Peel
L.S. #752
For: Davidson
Industries
Dec. 11, 1981
M 89 - 66

Donald Peel
For: Davidson Industries, Inc.
May 6, 1983
M 94 - 64 C.S. 58/274
AMENDED - SEE
M 97-64

C.S. 62/19
4/2/84

1/4 Corner for Sections 3 and 4

Set - 1 1/2" x 40" iron pipe with brass cap.
BTs - 20" fir, bears S.57°E., 64.8 ft.
30" fir, bears S. 6°W., 30.4 ft.
RE-RENEWED, SEE CORNER NO. #188
12/81

156

Center 1/4 Section 3

Set - 1 1/2" x 40" iron pipe with brass cap.
24" fir, bears N.23°E., 40.2 ft.
17" fir, bears S.88°W., 23.7 ft.
RE-RENEWED, SEE CORNER NO. #189
12/81

157

1/4 corner for Sections 3 and 2 (W.C.)

Position for 1/4 Corner is occupied by a 40" fir, so I set a witness
corner S.0°32'50"W., 4.0 ft. from exact corner point.
Set - 1 1/2" x 40" iron pipe with brass cap marked "W.C."
BTs - 25" fir, bears S.54°E., 41.0 ft. (Scribed "X")
40" fir, bears S. 47°W., 15.1 ft. (scribed "X")
Bearing and distances are from Witness Corner.
FD OK BY Daniel Baker 5/93 M 118-6

158

Section corner for Secs. 3 and 4; and Secs. 33 & 34 of T.19-11.
(Corner lies in Lane County)

Set - 2" x 48" iron pipe with brass cap.
BTs - 11" fir, N.42°E., 253.0 ft.
19" Alder, N.50°W., 72.5 ft. (bark scribed)
RE-RENEWED, SEE CORNER NO. #186
12/81

159

1/4 Corner for Secs 3 and Sec. 34 of T.19-11.
(Corner lies in Lane County)

Set - 2" x 48" iron pipe with brass cap
BTs - 16" alder, N.7°W., 123.9 ft. (bark scribed)
36" Hemlock, S.13°W., 301.2 ft.
RE-RENEWED, SEE CORNER NO. #187
12/81

160

Closing corner for sections 6 and 7 only of T.20-10.

Found - 10"x7"x7" stone mkd. C C with 1 notch in circle of stones
approx. 4 ft. in diam.
Set - U.S.F.S. alum. monument in mound of stone.
34" fir, N.79 1/2°E., 92.5 ft.
20" alder, S.45 1/2°E., 12.0 ft. (bark scribed)
17" fir, N.60°E., 95.8 ft. (Prochnau BT) See Ren. #101
20" fir snag, S.72°E., 56.6 ft. (Prochnau BT)
Note: Closing corner set by J. Prochnau in 1971 bears N.51°33'26"E.,
23.58 ft. Ren. #101

161

1/4 Corner for Section 1 only.

Set - U.S.F.S. Alum. monument buried 4" below surface of Rd. No.4811.
23" fir, N.42°W., 52.7 ft. (Prochnau BT) See Renewals #98 & 115
18" fir, N.88°W., 32.2 ft. (Prochnau BT)
Note: 1/4 corner set by J. Prochnau in 1971 bears N.13°36'00"W., 11.77ft

162

Center 1/4 corner for section 1

Set - 1 1/2" x 36" iron pipe with brass cap.
39" fir, S.20°E., 45.7 ft.
31" fir, S.86°W., 36.8 ft.
RE-RENEWED, SEE CORNER NO. #176

163

1/4 Corner for Secs. 1 and 2

Set - 1 1/2" x 36" iron pipe with brass cap.
31" fir, S.59°E., 32.2 ft.
39" fir, N.15°W., 18.1 ft.
RE-RENEWED, SEE CORNER NO. #177

164

Center 1/4 corner for section 2

Set - 1 1/2" x 36" iron pipe with brass cap.
26" fir, S.27°E., 9.4 ft.
21" fir, S.60°W., 23.3 ft.
RE-RENEWED, SEE CORNER NO. #178

165

Note: These corners formerly set in wrong positions. See 79 97-39 9/80 D.S.