

Douglas County Surveyor's Record of
Government Corners Renewed

T 20

T. S.

R 11

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31081

166

North 1/4 Corner for Section 6
Found - 1" iron pipe set in Lane Co. survey 17,453.
25" fir snag, N.41°W., 10.7 ft. (scribe vis.) 1889 BT.
New BTs - 6" spruce, S.78°E., 6.7 ft. with scribed washer.
8" fir, N.7°E., 12.4 ft. with scribed washer.

167

Northeast corner for section 6.
CORNER REPORT ONLY.
Found - Old fence post in 30" of water. Line of posts running N-S-W.
This post has long been recognized by adjacent landowners as
the section corner. See Re-stab. card #5335 and Lane Co.
Survey 12,651.

168

Witness corner for the Northeast corner of Section 6.
Set - 1 1/2" x 36" iron pipe and brass cap. Orange magnetic marker
buried under pipe.
Section corner bears N.89°27'07"E., 780.0 ft.
BTs - 16" hemlock, N.14°W., 29.6 ft.
28" hemlock, S.42°W., 28.0 ft.

169

Witness corner for the Northwest corner of section 5.
Set - 1 1/2" x 36" iron pipe and brass cap. Orange magnetic marker
buried under pipe.
Section corner bears S.89°40'07"W., 220.0 ft.
BTs - 16" fir, S.89°E., 28.4 ft.
18" fir, N.30°W., 40.6 ft.

170

North 1/4 corner for section 5.
CORNER REPORT ONLY.
Found - 1" iron pipe axle and flange bear east 0.35 ft. See re-estab
card 3902. Ren. #31
39" fir stump, N.51°E., 49.4 ft. (no marks), 1889 BT.
7" alder, S.16°W., 14.0 ft. (scribe vis.) 1968 BT.
21" spruce, N.80°W., 29.0 ft. (scar vis.) 1968 BT.

171

Witness corner to center 1/4 corner of Sec. 6
Set - 1 1/2" x 36" iron pipe and brass cap. Orange magnetic marker
buried under pipe.
Center 1/4 corner bears N.89°26'41"W., 125.0 ft.
BTs - 22" alder, bears S.87°W., 11.2 ft. bark scribed.
44" spruce, S.77°E., 40.2 ft.

172

Section corner for Secs. 2, 3, 10 and 11.
Found - 1 1/4" iron pipe with Douglas Co. Brass Cap "1970". Ren. #88
27" fir, N.67 1/4°E., 20.3 ft. (1916 BT)
33" Fir, N.89 1/2°E., 30.0 ft. (1970 BT) (No record)
21" Fir, S.37°E., 24.7 ft. (1916 BT)
37" fir, S.88 1/2°W., 56.9 ft. (1970BT)
27" fir, N.18 3/4°W., 11.0 ft. (1916 BT)
Set - U.S.F.S. Alum. mon. S.86°16'55"W., 44.87 ft. (Ref. Mon.)
Stamped "T20S R11W RM S10 N88-16-55E 44.87 PLS 752 198

173

1/4 Corner for Secs. 2 and 11
Set - Cemented 2 1/2" brass cap in solid rock face. marked T20S R11W
1/4 S2 S11 PLS 752 1984".
New BTs - 22" Alder, N.76 1/2°E., 37.3 ft. (bark scribed) - 1/4 S2 BT.
20" fir, S.48 3/4°W., 78.4 ft. - 1/4 S11 BT.

8/84

Les Roberts LS 1039
Roberts Surveying Inc. Eugene
For: International Paper Co.
October, 1983
M 90 - 50

Donald Peel LS #752
For: U.S. Forest
Service
Aug. 1984
M 97 - 39
C.S. 58/274

FD OK
BY DONALD PEEL
5/93 M118-6