

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 20 T. S. R 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

174

Section Corner for Secs. 1, 2, 11 and 12.
Set - U.S.F.S. Alum. monument marked "T20S R11W S2 S1 S11 S12 PLS 752 1984".
New BTs- 18" alder, N.3°E., 12.4 ft. (bark scribed) - T20S R11W S1 BT.
15" Alder, S.20 1/4°E., 4.3 ft. (bark scribed) T20S R11W S12 BT.
45" Fir, S.56 3/4°W., 45.5 ft. T20S R11W
22" fir, N.52°W., 56.8 ft. T20S R11W S2 BT.
Corner falls 50 ft. west of small intermittent stream flowing S.20°W., approx. 300 ft. north of westerly flowing creek (a fork of 5mile creek).

Donald Peel LS #752
For: U.S. Forest Service
August, 1984
M 97 - 39
C.S. 58/274

175

1/4 Corner for Sections 1 and 12.
Set - U.S.F.S. Alum. monument mkd. T20S R11W 1/4 S1 S12 PLS 752 1984.
BTs - 42" fir, N.23 1/2°E., 36.5 ft. - 1/4 S1 BT.
40" fir, S.74 1/2°W., 19.9 ft. - 1/4 S12 BT.

176

Center 1/4 Corner for Section 1
Set - 1 1/2" x 36" I.P. with brass cap and mkd. "PLS 752".
BTs - 34" fir stump, N.82 1/4°E., 8.4 ft.
24" fir, S.54 1/2°W., 57.1 ft. Ren. #163
Note: Position of corner as per M 94 - 64 bears S.0°00'06"W., 57.1 ft.

Donald Peel LS #752
For: Davidson Industries
November 27, 1984
M 97 - 64

177

1/4 Corner for Sections 1 and 2
Set - 1 1/2" x 36" I.P. with brass cap mkd. "PLS 752".
BTs - 37" fir, S.81 1/2°E., 62.6 ft.
31" fir, S.57 1/2°W., 53.3 ft.
Note: Position of cor. per M94-64 bears South, 223.95 ft. Ren. #164

178

Center 1/4 Corner for Section ~~1~~ 2
Set - 1 1/2" x 36" I.P. with brass cap mkd. "PLS 752". FOOK BY Daniel Baker 5/93 M118-6
BTs - 36" fir stump, N.67°W., 75.9 ft.
36" fir, S.32°W., 36.3 ft. Ren. #
Note: Position of cor. as per M94 - 64 bears S.0°00'02"E., 11.98 ft. 165

179

WEST 1/4 Sec. Cor. for Sec. 7 Only, (T20-10) See Ren. #103
Found - 2" iron pipe from Prochnau survey bears N.12°09'12"W., 2.14 ft. from corner set this survey. (REMOVED CAP)
Old BT's- 24" D. Fir, bears N.31°E., 50.2 ft. dist., with a healed face.
16" D. Fir, bears N.80°E., 75.2 ft. dist., with a healed face.
SET - 3 1/2" x 30" aluminum flared pipe, with aluminum cap stamped T20S R11W R10W 1/4 S7 1985 RLS 1922.

180

EAST 1/4 Sec. Cor. to sec. 13 Only.
SET - An aluminum Surv-Kap on a 5/8 in. iron rod in rock. Stamped: T20S R11W R10W 1/4 S13 1985 RLS 1922.
BT's - A 32" D. Fir, bears N.39°E., 16.1 ft. dist., scribed: 1/4 S18 BT.
12" Maple, bears S.61°E., 68.3 ft. dist., scribed X BT.

181

WEST 1/4 Sec. Corner to Section 18 Only, (T20-10)
SET - A 3 1/2" x 30" Aluminum flared pipe, with an alum. cap stamped: T20S R11W R10W 1/4 S18 1985 RLS 1922
BT's - 8" Alder, bears S.74°E., 29.7 ft. dist., bark scribed "1/4 S18" "BT"
10" D. Fir, bears S.69°W., 26.9 ft. dist., scribed X BT.
BO - Set a 3 1/2" x 30" aluminum flared pipe, with alum. cap for reference monument, stamped: RM 1/4 S18 N1-17E 40.7 ft. 1985 RLS 1922

182

EAST 1/4 Sec. Corner for Section 24 only.
SET - 3 1/2" x 30" aluminum flared pipe with alum. cap stamped: R11W T20S R10W 1/4 S24 1984 RPLS 1922
BT's - 6" D. Fir, N.46°W., 16.6 ft. dist., scribed: 1/4 S24 BT
9" D. Fir, S.43°E., 16.6 ft. dist., scribed: 1/4 S24 BT.

Michael J. Schwab, L.W. Hunnemuller
RPLS #1922 RPLS #1050
Sulphur Cadastral Survey - Siuslaw Natl. Forest
U.S. Forest Service
October, 1985
M 99 - 79 A & B