

**Douglas County Surveyor's Record of
Government Corners Renewed**

20 T. S. 11 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 91881

Donald Peel
For: Davidson Industries
inc.
De 11, 1981
M - 66

CORNER REPORT ONLY
Section Corner for Secs. 2 and 3. Also for Secs. 34 and 35 T19-11.
Found - A 2½" iron pipe with Lane Co. brass cap "1975"
A 9" fir, bears N 82°E, 13.5 ft. (closed face)
8" Alder, bears S 74°E, 28.1 ft. (bark scribed)
15" Alder, bears S 55°W, 21.3 ft. (bark scribed)
11" Alder, bears N 9° W, 28.3 ft. (bark scribed)

192

Daniel Baker LS1978
For International
Paper & Davidson
Industries
Dec. 23, 1987
M 105 - 40

1/4 Corner for Sections 4 and 5
Found - Original SW fir BT, 8" fir (now 40"), S.51½°W., 35 lks.
Set - 3/4" x 42" alum. rod and cap marked RLS 1978 T20S R11W 1/4 S5|S 4
1987".
New BTs - 34" spruce, N.23°E., 15.0 ft. "1/4 S4 BT".
40" Fir, S.51½°W., 23.1 ft. Closed face.

193

Center 1/4 Section 5
Set - 3/4" x 42" alum. rod with cap marked "RLS 1978 T20S R11W
C 1/4 ——— S5 1987"
New BTs - 9" Hemlock, N.83°E., 21.5 ft. "C 1/4 S5 BT".
13" Hemlock, S.42°W., 8.6 ft. "C 1/4 S5 BT"

194

M.C. for Sections 7; and Sec. 12 of T.20-12
(Point 1366.62 ft. southerly of point for Sec. cor for 1 and 12)
Set - 3/4" x 42" alum. rod and cap mkd. "RLS 1978 MC S12|S7 T20S R12W
R11W 1988".
30" Spruce, N.44°E., 68.5 ft. scribed MC S7 BT.
16" Alder, S.28°W., 11.8 ft. bark scribed MC S12 BT.

12/87

195

Witness Corner to West 1/4 Corner Section 7
(Point N.8°05'56"E., 100 ft. from true 1/4 cor.)
Set - 3/4" x 42" alum. rod and cap mkd. "RLS 1978 100.00' W.C. to 1/4
S7 R12W R11W 1988".
10" fir, S.59 3/4° W., 48.0 ft. scribed X BT.
10" fir, N.16¼°E., 38.3 ft. scribed X BT.

196

Daniel Baker
For: International
Paper Company and
Davidson Industries
July 1988
M 106 - 67

Center 1/4 Corner for Section 7
Set - 3/4" x 42" alum. rod and cap mkd. "RLS 1978 C 1/4 S7 T20S R11 W
1988".
27" fir, N.67°E., 46.3 ft. scribed C 1/4 S7 BT.
32" Fir, S.4°E., 58.3 ft. scribed C 1/4 S7 BT.

197

1/4 Corner for Sections 7 and 18
Found - 2½" pipe and brass cap. Ren. No. 78
60" fir stump, N.86°E., 27.0 ft.
New BTs- 15" fir, N.48°E., 19.5 ft. scribed 1/4 S7 BT.
15" fir, S.72°E., 19.8 ft. scribed 1/4 S18 BT.

198

Closing Corner for Sections 7 and 18. (West boundary)
Found - 2" very rusted pipe. Ren. No. 90
35" spruce, N.45°E., 30.5 ft.
54" fir stump, N.52°E., 108.0 ft.
32" dead spruce, S.61½°E., 62.0 ft.
Set - 3/4" x 42" alum. rod and cap mkd. RLS 1978 T20S S13|S7/S18 R12W
R11W 1988".

199

7/88