

**Douglas County Surveyor's Record of
Government Corners Renewed**

20 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner for sections 23 and 26. 200
 Found - 3" alum. cap on 2½" alum pipe.
 BTs - 16" alder, bark scribed bears S.52°E., 52.4 ft.
 11" alder, bark scribed, bears N.7°W., 33.6 ft. Ren No. 131
 New BTs 12.5" alder, bark scribed "T20S R11W S1/4 S23 BT" with tags
 and washer, bears N.47°E., 24.97 ft.
 10.5" alder, bark scribed "T20S R11W N1/4 S26 BT" with tags
 and washer, bears S.50°W., 47.15 ft.
 Set - Reference monument, Std. U.S.F.S. Disk: "RM N 1/4 S26 N.0°19'W
 50.98 1990 RLS 2244" bears S.0° 19'E.50.98 ft.
 Note - Distances are to side center of bearing trees. 12/90

1/4 Corner for sections 25 and 26. 201
 Found - Original bearing trees,
 Rotten fir stump bears N.16°W., 13.2 ft. to face.
 Rotten fir stump bears N.18°E., 30.4 ft. to face.
 Set - 3" alum. cap on 2½" X 30" alum. pipe mkd. USDA Forest Service.
 BTs - 89" fir, face scribed, "W1/4 S25 BT", tags and washers
 Mkd. bears S.61°E., 37.89 ft.
 40" maple, face scribed, "E 1/4 S26 BT" tags and washer,
 bears S.6°15'W., 26.61'.
 27" maple face scribed "E1/4 S26 BT" tags and washer,
 bears N.86°15'W., 40.01 ft.
 44" fir face scribed "W1/4 S25 BT" tags and washer,
 bears N.14°45'E., 48.31'.
 Note - All distances are to the side center of the bearing trees. 12/90

202

Section Corner for Sections 25, 26, 35 & 36.
 Set - 3" alum. cap mkd. U.S.D.A. Forest Service, on 2½" X 30" alum pipe.
 BTs - 38" douglas fir, face scribed, "T20S R11W S25 BT" tags and
 Mkd. washer, BEARS N.25°15'E., 39.45 ft.
 16" douglas fir, face scribed, "T20S R11W S36 BT" tags and washer,
 bears S.76°30'E., 13.77 ft.
 40" douglas fir, school marm, face scribed "T20S R11W S26 BT"
 bears N.20°30'W., 3.12 ft.
 Ref. Mon - Std U.S.F.S Disk mkd. "RM T20S R11W S26 S.83°11'E, 40.56'
 1990 RLS 2244" bears N.83°11'W., 40.56 ft.
 Note - Distances are to side center of bearing trees. 12/90

1/4 Corner for Sections 26 and 35 203
 Found - 2½" brass cap on 1½" O.D. iron pipe, 12" above ground, along
 side 2" O.D. iron pipe. Ren. No. 72
 Fnd BTs- 20" maple, healed face, bears N.69°E., 74.8 ft. (rec 76')
 12" maple, healed face, bears S38°W., 93.2 ft. (rec 96')
 Mkd BT - 13" alder, bark scribed "T20S R11W S1/4S26BT" tags
 bears, N.7°30'W., 14.10 ft
 Mkd BO - Rock 2.65 ft high, 4.5 ft. long, 2.4 ft. wide with "X"
 bears N.78°E., 3.79 ft.
 Note - All distances are to the side center of the bearing trees. 12/90

204

Center 1/4 for Section 26.
 Set - 3" alum. cap mkd. U.S.F.S. on 2½" X 30 " alum. pipe.
 BTs - 16" douglas fir, face scribed "C1/4 S26 BT" tags and washer,
 Mkd. bears N.48°15'E., 17.36 ft.
 22" douglas fir, face scribed "C1/4 S26 BT" tags and washer,
 bears S.32°E., 12.53 ft.
 15" douglas fir, face scribed "C1/4 S26 BT" tags and washer,
 bears S.64°W., 27.54 ft.
 Set RM - Std. U.S.F.S disk "RM C1/4 S26 S00°28'E., 51.00 1990 RLS 2244"
 bears N.0° 28'W., 51.00 ft.
 Note - Distances are to the side center of the bearing trees. 12/90

Harvey Wilcox
 For: U.S. Forest Service
 RLS No. 2244
 Dec. 1990 FILED 1991
 M 111 - 47 A - F