

**Douglas County Surveyor's Record of  
Government Corners Renewed**

20 T. S. 11 R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 21881

Center 1/4 for Section 35.

205

Set - 3" alum. cap mkd. U.S.F.S., on 2½" X 30" alum pipe.  
BTs Mkd- 25" douglas fir, face scribed "C1/4 S35 BT" tags and washer,  
bears N.22° 45'E., 90.63 ft. to side center.  
BO Mkd- P.K. nail with washer in rock face with tag,  
bears N.42°30'W., 112.96 ft.  
Power pole No. 10-121 with tag, bears N.68°W., 113.88 ft.  
Set RM- Std. U.S.F.S. disk mkd. "RM C1/4 S35 S.0°12'W.63.18' 1990  
RLS 2244" bears N.0°12'E., 63.18 ft.

12/90

1/4 Corner for Sections 35 and 36.

206

Set - 3" alum. cap mkd. U.S.F.S. on 2½" X 30" alum. pipe.  
BTs Mkd- 22" douglas fir, face scribed "E1/4 S35 BT" tags and washer  
bears N.20°30'W., 61.00 ft. to side center of tree.  
31" douglas fir, face scribed "W1/4 S36 BT" tags and washer  
bears N.3°E., 21.25 ft. to side center.  
31" douglas fir, face scribed "W1/4 S36 BT" tags and washer  
bears S.45°E., 6.10 ft. to side center.  
BO Mkd.-5 ft. high rock face, with P.K. nail and washer in the center  
of an "X", with tag, bears N.58°W., 18.60 ft.

12/90

Section Corner for Sec's 25 and 36; and sec's 30 and 31 of T.20 R.10.

207

Found - 2½" brass cap on 2½" IP. 14" above ground, with 1" IP. alongside.  
BTs Fnd.- Original BT 32" maple, rotten face, tags, bears N.29°W., 25.3 ft.  
17" cedar, healed face, tags, bears N.20°W., 47.3' Ren # 184  
76" spruce, visible scribe, tags, bears S.72°45'E., 74.3 ft.  
Cascara, dead, tags, bears S.72°E., 27.6 ft.  
65" douglas fir, visible scribe, tags, bears S.18°W., 70.3 ft.  
Set RM. - Std. U.S.F.S. disk "RM T20S R10W S30 S.88°20'W 43.40'  
1990 RLS 2244" Bears N.88°20'E., 43.4 ft.

12/90

Center 1/4 for Section 36.

208

Set - 3" alum. cap mkd. U.S.F.S. on 2½" X 30" alum. pipe.  
BTs Mkd - 27" douglas fir, face scribed, "C1/4 S36 BT" tags and washer  
bears N.60°15'W., 26.13 ft. to side center.  
7" douglas fir, face scribed, "C1/4 S36 BT" tags and washer  
bears S.24°15'W., 5.85 ft. to side center.  
46" cedar, face scribed "C1/4 S36 BT" tags and washer  
bears N.87°30'E., 90.57 ft. to side center.  
Set RM. - Std. U.S.F.S. disk "RM C1/4 S36 S89°52'W, 73.15' 1990 RLS 2244"  
bears N.89°52'E., 73.15 ft.

12/90

South East Corner for Section 36.

209

Found - 2½" brass cap on 1½" IP 12" above ground, with 1" IP along side.  
BTs Fnd.- 30" maple S.E. trunk of tree with healed face, tags,  
bears N.14°W., 15.2 ft. to side center. Ren. # 48  
21" douglas fir, healed face, tags, bears N.80°E., 83.6 ft. sde/cent  
37" douglas fir, healed face, tags, bears S.77°15'E., 42.9 ft.  
39" maple, healed face, tags, bears S.27°W., 11.2 ft. to side cen.  
Note - This tree trunk has blown down (39" maple) Retagged another  
trunk of the same tree, it bears S.25°30'W., 14.20 ft.  
Set RM - Std. U.S.F.S. disk "RM T20S R10W S31 S88°09'W 52.91' 1990RLS 2244"  
bears N.88°09'E., 52.91 ft.

12/90

West 1/4 Corner for Section 22

210

Found - 1964 Douglas County Brass Cap lying on the ground. Reset brass  
cap from 1964 Douglas County bearing tree. See Renewal # 37  
BTs Fnd - 10" hemlock snag, S.85°E., 76.0 ft. (scribe visible)  
14" hemlock snag, S.16°W., 46.8 ft. (scribe visible)  
BTs Mkd - 7" hemlock, N.63°E., 29.1 ft. Scribed 1/4 S22 BT. (painted red)  
10" fir N.76°W., 36.6 ft. Scribed 1/4 S21 BT. (painted red)  
Note - Corner lies on steep north slope about 50 ft. north of  
east-west ridge.

1/92

Harvey Wilcox RLS 2244  
For: U.S. Forest Service  
December 1990 FILED 1991  
M 111 - 47 A - F

FD. OR 2/92 STUNTNER M/M-80

Les Roberts  
For: Int. Paper &  
Champion Int.  
Nov. 1991  
M 114-29 C.S.63/138